



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Caps

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|------------------------|-------|--------|----------|-----------|--------|
| Cap (continued) | | | | | |
| Fipt | | | | | |
| 448-012 | 1-1/4 | 25 | 100 | 040 | 2.80 |
| 448-015 | 1-1/2 | 25 | 100 | 040 | 2.93 |
| 448-020 | 2 | 10 | 120 | 040 | 5.18 |
| 448-025 | 2-1/2 | 10 | 0 | 040 | 7.63 |
| 448-030 | 3 | 10 | 0 | 040 | 9.98 |
| 448-040 | 4 | 6 | 0 | 040 | 17.52 |
| 448-050 | 5 | 5 | 0 | 040 | 33.94 |
| 448-060 | 6 | 8 | 0 | 040 | 41.41 |
| 448-080F | 8 | 1 | 2 | 047 | 202.08 |
| 448-100F | 10 | 1 | 2 | 047 | 410.66 |
| 448-120F | 12 | 1 | 0 | 047 | 820.54 |

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

| | | | | | |
|-----------|-------|----|-----|-----|------|
| 448-012SR | 1-1/4 | 25 | 100 | 046 | 7.46 |
|-----------|-------|----|-----|-----|------|

Plugs

Plug

Spigot

| | | | | | |
|-----------------------|-------|----|------|-----|---------|
| 449-003 | 3/8 | 50 | 700 | 040 | 1.93 |
| 449-005 | 1/2 | 50 | 1000 | 040 | 1.56 |
| 449-007 | 3/4 | 50 | 300 | 040 | 1.82 |
| 449-010 | 1 | 50 | 200 | 040 | 2.19 |
| 449-012 | 1-1/4 | 25 | 150 | 040 | 2.93 |
| 449-015 | 1-1/2 | 25 | 100 | 040 | 3.73 |
| 449-020 | 2 | 10 | 120 | 040 | 4.61 |
| 449-025 | 2-1/2 | 10 | 0 | 040 | 7.91 |
| 449-030 | 3 | 10 | 0 | 040 | 10.43 |
| 449-040 | 4 | 6 | 0 | 040 | 23.61 |
| 449-060 | 6 | 6 | 0 | 040 | 31.97 |
| 449-060F ⁴ | 6 | 1 | 6 | 047 | 80.88 |
| 449-080F ⁴ | 8 | 1 | 6 | 047 | 124.54 |
| 449-100F ⁴ | 10 | 1 | 0 | 047 | 285.88 |
| 449-120F ⁴ | 12 | 1 | 0 | 047 | 467.44 |
| 449-140F ⁴ | 14 | 1 | 2 | 047 | 512.45 |
| 449-160F ⁴ | 16 | 1 | 0 | 047 | 566.69 |
| 449-180F ⁴ | 18 | 1 | 0 | 047 | 1011.28 |
| 449-200F ⁴ | 20 | 1 | 0 | 047 | 1850.11 |
| 449-240F ⁴ | 24 | 1 | 0 | 047 | 2462.74 |

⁴ Plug fabricated using Cap and pipe spigot.

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Plug - Counter Sunk

Spigot

| | | | | | |
|-----------|-----|----|-----|-----|------|
| 449-007CS | 3/4 | 50 | 300 | 040 | 1.82 |
| 449-010CS | 1 | 50 | 300 | 040 | 2.19 |

Plug

Mipt

| | | | | | |
|-----------------------|-------|----|-----|-----|--------|
| 450-003 | 3/8 | 50 | 700 | 040 | 2.09 |
| 450-005 | 1/2 | 50 | 300 | 040 | 1.93 |
| 450-007 | 3/4 | 50 | 300 | 040 | 2.07 |
| 450-010 | 1 | 50 | 300 | 040 | 3.37 |
| 450-012 | 1-1/4 | 25 | 300 | 040 | 3.55 |
| 450-015 | 1-1/2 | 25 | 150 | 040 | 3.81 |
| 450-020 | 2 | 10 | 120 | 040 | 4.92 |
| 450-025 | 2-1/2 | 10 | 80 | 040 | 6.83 |
| 450-030 | 3 | 10 | 0 | 040 | 10.35 |
| 450-040 | 4 | 6 | 0 | 040 | 23.35 |
| 450-060 | 6 | 6 | 0 | 040 | 68.45 |
| 450-080 | 8 | 6 | 0 | 040 | 83.64 |
| 450-080F ⁴ | 8 | 1 | 4 | 047 | 181.47 |
| 450-100F ⁴ | 10 | 1 | 3 | 047 | 361.62 |
| 450-120F ⁴ | 12 | 1 | 0 | 047 | 504.85 |

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

| | | | | | |
|-----------------------|-------|----|-----|-----|---------|
| 475-005 | 1/2 | 25 | 100 | 040 | 3.06 |
| 475-007 | 3/4 | 20 | 0 | 040 | 4.80 |
| 475-010 | 1 | 25 | 0 | 040 | 6.72 |
| 475-012 | 1-1/4 | 20 | 0 | 040 | 10.33 |
| 475-015 | 1-1/2 | 20 | 0 | 040 | 13.24 |
| 475-020 | 2 | 10 | 0 | 040 | 39.73 |
| 475-025 | 2-1/2 | 8 | 0 | 040 | 90.81 |
| 475-030 | 3 | 5 | 0 | 040 | 66.93 |
| 475-040 | 4 | 4 | 0 | 040 | 126.23 |
| 475-050F | 5 | 1 | 3 | 047 | 492.59 |
| 475-060 | 6 | 3 | 0 | 040 | 267.06 |
| 475-080 | 8 | 1 | 0 | 040 | 429.55 |
| 475-100 | 10 | 1 | 0 | 041 | 1423.35 |
| 475-100F ² | 10 | 1 | 0 | 047 | 1194.36 |

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|------------------------------------|------|--------|----------|-----------|---------|
| Wye (continued) | | | | | |
| Socket x Socket x Socket | | | | | |
| 475-120 | 12 | 1 | 0 | 041 | 2103.07 |
| 475-120F ² | 12 | 1 | 0 | 047 | 1623.62 |
| 475-140F ² | 14 | 1 | 0 | 047 | 2300.25 |
| 475-160F ² | 16 | 1 | 0 | 047 | 2973.35 |
| 475-180F ² | 18 | 1 | 0 | 047 | 3806.94 |
| 475-200F ² | 20 | 1 | 0 | 047 | 4500.87 |
| 475-240F ² | 24 | 1 | 0 | 047 | 5597.64 |
| ¹ Sized with Bushing | | | | | |
| ² Fiberglass reinforced | | | | | |



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

| | | | | | |
|-----------------------|-------------|----|---|-----|--------|
| 475-101 ¹ | 3/4X1/2 | 20 | 0 | 040 | 9.46 |
| 475-130 ¹ | 1X1/2 | 20 | 0 | 040 | 12.03 |
| 475-131 ¹ | 1X3/4 | 20 | 0 | 040 | 12.03 |
| 475-166 ¹ | 1-1/4X1/2 | 20 | 0 | 040 | 16.19 |
| 475-167 ¹ | 1-1/4X3/4 | 20 | 0 | 040 | 16.19 |
| 475-168 ¹ | 1-1/4X1 | 20 | 0 | 040 | 16.19 |
| 475-209 ¹ | 1-1/2X1/2 | 20 | 0 | 040 | 19.27 |
| 475-210 ¹ | 1-1/2X3/4 | 20 | 0 | 040 | 19.27 |
| 475-211 ¹ | 1-1/2X1 | 20 | 0 | 040 | 19.27 |
| 475-212 ¹ | 1-1/2X1-1/4 | 20 | 0 | 040 | 19.27 |
| 475-247 ¹ | 2X1/2 | 10 | 0 | 040 | 43.78 |
| 475-248 ¹ | 2X3/4 | 10 | 0 | 040 | 43.78 |
| 475-249 ¹ | 2X1 | 10 | 0 | 040 | 43.78 |
| 475-250 ¹ | 2X1-1/4 | 10 | 0 | 040 | 43.78 |
| 475-251 ¹ | 2X1-1/2 | 10 | 0 | 040 | 43.78 |
| 475-292 ¹ | 2-1/2X2 | 4 | 0 | 040 | 97.54 |
| 475-334 ¹ | 3X3/4 | 5 | 0 | 040 | 76.01 |
| 475-335 ¹ | 3X1 | 5 | 0 | 040 | 76.01 |
| 475-336 ¹ | 3X1-1/4 | 5 | 0 | 040 | 76.01 |
| 475-337 ¹ | 3X1-1/2 | 5 | 0 | 040 | 76.01 |
| 475-338 ¹ | 3X2 | 5 | 0 | 040 | 76.01 |
| 475-339 ¹ | 3X2-1/2 | 5 | 0 | 040 | 76.01 |
| 475-420 | 4X2 | 4 | 0 | 040 | 146.02 |
| 475-421 ¹ | 4X2-1/2 | 4 | 0 | 040 | 146.02 |
| 475-422 ¹ | 4X3 | 4 | 0 | 040 | 146.02 |
| 475-488F ² | 5X3 | 1 | 4 | 047 | 391.79 |
| 475-490F ² | 5X4 | 1 | 4 | 047 | 407.98 |
| 475-528 ¹ | 6X2 | 4 | 0 | 040 | 315.16 |
| 475-529 ¹ | 6X2-1/2 | 5 | 0 | 040 | 315.16 |
| 475-530 ¹ | 6X3 | 5 | 0 | 040 | 315.16 |
| 475-532 | 6X4 | 5 | 0 | 040 | 343.37 |
| 475-578F ² | 8X2 | 1 | 2 | 047 | 589.71 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|------|--------|----------|-----------|------|
|-------------|------|--------|----------|-----------|------|

Wye - Reducing (continued)
Socket x Socket x Socket

| | | | | | |
|-----------------------|----------|---|---|-----|---------|
| 475-579F ² | 8X2-1/2 | 1 | 0 | 047 | 625.78 |
| 475-580F ² | 8X3 | 1 | 2 | 047 | 640.72 |
| 475-582 | 8X4 | 2 | 0 | 040 | 588.16 |
| 475-582F ² | 8X4 | 1 | 2 | 047 | 660.88 |
| 475-585F ² | 8X6 | 1 | 0 | 047 | 680.92 |
| 475-621F ² | 10X2 | 1 | 0 | 047 | 708.88 |
| 475-622F ² | 10X2-1/2 | 1 | 0 | 047 | 721.07 |
| 475-623F ² | 10X3 | 1 | 0 | 047 | 759.57 |
| 475-624F ² | 10X4 | 1 | 0 | 047 | 803.80 |
| 475-626 | 10X6 | 1 | 0 | 041 | 1219.77 |
| 475-626F ² | 10X6 | 1 | 0 | 047 | 887.55 |
| 475-628 | 10X8 | 1 | 0 | 041 | 1355.31 |
| 475-628F ² | 10X8 | 1 | 0 | 047 | 949.68 |
| 475-661F ² | 12X2 | 1 | 0 | 047 | 962.24 |
| 475-663F ² | 12X3 | 1 | 0 | 047 | 985.20 |
| 475-664F ² | 12X4 | 1 | 0 | 047 | 1031.08 |
| 475-666F ² | 12X6 | 1 | 0 | 047 | 1036.03 |
| 475-668F ² | 12X8 | 1 | 0 | 047 | 1201.47 |
| 475-670F ² | 12X10 | 1 | 0 | 047 | 1373.74 |
| 475-691F ² | 14X2 | 1 | 0 | 047 | 1143.87 |
| 475-693F ² | 14X3 | 1 | 0 | 047 | 1238.07 |
| 475-694F ² | 14X4 | 1 | 0 | 047 | 1298.40 |
| 475-696F ² | 14X6 | 1 | 0 | 047 | 1462.85 |
| 475-698F ² | 14X8 | 1 | 0 | 047 | 1676.18 |
| 475-700F ² | 14X10 | 1 | 0 | 047 | 1872.38 |
| 475-702F ² | 14X12 | 1 | 0 | 047 | 2097.78 |
| 475-751F ² | 16X2 | 1 | 0 | 047 | 1328.99 |
| 475-753F ² | 16X3 | 1 | 0 | 047 | 1436.66 |
| 475-754F ² | 16X4 | 1 | 0 | 047 | 1494.04 |
| 475-756F ² | 16X6 | 1 | 0 | 047 | 1681.27 |
| 475-758F ² | 16X8 | 1 | 0 | 047 | 1914.67 |
| 475-760F ² | 16X10 | 1 | 0 | 047 | 2130.99 |
| 475-762F ² | 16X12 | 1 | 0 | 047 | 2374.69 |
| 475-764F ² | 16X14 | 1 | 0 | 047 | 2687.81 |
| 475-781F ² | 18X2 | 1 | 0 | 047 | 1450.05 |
| 475-783F ² | 18X3 | 1 | 0 | 047 | 1516.42 |
| 475-784F ² | 18X4 | 1 | 0 | 047 | 1538.94 |
| 475-786F ² | 18X6 | 1 | 0 | 047 | 2948.51 |
| 475-788F ² | 18X8 | 1 | 0 | 047 | 2200.54 |
| 475-790F ² | 18X10 | 1 | 0 | 047 | 2447.64 |
| 475-792F ² | 18X12 | 1 | 0 | 047 | 2839.49 |
| 475-794F ² | 18X14 | 1 | 0 | 047 | 3117.60 |
| 475-796F ² | 18X16 | 1 | 0 | 047 | 3269.62 |
| 475-811F ² | 20X2 | 1 | 0 | 047 | 1524.76 |
| 475-813F ² | 20X3 | 1 | 0 | 047 | 1652.33 |
| 475-814F ² | 20X4 | 1 | 0 | 047 | 1673.73 |
| 475-816F ² | 20X6 | 1 | 0 | 047 | 1705.13 |
| 475-818F ² | 20X8 | 1 | 0 | 047 | 2304.93 |
| 475-820F ² | 20X10 | 1 | 0 | 047 | 2562.40 |
| 475-822F ² | 20X12 | 1 | 0 | 047 | 3088.08 |
| 475-824F ² | 20X14 | 1 | 0 | 047 | 3455.95 |
| 475-826F ² | 20X16 | 1 | 0 | 047 | 3830.55 |
| 475-828F ² | 20X18 | 1 | 0 | 047 | 4111.78 |
| 475-901F ² | 24X2 | 1 | 0 | 047 | 1924.67 |



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Wyes

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|------------------------------------|-------|--------|----------|-----------|---------|
| Wye - Reducing (continued) | | | | | |
| Socket x Socket x Socket | | | | | |
| 475-903F ² | 24X3 | 1 | 0 | 047 | 1967.01 |
| 475-904F ² | 24X4 | 1 | 0 | 047 | 2021.23 |
| 475-906F ² | 24X6 | 1 | 0 | 047 | 3557.57 |
| 475-908F ² | 24X8 | 1 | 0 | 047 | 3880.76 |
| 475-910F ² | 24X10 | 1 | 0 | 047 | 3921.75 |
| 475-912F ² | 24X12 | 1 | 0 | 047 | 4151.32 |
| 475-914F ² | 24X14 | 1 | 0 | 047 | 4293.75 |
| 475-916F ² | 24X16 | 1 | 0 | 047 | 4496.60 |
| 475-918F ² | 24X18 | 1 | 0 | 047 | 4888.34 |
| 475-920F ² | 24X20 | 1 | 0 | 047 | 5343.36 |
| ¹ Sized with Bushing | | | | | |
| ² Fiberglass reinforced | | | | | |



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|--|------|--------|----------|-----------|---------|
| 476-020F ² | 2 | 1 | 4 | 047 | 308.51 |
| 476-030F ² | 3 | 1 | 3 | 047 | 508.15 |
| 476-040F ² | 4 | 1 | 2 | 047 | 566.03 |
| 476-060F ² | 6 | 1 | 0 | 047 | 644.61 |
| 476-080F ² | 8 | 1 | 0 | 047 | 785.02 |
| 476-100F ² | 10 | 1 | 0 | 047 | 1439.52 |
| 476-120F ² | 12 | 1 | 0 | 047 | 1713.76 |
| 476-140F ² | 14 | 1 | 0 | 047 | 2494.22 |
| ² Fiberglass reinforced | | | | | |
| For larger sizes please contact your Regional Spears® Distribution Center. | | | | | |



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-----------------------|----------|--------|----------|-----------|--------|
| 476-338 | 3X2 | 5 | 0 | 040 | 111.56 |
| 476-420F ² | 4X2 | 1 | 4 | 047 | 501.11 |
| 476-421F ² | 4X2-1/2 | 1 | 2 | 047 | 522.82 |
| 476-422F ² | 4X3 | 1 | 3 | 047 | 537.86 |
| 476-528F ² | 6X2 | 1 | 2 | 047 | 504.61 |
| 476-529F ² | 6X2-1/2 | 1 | 2 | 047 | 549.35 |
| 476-530F ² | 6X3 | 1 | 2 | 047 | 570.94 |
| 476-532F ² | 6X4 | 1 | 0 | 047 | 579.86 |
| 476-578F ² | 8X2 | 1 | 2 | 047 | 615.60 |
| 476-579F ² | 8X2-1/2 | 1 | 2 | 047 | 640.07 |
| 476-580F ² | 8X3 | 1 | 0 | 047 | 688.80 |
| 476-582F ² | 8X4 | 1 | 0 | 047 | 697.66 |
| 476-585F ² | 8X6 | 1 | 0 | 047 | 731.40 |
| 476-621F ² | 10X2 | 1 | 0 | 047 | 917.19 |
| 476-622F ² | 10X2-1/2 | 1 | 0 | 047 | 971.76 |

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|--|----------|--------|----------|-----------|---------|
| Double Wye - Reducing (continued) | | | | | |
| Socket x Socket x Socket x Socket | | | | | |
| 476-623F ² | 10X3 | 1 | 0 | 047 | 999.62 |
| 476-624F ² | 10X4 | 1 | 0 | 047 | 1098.34 |
| 476-626F ² | 10X6 | 1 | 0 | 047 | 1232.00 |
| 476-628F ² | 10X8 | 1 | 0 | 047 | 1284.72 |
| 476-661F ² | 12X2 | 1 | 0 | 047 | 1308.55 |
| 476-662F ² | 12X2 1/2 | 1 | 0 | 047 | 1323.40 |
| 476-663F ² | 12X3 | 1 | 0 | 047 | 1394.43 |
| 476-664F ² | 12X4 | 1 | 0 | 047 | 1421.66 |
| 476-666F ² | 12X6 | 1 | 0 | 047 | 1502.33 |
| 476-668F ² | 12X8 | 1 | 0 | 047 | 1540.86 |
| 476-670F ² | 12X10 | 1 | 0 | 047 | 1632.39 |
| 476-756F | 16X6 | 1 | 0 | 047 | 2742.91 |
| 476-786F | 18X6 | 1 | 0 | 047 | 1536.64 |
| ² Fiberglass reinforced | | | | | |
| For larger sizes please contact your Regional Spears® Distribution Center. | | | | | |

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|-------|--------|----------|-----------|--------|
| 457-005 | 1/2 | 20 | 120 | 040 | 6.99 |
| 457-007 | 3/4 | 15 | 90 | 040 | 7.95 |
| 457-010 | 1 | 10 | 60 | 040 | 8.19 |
| 457-012 | 1-1/4 | 5 | 30 | 040 | 26.38 |
| 457-015 | 1-1/2 | 5 | 20 | 040 | 27.46 |
| 457-020 | 2 | 5 | 0 | 040 | 37.06 |
| 457-025 | 2-1/2 | 5 | 0 | 040 | 51.87 |
| 457-030 | 3 | 5 | 0 | 040 | 82.85 |
| 457-040 | 4 | 4 | 0 | 040 | 114.72 |
| 457-060 | 6 | 1 | 0 | 040 | 254.91 |



Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

| Part Number | Size | Std Pk | Mstr Ctn | Prod Code | MSRP |
|-------------|-------|--------|----------|-----------|--------|
| 497-005 | 1/2 | 20 | 120 | 040 | 7.69 |
| 497-007 | 3/4 | 15 | 90 | 040 | 8.80 |
| 497-010 | 1 | 10 | 60 | 040 | 8.99 |
| 497-012 | 1-1/4 | 5 | 30 | 040 | 29.01 |
| 497-015 | 1-1/2 | 5 | 20 | 040 | 30.24 |
| 497-020 | 2 | 5 | 0 | 040 | 40.78 |
| 497-025 | 2-1/2 | 5 | 0 | 040 | 57.08 |
| 497-030 | 3 | 5 | 0 | 040 | 91.04 |
| 497-040 | 4 | 4 | 0 | 040 | 122.48 |
| 497-060 | 6 | 1 | 0 | 040 | 272.18 |

