



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
Cap (continued)				
Fipt				
448-012	1-1/4	25	100	040
448-015	1-1/2	25	100	040
448-020	2	10	120	040
448-025	2-1/2	10	0	040
448-030	3	10	0	040
448-040	4	6	0	040
448-050	5	5	0	040
448-060	6	8	0	040
448-080F	8	1	2	047
448-100F	10	1	2	047
448-120F	12	1	0	047

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046
-----------	-------	----	-----	-----

Plugs

Plug

Spigot

449-003	3/8	50	700	040
449-005	1/2	50	1000	040
449-007	3/4	50	300	040
449-010	1	50	200	040
449-012	1-1/4	25	150	040
449-015	1-1/2	25	100	040
449-020	2	10	120	040
449-025	2-1/2	10	0	040
449-030	3	10	0	040
449-040	4	6	0	040
449-060	6	6	0	040
449-060F ⁴	6	1	6	047
449-080F ⁴	8	1	6	047
449-100F ⁴	10	1	0	047
449-120F ⁴	12	1	0	047
449-140F ⁴	14	1	2	047
449-160F ⁴	16	1	0	047
449-180F ⁴	18	1	0	047
449-200F ⁴	20	1	0	047
449-240F ⁴	24	1	0	047

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
-------------	------	--------	----------	-----------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040
449-010CS	1	50	300	040

Plug

Mipt

450-003	3/8	50	700	040
450-005	1/2	50	300	040
450-007	3/4	50	300	040
450-010	1	50	300	040
450-012	1-1/4	25	300	040
450-015	1-1/2	25	150	040
450-020	2	10	120	040
450-025	2-1/2	10	80	040
450-030	3	10	0	040
450-040	4	6	0	040
450-060	6	6	0	040
450-080	8	6	0	040
450-080F ⁴	8	1	4	047
450-100F ⁴	10	1	3	047
450-120F ⁴	12	1	0	047

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6"-150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040
475-007	3/4	20	0	040
475-010	1	25	0	040
475-012	1-1/4	20	0	040
475-015	1-1/2	20	0	040
475-020	2	10	0	040
475-025	2-1/2	8	0	040
475-030	3	5	0	040
475-040	4	4	0	040
475-050F	5	1	3	047
475-060	6	3	0	040
475-080	8	1	0	040
475-100	10	1	0	041
475-100F ²	10	1	0	047

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
Wye (continued)				
Socket x Socket x Socket				
475-120	12	1	0	041
475-120F ²	12	1	0	047
475-140F ²	14	1	0	047
475-160F ²	16	1	0	047
475-180F ²	18	1	0	047
475-200F ²	20	1	0	047
475-240F ²	24	1	0	047
¹ Sized with Bushing				
² Fiberglass reinforced				



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-101 ¹	3/4X1/2	20	0	040
475-130 ¹	1X1/2	20	0	040
475-131 ¹	1X3/4	20	0	040
475-166 ¹	1-1/4X1/2	20	0	040
475-167 ¹	1-1/4X3/4	20	0	040
475-168 ¹	1-1/4X1	20	0	040
475-209 ¹	1-1/2X1/2	20	0	040
475-210 ¹	1-1/2X3/4	20	0	040
475-211 ¹	1-1/2X1	20	0	040
475-212 ¹	1-1/2X1-1/4	20	0	040
475-247 ¹	2X1/2	10	0	040
475-248 ¹	2X3/4	10	0	040
475-249 ¹	2X1	10	0	040
475-250 ¹	2X1-1/4	10	0	040
475-251 ¹	2X1-1/2	10	0	040
475-292 ¹	2-1/2X2	4	0	040
475-334 ¹	3X3/4	5	0	040
475-335 ¹	3X1	5	0	040
475-336 ¹	3X1-1/4	5	0	040
475-337 ¹	3X1-1/2	5	0	040
475-338 ¹	3X2	5	0	040
475-339 ¹	3X2-1/2	5	0	040
475-420	4X2	4	0	040
475-421 ¹	4X2-1/2	4	0	040
475-422 ¹	4X3	4	0	040
475-488F ²	5X3	1	4	047
475-490F ²	5X4	1	4	047
475-528 ¹	6X2	4	0	040
475-529 ¹	6X2-1/2	5	0	040
475-530 ¹	6X3	5	0	040
475-532	6X4	5	0	040
475-578F ²	8X2	1	2	047

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
-------------	------	--------	----------	-----------

Wye - Reducing (continued)
Socket x Socket x Socket

475-579F ²	8X2-1/2	1	0	047
475-580F ²	8X3	1	2	047
475-582	8X4	2	0	040
475-582F ²	8X4	1	2	047
475-585F ²	8X6	1	0	047
475-621F ²	10X2	1	0	047
475-622F ²	10X2-1/2	1	0	047
475-623F ²	10X3	1	0	047
475-624F ²	10X4	1	0	047
475-626	10X6	1	0	041
475-626F ²	10X6	1	0	047
475-628	10X8	1	0	041
475-628F ²	10X8	1	0	047
475-661F ²	12X2	1	0	047
475-663F ²	12X3	1	0	047
475-664F ²	12X4	1	0	047
475-666F ²	12X6	1	0	047
475-668F ²	12X8	1	0	047
475-670F ²	12X10	1	0	047
475-691F ²	14X2	1	0	047
475-693F ²	14X3	1	0	047
475-694F ²	14X4	1	0	047
475-696F ²	14X6	1	0	047
475-698F ²	14X8	1	0	047
475-700F ²	14X10	1	0	047
475-702F ²	14X12	1	0	047
475-751F ²	16X2	1	0	047
475-753F ²	16X3	1	0	047
475-754F ²	16X4	1	0	047
475-756F ²	16X6	1	0	047
475-758F ²	16X8	1	0	047
475-760F ²	16X10	1	0	047
475-762F ²	16X12	1	0	047
475-764F ²	16X14	1	0	047
475-781F ²	18X2	1	0	047
475-783F ²	18X3	1	0	047
475-784F ²	18X4	1	0	047
475-786F ²	18X6	1	0	047
475-788F ²	18X8	1	0	047
475-790F ²	18X10	1	0	047
475-792F ²	18X12	1	0	047
475-794F ²	18X14	1	0	047
475-796F ²	18X16	1	0	047
475-811F ²	20X2	1	0	047
475-813F ²	20X3	1	0	047
475-814F ²	20X4	1	0	047
475-816F ²	20X6	1	0	047
475-818F ²	20X8	1	0	047
475-820F ²	20X10	1	0	047
475-822F ²	20X12	1	0	047
475-824F ²	20X14	1	0	047
475-826F ²	20X16	1	0	047
475-828F ²	20X18	1	0	047
475-901F ²	24X2	1	0	047



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
-------------	------	--------	----------	-----------

Wye - Reducing (continued)
Socket x Socket x Socket

475-903F ²	24X3	1	0	047
475-904F ²	24X4	1	0	047
475-906F ²	24X6	1	0	047
475-908F ²	24X8	1	0	047
475-910F ²	24X10	1	0	047
475-912F ²	24X12	1	0	047
475-914F ²	24X14	1	0	047
475-916F ²	24X16	1	0	047
475-918F ²	24X18	1	0	047
475-920F ²	24X20	1	0	047

¹ Sized with Bushing
² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047
476-030F ²	3	1	3	047
476-040F ²	4	1	2	047
476-060F ²	6	1	0	047
476-080F ²	8	1	0	047
476-100F ²	10	1	0	047
476-120F ²	12	1	0	047
476-140F ²	14	1	0	047

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040
476-420F ²	4X2	1	4	047
476-421F ²	4X2-1/2	1	2	047
476-422F ²	4X3	1	3	047
476-528F ²	6X2	1	2	047
476-529F ²	6X2-1/2	1	2	047
476-530F ²	6X3	1	2	047
476-532F ²	6X4	1	0	047
476-578F ²	8X2	1	2	047
476-579F ²	8X2-1/2	1	2	047
476-580F ²	8X3	1	0	047
476-582F ²	8X4	1	0	047
476-585F ²	8X6	1	0	047
476-621F ²	10X2	1	0	047
476-622F ²	10X2-1/2	1	0	047

Part Number	Size	Std Pk	Mstr Ctn	Prod Code
-------------	------	--------	----------	-----------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047
476-624F ²	10X4	1	0	047
476-626F ²	10X6	1	0	047
476-628F ²	10X8	1	0	047
476-661F ²	12X2	1	0	047
476-662F ²	12X2 1/2	1	0	047
476-663F ²	12X3	1	0	047
476-664F ²	12X4	1	0	047
476-666F ²	12X6	1	0	047
476-668F ²	12X8	1	0	047
476-670F ²	12X10	1	0	047
476-756F	16X6	1	0	047
476-786F	18X6	1	0	047

² Fiberglass reinforced
For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040
457-007	3/4	15	90	040
457-010	1	10	60	040
457-012	1-1/4	5	30	040
457-015	1-1/2	5	20	040
457-020	2	5	0	040
457-025	2-1/2	5	0	040
457-030	3	5	0	040
457-040	4	4	0	040
457-060	6	1	0	040



Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040
497-007	3/4	15	90	040
497-010	1	10	60	040
497-012	1-1/4	5	30	040
497-015	1-1/2	5	20	040
497-020	2	5	0	040
497-025	2-1/2	5	0	040
497-030	3	5	0	040
497-040	4	4	0	040
497-060	6	1	0	040

