



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Fipt					
448-012	1-1/4	25	100	040	2.95
448-015	1-1/2	25	100	040	3.08
448-020	2	10	120	040	5.45
448-025	2-1/2	10	0	040	8.03
448-030	3	10	0	040	10.51
448-040	4	6	0	040	18.44
448-050	5	5	0	040	35.73
448-060	6	8	0	040	43.59
448-080F	8	1	2	047	212.72
448-100F	10	1	2	047	432.27
448-120F	12	1	0	047	863.73

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	7.85
-----------	-------	----	-----	-----	------

Plugs

Plug

Spigot

449-003	3/8	50	700	040	2.03
449-005	1/2	50	1000	040	1.64
449-007	3/4	50	300	040	1.92
449-010	1	50	200	040	2.31
449-012	1-1/4	25	150	040	3.08
449-015	1-1/2	25	100	040	3.93
449-020	2	10	120	040	4.85
449-025	2-1/2	10	0	040	8.33
449-030	3	10	0	040	10.98
449-040	4	6	0	040	24.85
449-060	6	6	0	040	33.65
449-060F ⁴	6	1	6	047	85.14
449-080F ⁴	8	1	6	047	131.09
449-100F ⁴	10	1	0	047	300.93
449-120F ⁴	12	1	0	047	492.04
449-140F ⁴	14	1	2	047	539.42
449-160F ⁴	16	1	0	047	596.52
449-180F ⁴	18	1	0	047	1064.51
449-200F ⁴	20	1	0	047	1947.48
449-240F ⁴	24	1	0	047	2592.36

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040	1.92
449-010CS	1	50	300	040	2.31

Plug

Mipt

450-003	3/8	50	700	040	2.20
450-005	1/2	50	300	040	2.03
450-007	3/4	50	300	040	2.18
450-010	1	50	300	040	3.55
450-012	1-1/4	25	300	040	3.74
450-015	1-1/2	25	150	040	4.01
450-020	2	10	120	040	5.18
450-025	2-1/2	10	80	040	7.19
450-030	3	10	0	040	10.89
450-040	4	6	0	040	24.58
450-060	6	6	0	040	72.05
450-080	8	6	0	040	88.04
450-080F ⁴	8	1	4	047	191.02
450-100F ⁴	10	1	3	047	380.65
450-120F ⁴	12	1	0	047	531.42

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	3.22
475-007	3/4	20	0	040	5.05
475-010	1	25	0	040	7.07
475-012	1-1/4	20	0	040	10.87
475-015	1-1/2	20	0	040	13.94
475-020	2	10	0	040	41.82
475-025	2-1/2	8	0	040	95.59
475-030	3	5	0	040	70.45
475-040	4	4	0	040	132.87
475-050F ²	5	1	3	047	518.52
475-060	6	3	0	040	281.12
475-080	8	1	0	040	452.16
475-100	10	1	0	041	1498.26
475-100F ²	10	1	0	047	1257.22

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye (continued)					
Socket x Socket x Socket					
475-120	12	1	0	041	2213.76
475-120F ²	12	1	0	047	1709.07
475-140F ²	14	1	0	047	2421.32
475-160F ²	16	1	0	047	3129.84
475-180F ²	18	1	0	047	4007.31
475-200F ²	20	1	0	047	4737.76
475-240F ²	24	1	0	047	5892.25

¹ Sized with Bushing
² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-101 ¹	3/4X1/2	20	0	040	9.96
475-130 ¹	1X1/2	20	0	040	12.66
475-131 ¹	1X3/4	20	0	040	12.66
475-166 ¹	1-1/4X1/2	20	0	040	17.04
475-167 ¹	1-1/4X3/4	20	0	040	17.04
475-168 ¹	1-1/4X1	20	0	040	17.04
475-209 ¹	1-1/2X1/2	20	0	040	20.28
475-210 ¹	1-1/2X3/4	20	0	040	20.28
475-211 ¹	1-1/2X1	20	0	040	20.28
475-212 ¹	1-1/2X1-1/4	20	0	040	20.28
475-247 ¹	2X1/2	10	0	040	46.08
475-248 ¹	2X3/4	10	0	040	46.08
475-249 ¹	2X1	10	0	040	46.08
475-250 ¹	2X1-1/4	10	0	040	46.08
475-251 ¹	2X1-1/2	10	0	040	46.08
475-292 ¹	2-1/2X2	4	0	040	102.67
475-334 ¹	3X3/4	5	0	040	80.01
475-335 ¹	3X1	5	0	040	80.01
475-336 ¹	3X1-1/4	5	0	040	80.01
475-337 ¹	3X1-1/2	5	0	040	80.01
475-338 ¹	3X2	5	0	040	80.01
475-339 ¹	3X2-1/2	5	0	040	80.01
475-420	4X2	4	0	040	153.71
475-421 ¹	4X2-1/2	4	0	040	153.71
475-422 ¹	4X3	4	0	040	153.71
475-488F ²	5X3	1	4	047	412.41
475-490F ²	5X4	1	4	047	429.45
475-528 ¹	6X2	4	0	040	331.75
475-529 ¹	6X2-1/2	5	0	040	331.75
475-530 ¹	6X3	5	0	040	331.75
475-532	6X4	5	0	040	361.44
475-578F ²	8X2	1	2	047	620.75

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)
Socket x Socket x Socket

475-579F ²	8X2-1/2	1	0	047	658.72
475-580F ²	8X3	1	2	047	674.44
475-582	8X4	2	0	040	619.12
475-582F ²	8X4	1	2	047	695.66
475-585F ²	8X6	1	0	047	716.76
475-621F ²	10X2	1	0	047	746.19
475-622F ²	10X2-1/2	1	0	047	759.02
475-623F ²	10X3	1	0	047	799.55
475-624F ²	10X4	1	0	047	846.11
475-626	10X6	1	0	041	1283.97
475-626F ²	10X6	1	0	047	934.26
475-628	10X8	1	0	041	1426.64
475-628F ²	10X8	1	0	047	999.66
475-661F ²	12X2	1	0	047	1012.88
475-663F ²	12X3	1	0	047	1037.05
475-664F ²	12X4	1	0	047	1085.35
475-666F ²	12X6	1	0	047	1090.56
475-668F ²	12X8	1	0	047	1264.71
475-670F ²	12X10	1	0	047	1446.04
475-691F ²	14X2	1	0	047	1204.07
475-693F ²	14X3	1	0	047	1303.23
475-694F ²	14X4	1	0	047	1366.74
475-696F ²	14X6	1	0	047	1539.84
475-698F ²	14X8	1	0	047	1764.40
475-700F ²	14X10	1	0	047	1970.93
475-702F ²	14X12	1	0	047	2208.19
475-751F ²	16X2	1	0	047	1398.94
475-753F ²	16X3	1	0	047	1512.27
475-754F ²	16X4	1	0	047	1572.67
475-756F ²	16X6	1	0	047	1769.76
475-758F ²	16X8	1	0	047	2015.44
475-760F ²	16X10	1	0	047	2243.15
475-762F ²	16X12	1	0	047	2499.67
475-764F ²	16X14	1	0	047	2829.27
475-781F ²	18X2	1	0	047	1526.37
475-783F ²	18X3	1	0	047	1596.23
475-784F ²	18X4	1	0	047	1619.94
475-786F ²	18X6	1	0	047	3103.69
475-788F ²	18X8	1	0	047	2316.36
475-790F ²	18X10	1	0	047	2576.46
475-792F ²	18X12	1	0	047	2988.94
475-794F ²	18X14	1	0	047	3281.68
475-796F ²	18X16	1	0	047	3441.71
475-811F ²	20X2	1	0	047	1605.01
475-813F ²	20X3	1	0	047	1739.29
475-814F ²	20X4	1	0	047	1761.82
475-816F ²	20X6	1	0	047	1794.87
475-818F ²	20X8	1	0	047	2426.24
475-820F ²	20X10	1	0	047	2697.26
475-822F ²	20X12	1	0	047	3250.61
475-824F ²	20X14	1	0	047	3637.84
475-826F ²	20X16	1	0	047	4032.16
475-828F ²	20X18	1	0	047	4328.19
475-901F ²	24X2	1	0	047	2025.97



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye - Reducing (continued)					
Socket x Socket x Socket					
475-903F ²	24X3	1	0	047	2070.54
475-904F ²	24X4	1	0	047	2127.61
475-906F ²	24X6	1	0	047	3744.81
475-908F ²	24X8	1	0	047	4085.01
475-910F ²	24X10	1	0	047	4128.16
475-912F ²	24X12	1	0	047	4369.81
475-914F ²	24X14	1	0	047	4519.74
475-916F ²	24X16	1	0	047	4733.26
475-918F ²	24X18	1	0	047	5145.62
475-920F ²	24X20	1	0	047	5624.59
¹ Sized with Bushing					
² Fiberglass reinforced					

Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
476-020F ²	2	1	4	047	324.75
476-030F ²	3	1	3	047	534.89
476-040F ²	4	1	2	047	595.82
476-060F ²	6	1	0	047	678.54
476-080F ²	8	1	0	047	826.34
476-100F ²	10	1	0	047	1515.28
476-120F ²	12	1	0	047	1803.96
476-140F ²	14	1	0	047	2625.49
² Fiberglass reinforced					
For larger sizes please contact your Regional Spears® Distribution Center.					

Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
476-338	3X2	5	0	040	117.43
476-420F ²	4X2	1	4	047	527.48
476-421F ²	4X2-1/2	1	2	047	550.34
476-422F ²	4X3	1	3	047	566.17
476-528F ²	6X2	1	2	047	531.17
476-529F ²	6X2-1/2	1	2	047	578.26
476-530F ²	6X3	1	2	047	600.99
476-532F ²	6X4	1	0	047	610.38
476-578F ²	8X2	1	2	047	648.00
476-579F ²	8X2-1/2	1	2	047	673.76
476-580F ²	8X3	1	0	047	725.05
476-582F ²	8X4	1	0	047	734.38
476-585F ²	8X6	1	0	047	769.89
476-621F ²	10X2	1	0	047	965.46
476-622F ²	10X2-1/2	1	0	047	1022.91

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	1052.23
476-624F ²	10X4	1	0	047	1156.15
476-626F ²	10X6	1	0	047	1296.84
476-628F ²	10X8	1	0	047	1352.34
476-661F ²	12X2	1	0	047	1377.42
476-662F ²	12X2 1/2	1	0	047	1393.05
476-663F ²	12X3	1	0	047	1467.82
476-664F ²	12X4	1	0	047	1496.48
476-666F ²	12X6	1	0	047	1581.40
476-668F ²	12X8	1	0	047	1621.96
476-670F ²	12X10	1	0	047	1718.31
476-756F ²	16X6	1	0	047	2887.27
476-786F ²	18X6	1	0	047	1617.52

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
457-005	1/2	20	120	040	7.36
457-007	3/4	15	90	040	8.37
457-010	1	10	60	040	8.62
457-012	1-1/4	5	30	040	27.77
457-015	1-1/2	5	20	040	28.91
457-020	2	5	0	040	39.01
457-025	2-1/2	5	0	040	54.60
457-030	3	5	0	040	87.21
457-040	4	4	0	040	120.76
457-060	6	1	0	040	268.33

Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
497-005	1/2	20	120	040	8.09
497-007	3/4	15	90	040	9.26
497-010	1	10	60	040	9.46
497-012	1-1/4	5	30	040	30.54
497-015	1-1/2	5	20	040	31.83
497-020	2	5	0	040	42.93
497-025	2-1/2	5	0	040	60.08
497-030	3	5	0	040	95.83
497-040	4	4	0	040	128.93
497-060	6	1	0	040	286.51