



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
Fipt					
448-012	1-1/4	25	100	040	2.80
448-015	1-1/2	25	100	040	2.93
448-020	2	10	120	040	5.18
448-025	2-1/2	10	0	040	7.63
448-030	3	10	0	040	9.98
448-040	4	6	0	040	17.52
448-050	5	5	0	040	33.94
448-060	6	8	0	040	41.41
448-080F	8	1	2	047	202.08
448-100F	10	1	2	047	410.66
448-120F	12	1	0	047	820.54

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	7.46
-----------	-------	----	-----	-----	------

Plugs

Plug

Spigot

449-003	3/8	50	700	040	1.93
449-005	1/2	50	1000	040	1.56
449-007	3/4	50	300	040	1.82
449-010	1	50	200	040	2.19
449-012	1-1/4	25	150	040	2.93
449-015	1-1/2	25	100	040	3.73
449-020	2	10	120	040	4.61
449-025	2-1/2	10	0	040	7.91
449-030	3	10	0	040	10.43
449-040	4	6	0	040	23.61
449-060	6	6	0	040	31.97
449-060F ⁴	6	1	6	047	80.88
449-080F ⁴	8	1	6	047	124.54
449-100F ⁴	10	1	0	047	285.88
449-120F ⁴	12	1	0	047	467.44
449-140F ⁴	14	1	2	047	512.45
449-160F ⁴	16	1	0	047	566.69
449-180F ⁴	18	1	0	047	1011.28
449-200F ⁴	20	1	0	047	1850.11
449-240F ⁴	24	1	0	047	2462.74

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040	1.82
449-010CS	1	50	300	040	2.19

Plug

Mipt

450-003	3/8	50	700	040	2.09
450-005	1/2	50	300	040	1.93
450-007	3/4	50	300	040	2.07
450-010	1	50	300	040	3.37
450-012	1-1/4	25	300	040	3.55
450-015	1-1/2	25	150	040	3.81
450-020	2	10	120	040	4.92
450-025	2-1/2	10	80	040	6.83
450-030	3	10	0	040	10.35
450-040	4	6	0	040	23.35
450-060	6	6	0	040	68.45
450-080	8	6	0	040	83.64
450-080F ⁴	8	1	4	047	181.47
450-100F ⁴	10	1	3	047	361.62
450-120F ⁴	12	1	0	047	504.85

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2 - 1/2" - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	3.06
475-007	3/4	20	0	040	4.80
475-010	1	25	0	040	6.72
475-012	1-1/4	20	0	040	10.33
475-015	1-1/2	20	0	040	13.24
475-020	2	10	0	040	39.73
475-025	2-1/2	8	0	040	90.81
475-030	3	5	0	040	66.93
475-040	4	4	0	040	126.23
475-050F	5	1	3	047	492.59
475-060	6	3	0	040	267.06
475-080	8	1	0	040	429.55
475-100	10	1	0	041	1423.35
475-100F ²	10	1	0	047	1194.36

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye (continued)					
Socket x Socket x Socket					
475-120	12	1	0	041	2103.07
475-120F ²	12	1	0	047	1623.62
475-140F ²	14	1	0	047	2300.25
475-160F ²	16	1	0	047	2973.35
475-180F ²	18	1	0	047	3806.94
475-200F ²	20	1	0	047	4500.87
475-240F ²	24	1	0	047	5597.64
¹ Sized with Bushing					
² Fiberglass reinforced					



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-101 ¹	3/4X1/2	20	0	040	9.46
475-130 ¹	1X1/2	20	0	040	12.03
475-131 ¹	1X3/4	20	0	040	12.03
475-166 ¹	1-1/4X1/2	20	0	040	16.19
475-167 ¹	1-1/4X3/4	20	0	040	16.19
475-168 ¹	1-1/4X1	20	0	040	16.19
475-209 ¹	1-1/2X1/2	20	0	040	19.27
475-210 ¹	1-1/2X3/4	20	0	040	19.27
475-211 ¹	1-1/2X1	20	0	040	19.27
475-212 ¹	1-1/2X1-1/4	20	0	040	19.27
475-247 ¹	2X1/2	10	0	040	43.78
475-248 ¹	2X3/4	10	0	040	43.78
475-249 ¹	2X1	10	0	040	43.78
475-250 ¹	2X1-1/4	10	0	040	43.78
475-251 ¹	2X1-1/2	10	0	040	43.78
475-292 ¹	2-1/2X2	4	0	040	97.54
475-334 ¹	3X3/4	5	0	040	76.01
475-335 ¹	3X1	5	0	040	76.01
475-336 ¹	3X1-1/4	5	0	040	76.01
475-337 ¹	3X1-1/2	5	0	040	76.01
475-338 ¹	3X2	5	0	040	76.01
475-339 ¹	3X2-1/2	5	0	040	76.01
475-420	4X2	4	0	040	146.02
475-421 ¹	4X2-1/2	4	0	040	146.02
475-422 ¹	4X3	4	0	040	146.02
475-488F ²	5X3	1	4	047	391.79
475-490F ²	5X4	1	4	047	407.98
475-528 ¹	6X2	4	0	040	315.16
475-529 ¹	6X2-1/2	5	0	040	315.16
475-530 ¹	6X3	5	0	040	315.16
475-532	6X4	5	0	040	343.37
475-578F ²	8X2	1	2	047	589.71

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)
Socket x Socket x Socket

475-579F ²	8X2-1/2	1	0	047	625.78
475-580F ²	8X3	1	2	047	640.72
475-582	8X4	2	0	040	588.16
475-582F ²	8X4	1	2	047	660.88
475-585F ²	8X6	1	0	047	680.92
475-621F ²	10X2	1	0	047	708.88
475-622F ²	10X2-1/2	1	0	047	721.07
475-623F ²	10X3	1	0	047	759.57
475-624F ²	10X4	1	0	047	803.80
475-626	10X6	1	0	041	1219.77
475-626F ²	10X6	1	0	047	887.55
475-628	10X8	1	0	041	1355.31
475-628F ²	10X8	1	0	047	949.68
475-661F ²	12X2	1	0	047	962.24
475-663F ²	12X3	1	0	047	985.20
475-664F ²	12X4	1	0	047	1031.08
475-666F ²	12X6	1	0	047	1036.03
475-668F ²	12X8	1	0	047	1201.47
475-670F ²	12X10	1	0	047	1373.74
475-691F ²	14X2	1	0	047	1143.87
475-693F ²	14X3	1	0	047	1238.07
475-694F ²	14X4	1	0	047	1298.40
475-696F ²	14X6	1	0	047	1462.85
475-698F ²	14X8	1	0	047	1676.18
475-700F ²	14X10	1	0	047	1872.38
475-702F ²	14X12	1	0	047	2097.78
475-751F ²	16X2	1	0	047	1328.99
475-753F ²	16X3	1	0	047	1436.66
475-754F ²	16X4	1	0	047	1494.04
475-756F ²	16X6	1	0	047	1681.27
475-758F ²	16X8	1	0	047	1914.67
475-760F ²	16X10	1	0	047	2130.99
475-762F ²	16X12	1	0	047	2374.69
475-764F ²	16X14	1	0	047	2687.81
475-781F ²	18X2	1	0	047	1450.05
475-783F ²	18X3	1	0	047	1516.42
475-784F ²	18X4	1	0	047	1538.94
475-786F ²	18X6	1	0	047	2948.51
475-788F ²	18X8	1	0	047	2200.54
475-790F ²	18X10	1	0	047	2447.64
475-792F ²	18X12	1	0	047	2839.49
475-794F ²	18X14	1	0	047	3117.60
475-796F ²	18X16	1	0	047	3269.62
475-811F ²	20X2	1	0	047	1524.76
475-813F ²	20X3	1	0	047	1652.33
475-814F ²	20X4	1	0	047	1673.73
475-816F ²	20X6	1	0	047	1705.13
475-818F ²	20X8	1	0	047	2304.93
475-820F ²	20X10	1	0	047	2562.40
475-822F ²	20X12	1	0	047	3088.08
475-824F ²	20X14	1	0	047	3455.95
475-826F ²	20X16	1	0	047	3830.55
475-828F ²	20X18	1	0	047	4111.78
475-901F ²	24X2	1	0	047	1924.67



Schedule 40 Fittings Product
PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Wye - Reducing (continued)					
Socket x Socket x Socket					
475-903F ²	24X3	1	0	047	1967.01
475-904F ²	24X4	1	0	047	2021.23
475-906F ²	24X6	1	0	047	3557.57
475-908F ²	24X8	1	0	047	3880.76
475-910F ²	24X10	1	0	047	3921.75
475-912F ²	24X12	1	0	047	4151.32
475-914F ²	24X14	1	0	047	4293.75
475-916F ²	24X16	1	0	047	4496.60
475-918F ²	24X18	1	0	047	4888.34
475-920F ²	24X20	1	0	047	5343.36
¹ Sized with Bushing					
² Fiberglass reinforced					



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047	308.51
476-030F ²	3	1	3	047	508.15
476-040F ²	4	1	2	047	566.03
476-060F ²	6	1	0	047	644.61
476-080F ²	8	1	0	047	785.02
476-100F ²	10	1	0	047	1439.52
476-120F ²	12	1	0	047	1713.76
476-140F ²	14	1	0	047	2494.22
² Fiberglass reinforced					
For larger sizes please contact your Regional Spears® Distribution Center.					



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	111.56
476-420F ²	4X2	1	4	047	501.11
476-421F ²	4X2-1/2	1	2	047	522.82
476-422F ²	4X3	1	3	047	537.86
476-528F ²	6X2	1	2	047	504.61
476-529F ²	6X2-1/2	1	2	047	549.35
476-530F ²	6X3	1	2	047	570.94
476-532F ²	6X4	1	0	047	579.86
476-578F ²	8X2	1	2	047	615.60
476-579F ²	8X2-1/2	1	2	047	640.07
476-580F ²	8X3	1	0	047	688.80
476-582F ²	8X4	1	0	047	697.66
476-585F ²	8X6	1	0	047	731.40
476-621F ²	10X2	1	0	047	917.19
476-622F ²	10X2-1/2	1	0	047	971.76

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	999.62
476-624F ²	10X4	1	0	047	1098.34
476-626F ²	10X6	1	0	047	1232.00
476-628F ²	10X8	1	0	047	1284.72
476-661F ²	12X2	1	0	047	1308.55
476-662F ²	12X2 1/2	1	0	047	1323.40
476-663F ²	12X3	1	0	047	1394.43
476-664F ²	12X4	1	0	047	1421.66
476-666F ²	12X6	1	0	047	1502.33
476-668F ²	12X8	1	0	047	1540.86
476-670F ²	12X10	1	0	047	1632.39
476-756F	16X6	1	0	047	2742.91
476-786F	18X6	1	0	047	1536.64

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions

Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	6.99
457-007	3/4	15	90	040	7.95
457-010	1	10	60	040	8.19
457-012	1-1/4	5	30	040	26.38
457-015	1-1/2	5	20	040	27.46
457-020	2	5	0	040	37.06
457-025	2-1/2	5	0	040	51.87
457-030	3	5	0	040	82.85
457-040	4	4	0	040	114.72
457-060	6	1	0	040	254.91



Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	7.69
497-007	3/4	15	90	040	8.80
497-010	1	10	60	040	8.99
497-012	1-1/4	5	30	040	29.01
497-015	1-1/2	5	20	040	30.24
497-020	2	5	0	040	40.78
497-025	2-1/2	5	0	040	57.08
497-030	3	5	0	040	91.04
497-040	4	4	0	040	122.48
497-060	6	1	0	040	272.18

