



Repair Couplings

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
Repair Coupling - Spigot x Socket (continued)						
PVC White with EPDM O-ring						
S118-60	6	6	1	0	025	199.00
Unit Must Be Thrust Blocked T = Repair Coupling Travel						

Repair Coupling - Socket x Socket

PVC White with EPDM O-ring

Can be used as short-stroke Expansion Joint

S119-05	1/2	3	30	0	025	6.16
S119-07	3/4	4	24	0	025	7.00
S119-10	1	4	20	0	025	8.07
S119-12	1-1/4	4	10	0	025	15.22
S119-15	1-1/2	4	16	0	025	16.58
S119-20	2	4	10	0	025	25.64
S119-25	2-1/2	6	5	0	025	37.20
S119-30	3	6	4	0	025	46.47
S119-40	4	6	2	0	025	81.33
S119-60	6	6	1	0	025	199.00

Unit Must Be Thrust Blocked
T = Repair Coupling Travel

Short Repair Couplings

Repair Coupling - Short, Spigot x Socket

PVC White with EPDM O-ring

SH118-05	1/2	2	36	0	025	6.16
SH118-07	3/4	2-1/4	30	0	025	7.00
SH118-10	1	2	35	0	025	8.07
SH118-12	1-1/4	2-1/2	25	0	025	15.22
SH118-15	1-1/2	2-3/4	32	0	025	16.58
SH118-20	2	3-1/4	15	0	025	25.64

Unit Must Be Thrust Blocked
T = Repair Coupling Travel

Repair Coupling - Short, Socket x Socket

PVC White with EPDM O-ring

SH119-05	1/2	2	40	0	025	6.16
SH119-07	3/4	2	30	0	025	7.00
SH119-10	1	2	30	0	025	8.07
SH119-12	1-1/4	2-1/2	20	0	025	15.22
SH119-15	1-1/2	2-3/4	21	0	025	16.58

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	------------	--------	----------	-----------	------

Repair Coupling - Short, Socket x Socket (continued)

PVC White with EPDM O-ring

SH119-20	2	3-1/4	12	0	025	25.64
----------	---	-------	----	---	-----	-------

Unit Must Be Thrust Blocked
T = Repair Coupling Travel

GripLoc™ Compression Couplings

Tightening nut compresses special stainless steel Gripper Ring to firmly grip pipe and prevent potential pull-out. Compressed Gland Ring ensures positive O-ring seal against pipe.



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

GripLoc™ Compression Couplings

WARNING: DO NOT INSERT FINGERS
For Cold Water Only - EPDM Gasket
1/2" - 2" Pressure Rated to 235 psi
3" - 4" Pressure Rated to 150 psi

Hand Tighten ONLY - No Nut Wrenches Required

S112-05	1/2	28	0	131	20.36
S112-07	3/4	24	0	131	22.49
S112-10	1	20	0	131	28.23
S112-12	1-1/4	1	10	131	34.43
S112-15	1-1/2	1	16	131	41.69
S112-20	2	1	12	131	49.14
S112-30	3	1	4	131	84.36
S112-40	4	1	4	131	95.38

GripLoc™ Compression Adapters

GripLoc™ Compression Male Adapter

WARNING: DO NOT INSERT FINGERS
For Cold Water Only - Mipt x EPDM
GripLoc™ Gasket

Hand Tighten ONLY - No Nut Wrenches Required

S135-05	1/2	1	25	131	12.20
S135-07	3/4	1	25	131	14.32