



**Repair Couplings**

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Repair Coupling - Spigot x Socket (continued)</b>						
<b>PVC White with EPDM O-ring</b>						
S118-60	6	6	1	0	025	209.47
Unit Must Be Thrust Blocked T = Repair Coupling Travel						

**Repair Coupling - Socket x Socket**

PVC White with EPDM O-ring

Can be used as short-stroke Expansion Joint

S119-05	1/2	3	30	0	025	6.48
S119-07	3/4	4	24	0	025	7.37
S119-10	1	4	20	0	025	8.49
S119-12	1-1/4	4	10	0	025	16.02
S119-15	1-1/2	4	16	0	025	17.45
S119-20	2	4	10	0	025	26.99
S119-25	2-1/2	6	5	0	025	39.16
S119-30	3	6	4	0	025	48.92
S119-40	4	6	2	0	025	85.61
S119-60	6	6	1	0	025	209.47

Unit Must Be Thrust Blocked  
T = Repair Coupling Travel

**Short Repair Couplings**

**Repair Coupling - Short, Spigot x Socket**

PVC White with EPDM O-ring

SH118-05	1/2	2	36	0	025	6.48
SH118-07	3/4	2-1/4	30	0	025	7.37
SH118-10	1	2	35	0	025	8.49
SH118-12	1-1/4	2-1/2	25	0	025	16.02
SH118-15	1-1/2	2-3/4	32	0	025	17.45
SH118-20	2	3-1/4	15	0	025	26.99

Unit Must Be Thrust Blocked  
T = Repair Coupling Travel

**Repair Coupling - Short, Socket x Socket**

PVC White with EPDM O-ring

SH119-05	1/2	2	40	0	025	6.48
SH119-07	3/4	2	30	0	025	7.37
SH119-10	1	2	30	0	025	8.49
SH119-12	1-1/4	2-1/2	20	0	025	16.02
SH119-15	1-1/2	2-3/4	21	0	025	17.45

Part Number	Size	Travel - T	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	------------	--------	----------	-----------	------

**Repair Coupling - Short, Socket x Socket (continued)**

PVC White with EPDM O-ring

SH119-20	2	3-1/4	12	0	025	26.99
----------	---	-------	----	---	-----	-------

Unit Must Be Thrust Blocked  
T = Repair Coupling Travel

**GripLoc™ Compression Couplings**

Tightening nut compresses special stainless steel Gripper Ring to firmly grip pipe and prevent potential pull-out. Compressed Gland Ring ensures positive O-ring seal against pipe.



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**GripLoc™ Compression Couplings**

**WARNING: DO NOT INSERT FINGERS**  
For Cold Water Only - EPDM Gasket  
1/2" - 2" Pressure Rated to 235 psi  
3" - 4" Pressure Rated to 150 psi

Hand Tighten ONLY - No Nut Wrenches Required

S112-05	1/2	28	0	131	21.43
S112-07	3/4	1	24	131	23.67
S112-10	1	1	20	131	29.72
S112-12	1-1/4	1	10	131	36.24
S112-15	1-1/2	1	16	131	43.88
S112-20	2	1	12	131	51.73
S112-30	3	1	4	131	88.80
S112-40	4	1	4	131	100.40

**GripLoc™ Compression Adapters**

**GripLoc™ Compression Male Adapter**

**WARNING: DO NOT INSERT FINGERS**  
For Cold Water Only - Mipt x EPDM  
GripLoc™ Gasket

Hand Tighten ONLY - No Nut Wrenches Required

S135-05	1/2	1	25	131	12.84
S135-07	3/4	1	25	131	15.07