



Pipe Flanges



PRODUCT

Contact Spears® for any Information not found.



Schedule 40 Fittings Product


Pipe Flanges

Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style -PIP

Flange x PIP Socket



125 psi Maximum Internal Pressure Rating @ 73°F (23°C)

354-060F	6X6.140	1	4	320	133.67
354-080F	8X8.160	1	2	320	202.42
354-100F	10X10.200	1	2	320	284.61
354-120F	12X12.240	1	2	320	412.21
354-150F	14X15.300	1	0	320	1098.76
354-151F	16X15.300	1	0	320	1253.46
354-181F	18X18.701	1	0	320	1904.21
354-182F	18X18.360	1	0	320	1904.21
354-201F	20X22.047	1	0	320	2900.51
354-241F	24X24.803	1	0	320	4247.72

For more information, refer to 80, 100 & 125 psi PIP Fabrication Fittings.

PIP = Plastic Irrigation Pipe (dimensions are NOT the same as IPS dimensions)

Sizes 6" - 16" are furnished with Glass Filled PVC ring.
 Sizes 18" - 24" are furnished with steel ring.

Flange One Piece

Socket

1/2" - 16" 150 psi Maximum Internal Pressure Rating @73°F (23°C)

18" - 24" 50 psi Maximum Internal Pressure Rating @73°F (23°C)

851-005	1/2	25	0	080	19.06
851-007	3/4	25	0	080	20.37
851-010	1	15	0	080	22.68
851-012	1-1/4	15	0	080	23.37
851-015	1-1/2	20	0	080	23.87
851-020	2	10	0	080	31.78
851-025	2-1/2	10	0	080	49.05
851-030	3	10	0	080	54.17
851-040	4	5	0	080	68.59
851-050	5	5	0	080	107.84
851-060	6	5	0	080	107.84
851-080	8	2	0	080	192.98
851-100F	10	1	2	083	524.40
851-120F	12	1	0	083	636.80
851-140F	14	1	0	083	1171.21
851-160F	16	1	0	083	1607.36
851-180F	18	1	0	083	3400.21
851-200F	20	1	0	083	4163.80
851-240F	24	1	0	083	5530.02



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange One Piece

Fipt

150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005	1/2	25	0	080	22.81
852-007	3/4	25	0	080	26.73
852-010	1	15	0	080	29.26
852-012	1-1/4	15	0	080	40.35
852-015	1-1/2	20	0	080	44.03
852-020	2	10	0	080	45.03
852-025	2-1/2	10	0	080	103.54
852-030	3	10	0	080	106.57
852-040	4	5	0	080	200.23
852-060F	6	1	8	083	240.55
852-080F	8	1	2	083	603.71



Flange - Special Reinforced One Piece

SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005SR	1/2	25	0	086	12.54
852-007SR	3/4	25	0	086	14.73
852-010SR	1	15	0	086	16.09
852-012SR	1-1/4	15	0	086	22.18
852-015SR	1-1/2	15	0	086	24.27
852-020SR	2	10	0	086	24.86
852-025SR	2-1/2	10	0	086	56.94
852-030SR	3	10	0	086	58.62
852-040SR	4	5	0	086	110.20



Flange - Blind

1/2" - 12" Molded - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

14" - 24" Fabricated - 50 psi Maximum Internal Pressure Rating @ 73°F (23°C)

853-005	1/2	25	0	080	26.72
853-007	3/4	25	0	080	31.82
853-010	1	15	0	080	43.46
853-012	1-1/4	20	0	080	53.35
853-015	1-1/2	15	0	080	53.35
853-020	2	10	0	080	79.72
853-025	2-1/2	10	0	080	129.87
853-030	3	10	0	080	156.73
853-040	4	8	0	080	195.24
853-050F	5	1	5	083	489.42
853-060	6	5	0	080	237.26
853-080	8	5	0	080	296.98
853-100	10	3	0	081	496.60
853-120	12	2	0	081	773.42





Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Flange - Blind (continued)					
853-140F	14	1	0	083	1471.36
853-160F	16	1	0	083	1744.75
853-180F	18	1	0	083	1962.20
853-200F	20	1	0	083	3171.59
853-240F	24	1	0	083	4228.39



Flange Van Stone Style with PVC Ring

Socket

1/2" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)

18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005	1/2	25	0	080	19.03
854-007	3/4	25	0	080	20.36
854-010	1	15	0	080	22.67
854-012	1-1/4	15	0	080	23.35
854-015	1-1/2	20	0	080	23.82
854-020	2	10	0	080	31.73
854-025	2-1/2	10	0	080	49.00
854P-030	3	10	0	080	54.15
854P-040	4	5	0	080	68.49
854P-050	5	5	0	080	107.75
854P-060	6	5	0	080	107.75
854P-080	8	2	0	080	194.33
854P-100	10	2	0	081	227.15
854P-120	12	2	0	081	244.91
854P-140	14	1	0	082	945.48
854P-160	16	1	0	082	1264.63
854P-180	18	1	0	082	2039.67
854-180FP	18	1	0	083	3227.12
854-200FP	20	1	0	083	3947.24
854-240FP	24	1	0	083	5369.55

Flange Van Stone Style with Glass Filled PVC Ring

Socket

3" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)

854-030	3	10	0	080	54.15
854-040	4	5	0	080	68.49
854-050	5	5	0	080	107.75
854-060	6	5	0	080	107.75
854-080	8	2	0	080	194.33
854-100	10	2	0	081	227.15
854-120	12	2	0	081	244.91
854-140	14	1	0	082	945.48
854-160	16	1	0	082	1264.63
854-180	18	1	0	082	2039.67



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with Glass Filled PVC Ring (continued)

Socket

18" flange has 4-section ring



Flange Van Stone Style PVC with Solid Ring

Socket

150 psi Maximum Internal Pressure Rating @73°F (23°C)

S854-020	2	10	0	080	39.66
S854-030	3	10	0	080	67.71
S854-040	4	5	0	080	85.64

Flange Van Stone Style PVC with Glass Filled PVC Solid Ring

Socket

150 psi Maximum Internal Pressure Rating @73°F (23°C)

S854-060	6	5	0	080	134.71
S854-080	8	2	0	080	219.32
S854-100	10	2	0	081	283.93
S854-120	12	2	0	081	306.11



Flange Van Stone Style with Steel Ring

Socket

150 psi Maximum Internal Pressure Rating @73°F (23°C)

854-180FS	18	1	0	083	1905.15
854-200FS	20	1	0	083	2308.62
854-240FS	24	1	0	083	3107.04



Flange Van Stone Style Class 300 Bolt Pattern Fabricated with PVC Ring

Socket

1/2" - 16" molded with fab ring - 150 psi = maximum internal pressure rating @ 73°F (23°C)

18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005CL300	1/2	1	25	083	156.46
854-007CL300	3/4	1	25	083	181.80
854-010CL300	1	1	15	083	285.65
854-012CL300	1-1/4	1	15	083	291.67
854-015CL300	1-1/2	1	20	083	302.98
854-020CL300	2	10	0	083	319.00
854-025CL300	2-1/2	1	10	083	350.27
854-030CL300	3	1	10	083	384.68
854-040CL300	4	1	3	083	652.28
854-060CL300	6	1	4	083	1242.36
854-080CL300	8	1	3	083	1414.14
854-100CL300	10	1	2	083	1664.84
854-120CL300	12	1	0	083	2133.00
854-140CL300	14	1	0	083	2351.83
854-160CL300	16	1	0	083	2449.18
854-180CL300	18	1	0	083	3424.33





Pipe Flanges

Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style Class 300 Bolt Pattern Fabricated with PVC Ring (continued)

Socket

854-200CL300	20	1	0	083	5937.07
854-240CL300	24	1	0	083	8721.04



Flange Van Stone Style with PVC Ring

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

855-005	1/2	25	0	080	22.77
855-007	3/4	25	0	080	26.72
855-010	1	15	0	080	29.22
855-012	1-1/4	15	0	080	40.27
855-015	1-1/2	20	0	080	43.99
855-020	2	10	0	080	45.01
855-025	2-1/2	10	0	080	103.46



Flange Van Stone Style with Glass Filled PVC Ring

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

855-030	3	10	0	080	106.43
855-040	4	5	0	080	193.51
855-060	6	1	4	080	304.31
855-060F	6	1	4	083	270.49
855-080	8	2	0	080	377.09
855-080F	8	1	2	083	335.60
855-100F	10	1	2	083	378.09



Flange Van Stone Style with PVC Ring

Spigot

1/2" - 16" = 150 psi maximum internal pressure rating @ 73°F (23°C)

18" - 24" = 50 psi maximum internal pressure rating @ 73°F (23°C)

856-005	1/2	25	0	080	19.14
856-007	3/4	25	0	080	20.51
856-010	1	15	0	080	22.86
856-012	1-1/4	15	0	080	23.58
856-015	1-1/2	15	0	080	24.05
856-020	2	10	0	080	31.97
856-025	2-1/2	10	0	080	49.41
856P-030	3	10	0	080	54.58
856P-040	4	5	0	080	69.06
856P-060	6	4	0	080	108.63
856P-080	8	2	0	080	194.33
856P-100	10	2	0	081	227.15
856P-120	12	2	0	081	244.91



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with PVC Ring (continued)

Spigot

856-200FP	20	1	0	083	3947.24
856-240FP	24	1	0	083	5369.55



Flange Van Stone Style with Glass Filled PVC Ring

Spigot

3" - 12" molded, 14" - 18" molded/fabricated - 150 psi = maximum internal pressure rating @ 73°F (23°C)

856-030	3	10	0	080	54.58
856-040	4	5	0	080	69.06
856-060	6	4	0	080	108.63
856-080	8	2	0	080	194.33
856-100	10	2	0	081	227.15
856-120	12	2	0	081	244.91
856-140FP	14	1	0	083	2028.37
856-160FP	16	1	0	083	2460.97
856-180FP	18	1	0	083	3227.12

** Fabricated from molded socket flanges with pipe spigot. 18" flange uses 4-piece ring



Flange Van Stone Style with Steel Ring

Spigot

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

856-140FS	14	1	0	083	1026.55
856-160FS	16	1	0	083	1254.75
856-180FS	18	1	0	083	1421.76
856-200FS	20	1	0	083	1712.49
856-240FS	24	1	0	083	2325.38



Flange, One Piece PVC Multi-Bolt Pattern*

ASTM Socket x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M851-100	10	2	0	081	199.74
M851-120	12	2	0	081	344.00

Hubs fit 10" and 12" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 10" and 12" in ANSI Class 150, B.S. 4504 PN10, B.S. 4504 PN16, Table E & JIS 10K for size 10", Table D & E for size 12" Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.



Flange Van Stone Style with Multi-Bolt Pattern PVC Ring*

ASTM Socket x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M854-020	2	10	0	080	31.73
----------	---	----	---	-----	-------

Schedule 40 Fittings Product
Pipe Flanges & Van Stone Style Flange Replacement Split Rings



Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with Multi-Bolt Pattern PVC Ring*

(continued)

ASTM Socket x Multi-bolt Pattern Ring

* Hubs fit 2" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 2" in ANSI Class 150, B.S. 4504 PN10 B.S. 4504 PN16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.



Flange Van Stone Style with Multi-Bolt Pattern Glass Filled PVC Ring*

ASTM Socket x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M854-060	6	5	0	080	107.75
M854-080	8	2	0	080	175.45

* Hubs fit 6" and 8" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 6" and 8" in ANSI Class 150, B.S. 4504 PN10 B.S. 4504 PN16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.



Flange Van Stone Style with Multi-Bolt Pattern PVC Ring*

ASTM Spigot x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M856-020	2	10	0	080	31.97
----------	---	----	---	-----	-------

* Spigots fit 2" ASTM IPS fitting socket. Rings are manufactured to accept bolt patterns in size 2" in ANSI Class 150, B.S. 4504 NP10 B.S. 4504 NP16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.



Flange Van Stone Style with Multi-Bolt Pattern Glass Filled PVC Ring*

ASTM Spigot x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M856-060	6	4	0	080	108.63
M856-080	8	2	0	080	176.78

* Spigots fit 6" and 8" ASTM IPS fitting socket. Rings are manufactured to accept bolt patterns in size 6" and 8" in ANSI Class 150, B.S. 4504 PN10 B.S. 4504 PN16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with Multi-Bolt Pattern Glass Filled PVC Ring* (continued)

ASTM Spigot x Multi-bolt Pattern Ring

Application & Use of Van Stone Style Flange Replacement Split Rings

Designed for easy Van Stone style flange ring replacement in the event of system modification, repair, or improper assembly without having to remove existing flange hub. Split rings are made as a direct replacement of existing one-piece rings used on Spears® brand only of Van Stone style flanges with ANSI Class 150 bolt pattern plastic rings. Remove old ring to be replaced then simply place the split ring sections around hub and install flange bolts (not included) through special designed section overlap to hold in position. Install appropriate user supplied bolts, washers and gasket (see Flange Gasket and Bolt Hardware Kits in this catalog); torque to specifications according to normal flange assembly. Split rings are a set of either 2-pieces or 4-pieces (illustrated) sections depending on size, in regular PVC, Glass Filled PVC, or CPVC for flange type and sizes listed.



Van Stone Style Flange Replacement Split Rings

Flange Replacement Split Rings, PVC

For Spears® flanges with regular PVC Rings



854P-005-1S	1/2	10	0	080	57.87
854P-007-1S	3/4	10	0	080	61.44
854P-010-1S	1	15	0	080	68.71
854P-012-1S	1-1/4	15	0	080	70.05
854P-015-1S	1-1/2	10	0	080	71.77
854P-020-1S	2	10	0	080	95.25
854P-025-1S	2-1/2	10	0	080	110.19
854P-030-1S	3	10	0	080	122.17
854P-040-1S	4	1	10	080	130.97
854P-050-1S	5	5	0	080	177.36
854P-060-1S	6	5	0	080	209.87
854P-080-1S	8	4	0	080	239.79
854P-100-1S	10	4	0	081	302.71
854P-120-1S	12	2	0	081	375.19
854P-140-1S	14	2	0	082	513.89
854P-160-1S	16	4	0	082	638.40
854P-180-1S	18	1	0	082	693.36
854P-200-1S	20	1	0	083	3680.06
854P-240-1S	24	1	0	083	4509.00

Fits 854-xxx Socket, 855-xxx Threaded, and 856-xxx Spigot hub configurations

Flange Replacement Split Rings, Glass Filled PVC

For Spears® flanges with Glass Filled PVC Rings



854-030-1S	3	10	0	080	122.17
854-040-1S	4	10	0	080	130.97



Van Stone Style Flange Replacement Split Rings & Flange Bolt Kits

Van Stone Style Flange Replacement Split Rings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Replacement Split Rings, Glass Filled PVC (continued)

For Spears® flanges with Glass Filled PVC Rings

854-050-1S	5	5	0	080	177.36
854-060-1S	6	5	0	080	209.87
854-080-1S	8	4	0	080	239.79
854-100-1S	10	4	0	081	302.71
854-120-1S	12	2	0	081	375.19
854-140-1S	14	2	0	081	513.89
854-160-1S	16	1	0	082	638.40
854-180-1S	18	1	0	082	693.36

Fits 854-xxx Socket, 855-xxx Threaded, and 856-xxx Spigot hub configurations

Flange Bolt Kits

Flange Bolt Kit Selection Guide

Order Gaskets & Bolt Kits Separately

- Kit Contains All Bolts, Nuts, & Flat Washers for Specified Flange Size
- For Connecting Two (2) Mating Spears® Flanges
- Pre-coated, Anti-seize Lubricated Bolts
- Available in Zinc Coated Steel, Type 304 Stainless Steel or Type 316 Stainless Steel

Flange Size	Bolts* Per Kit	Diameter (in-TP)	Length (in.)	Hardware Kit Part Numbers		
				Zinc	316 SS	304 SS
1/2	4	1/2-13	2	HK-005	HK1-005	HK2-005
3/4 & 1	4	1/2-13	2-1/4	HK-010	HK1-010	HK2-010
1-1/4 & 1-1/2	4	1/2-13	2-1/2	HK-015	HK1-015	HK2-015
2	4	5/8-11	3	HK-020	HK1-020	HK2-020
2-1/2	4	5/8-11	3-1/4	HK-025	HK1-025	HK2-025
3	4	5/8-11	3-1/2	HK-030	HK1-030	HK2-030
4	8	5/8-11	3-1/2	HK-040	HK1-035	HK2-035
5 & 6	8	3/4-10	4	HK-060	HK1-040	HK2-040
8	8	3/4-10	4-1/2	HK-080	HK1-045	HK2-045
10 & 12	12	7/8-9	5	HK-120	HK1-050	HK2-050

* Each Bolt Includes Nut & Two(2) Flat Washers

Flange Bolt Hardware Kits - Zinc Plated Steel

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts & Flat Washers



HK-005	1/2	1	10	017	10.56
HK-010	3/4 & 1	1	10	017	13.20
HK-015	1-1/4 & 1-1/2	1	10	017	19.84
HK-020	2	1	10	017	26.56

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Bolt Hardware Kits - Zinc Plated Steel (continued)

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts & Flat Washers

HK-025	2-1/2	1	10	017	31.84
HK-030	3	1	10	017	36.64
HK-040	4	1	5	017	75.92
HK-060	5 & 6	1	5	017	84.43
HK-080	8	1	0	017	98.95
HK-120	10 & 12	1	0	017	133.87

Flange Bolt Hardware Kits - Type 316 Stainless Steel

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts & Flat Washers



HK1-005	1/2	1	10	017	31.69
HK1-010	3/4 & 1	1	10	017	45.65
HK1-015	1-1/4 & 1-1/2	1	10	017	50.29
HK1-020	2	1	10	017	60.48
HK1-025	2-1/2	1	10	017	64.83
HK1-030	3	1	10	017	85.54
HK1-040	4	1	5	017	171.54
HK1-060	5 & 6	1	5	017	223.73
HK1-080	8	1	0	017	280.73
HK1-120	10 & 12	1	0	017	571.14

Flange Bolt Hardware Kits - Type 304 Stainless Steel

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts, & Flat Washers




HK2-005	1/2	1	10	017	27.73
HK2-010	3/4 & 1	1	10	017	39.55
HK2-015	1-1/4 & 1-1/2	1	10	017	46.59
HK2-020	2	1	10	017	54.80
HK2-025	2-1/2	1	10	017	58.11
HK2-030	3	1	10	017	72.16
HK2-040	4	1	5	017	144.31
HK2-060	5 & 6	1	5	017	152.12
HK2-080	8	1	0	017	200.02
HK2-120	10 & 12	1	0	017	354.51

Schedule 40 Fittings Product
Flange Gaskets - Full-Faced



Flange Gaskets - Full-Faced
Gasket Selection Guide



Flange Size	Bolt Holes	Gasket Part Number		
		Buna-N	EPDM	FKM
1/2	4	GK1-005	GK2-005	GK3-005
3/4	4	GK1-007	GK2-007	GK3-007
1	4	GK1-010	GK2-010	GK3-010
1-1/4	4	GK1-012	GK2-012	GK3-012
1-1/2	4	GK1-015	GK2-015	GK3-015
2	4	GK1-020	GK2-020	GK3-020
2-1/2	4	GK1-025	GK2-025	GK3-025
3	4	GK1-030	GK2-030	GK3-030
4	8	GK1-040	GK2-040	GK3-040
5	8	GK1-050	GK2-050	GK3-050
6	8	GK1-060	GK2-060	GK3-060
8	8	GK1-080	GK2-080	GK3-080
10	12	GK1-100	GK2-100	GK3-100
12	12	GK1-120	GK2-120	GK3-120

Order Gaskets & Bolt Kits Separately

- 1/8" Full-Face design with ANSI Class 150 Bolt Patterns
- Pressure rated to 150 psi @ 73°F
- Available in Buna-N, EPDM, or FKM

Flange Gaskets - Full-Faced Buna-N

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
GK1-005	1/2	1	25	017	3.39
GK1-007	3/4	1	25	017	3.88
GK1-010	1	1	25	017	4.00
GK1-012	1-1/4	1	25	017	4.09
GK1-015	1-1/2	1	25	017	4.40
GK1-020	2	1	25	017	4.92
GK1-025	2-1/2	1	25	017	5.41
GK1-030	3	1	25	017	8.33
GK1-040	4	1	25	017	9.31
GK1-050	5	1	25	017	11.03
GK1-060	6	1	25	017	11.34
GK1-080	8	1	25	017	14.95
GK1-100	10	1	25	017	18.97
GK1-120	12	1	25	017	25.59
GK1-140	14	1	25	017	49.49
GK1-160	16	1	25	017	238.12
GK1-180	18	1	25	017	271.19
GK1-240	24	1	25	017	327.69

Flange Gaskets - Full-Faced EPDM

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
GK2-005	1/2	1	25	017	4.49
GK2-007	3/4	1	25	017	4.79
GK2-010	1	1	25	017	5.00
GK2-012	1-1/4	1	25	017	5.25
GK2-015	1-1/2	1	25	017	5.64
GK2-020	2	1	25	017	6.88
GK2-025	2-1/2	1	25	017	8.26
GK2-030	3	1	25	017	12.15
GK2-040	4	1	25	017	13.83
GK2-050	5	1	25	017	17.29
GK2-060	6	1	25	017	18.15
GK2-080	8	1	25	017	24.18
GK2-100	10	1	25	017	31.51
GK2-120	12	1	25	017	43.35
GK2-140	14	1	25	017	105.74
GK2-160	16	1	25	017	187.60
GK2-180	18	1	25	017	219.12
GK2-200	20	1	25	017	254.32
GK2-240	24	1	25	017	383.93

Flange Gaskets - Full-Faced FKM

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
GK3-005	1/2	1	25	017	16.05
GK3-007	3/4	1	25	017	19.06
GK3-010	1	1	25	017	21.06
GK3-012	1-1/4	1	5	017	23.78
GK3-015	1-1/2	1	25	017	29.99
GK3-020	2	1	25	017	41.93
GK3-025	2-1/2	1	25	017	56.07
GK3-030	3	1	25	017	125.31
GK3-040	4	1	25	017	144.65
GK3-050	5	1	25	017	168.63
GK3-060	6	1	25	017	191.32
GK3-080	8	1	25	017	272.57
GK3-100	10	1	25	017	362.55
GK3-120	12	1	25	017	510.82
GK3-140	14	1	25	017	748.69
GK3-160	16	1	25	017	853.29
GK3-180	18	1	25	017	960.00
GK3-240	24	1	10	017	1222.01