



Pipe Flanges



PRODUCT

Contact Spears® for any Information not found.




Pipe Flanges

Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style -PIP

Flange x PIP Socket



125 psi Maximum Internal Pressure Rating @ 73°F (23°C)

354-060	6x6.140	5	0	080	119.39
354-060F	6X6.140	1	4	320	148.12
354-080	8X8.160	2	0	080	142.49
354-080F	8X8.160	1	2	320	224.28
354-100	10X10.200	2	0	081	297.78
354-100F	10X10.200	1	2	320	315.36
354-120	12X12.240	2	0	081	365.86
354-120F	12X12.240	1	2	320	456.75
354-150F	14X15.300	1	0	320	1217.46
354-151F	16X15.300	1	0	320	1388.87
354-181F	18X18.701	1	0	320	2109.93
354-182F	18X18.360	1	0	320	2109.93
354-201F	20X22.047	1	0	320	3213.86
354-241F	24X24.803	1	0	320	4706.61

For more information, refer to 80, 100 & 125 psi PIP Fabrication Fittings.

PIP = Plastic Irrigation Pipe (dimensions are NOT the same as IPS dimensions)

Sizes 6" - 16" are furnished with Glass Filled PVC ring.
 Sizes 18" - 24" are furnished with steel ring.

Flange One Piece

Socket



1/2" - 16" 150 psi Maximum Internal Pressure Rating @73°F (23°C)

18" - 24" 50 psi Maximum Internal Pressure Rating @73°F (23°C)

851-005	1/2	25	0	080	21.12
851-007	3/4	25	0	080	22.57
851-010	1	15	0	080	25.13
851-012	1-1/4	15	0	080	25.89
851-015	1-1/2	20	0	080	26.45
851-020	2	10	0	080	35.21
851-025	2-1/2	10	0	080	54.35
851-030	3	10	0	080	60.02
851-040	4	5	0	080	76.00
851-050	5	5	0	080	119.49
851-060	6	5	0	080	119.49
851-080	8	2	0	080	213.83
851-100F	10	1	2	083	581.05
851-120F	12	1	0	083	705.60
851-140F	14	1	0	083	1297.74
851-160F	16	1	0	083	1781.01
851-180F	18	1	0	083	3767.55
851-200F	20	1	0	083	4613.63
851-240F	24	1	0	083	6127.44

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange One Piece

Fipt



150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005	1/2	25	0	080	25.27
852-007	3/4	25	0	080	29.62
852-010	1	15	0	080	32.42
852-012	1-1/4	15	0	080	44.71
852-015	1-1/2	20	0	080	48.79
852-020	2	10	0	080	49.89
852-025	2-1/2	10	0	080	114.73
852-030	3	10	0	080	118.08
852-040	4	5	0	080	221.86
852-060F	6	1	8	083	266.54
852-080F	8	1	2	083	668.93

Flange - Special Reinforced One Piece

SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @73°F (23°C)

852-005SR	1/2	25	0	086	13.89
852-007SR	3/4	25	0	086	16.33
852-010SR	1	15	0	086	17.83
852-012SR	1-1/4	15	0	086	24.58
852-015SR	1-1/2	15	0	086	26.89
852-020SR	2	10	0	086	27.55
852-025SR	2-1/2	10	0	086	63.09
852-030SR	3	10	0	086	64.96
852-040SR	4	5	0	086	122.11

Flange - Blind

1/2" - 12" Molded - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

14" - 24" Fabricated - 50 psi Maximum Internal Pressure Rating @ 73°F (23°C)

853-005	1/2	25	0	080	29.61
853-007	3/4	25	0	080	35.25
853-010	1	15	0	080	48.16
853-012	1-1/4	20	0	080	59.12
853-015	1-1/2	15	0	080	59.12
853-020	2	10	0	080	88.34
853-025	2-1/2	10	0	080	143.91
853-030	3	10	0	080	173.66
853-040	4	8	0	080	216.34
853-050F	5	1	5	083	542.29
853-060	6	5	0	080	262.89
853-080	8	5	0	080	329.06
853-100	10	3	0	081	550.25
853-120	12	2	0	081	856.98

Schedule 40 Fittings Product
Pipe Flanges



Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Flange - Blind (continued)					
853-140F	14	1	0	083	1630.32
853-160F	16	1	0	083	1933.24
853-180F	18	1	0	083	2174.18
853-200F	20	1	0	083	3514.23
853-240F	24	1	0	083	4685.20

Flange Van Stone Style with PVC Ring

Socket



1/2" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)
18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005	1/2	25	0	080	21.08
854-007	3/4	25	0	080	22.56
854-010	1	15	0	080	25.12
854-012	1-1/4	15	0	080	25.87
854-015	1-1/2	20	0	080	26.39
854-020	2	10	0	080	35.16
854-025	2-1/2	10	0	080	54.29
854P-030	3	10	0	080	60.00
854P-040	4	5	0	080	75.88
854P-050	5	5	0	080	119.39
854P-060	6	5	0	080	119.39
854P-080	8	2	0	080	215.33
854P-100	10	2	0	081	251.69
854P-120	12	2	0	081	271.37
854P-140	14	1	0	082	1047.62
854P-160	16	1	0	082	1401.25
854P-180	18	1	0	082	2260.02
854-180FP	18	1	0	083	3575.76
854-200FP	20	1	0	083	4373.67
854-240FP	24	1	0	083	5949.64

Flange Van Stone Style with Glass Filled PVC Ring

Socket



3" - 18" molded - 150 psi = maximum internal pressure rating @ 73°F (23°C)

854-030	3	10	0	080	60.00
854-040	4	5	0	080	75.88
854-050	5	5	0	080	119.39
854-060	6	5	0	080	119.39
854-080	8	2	0	080	215.33
854-100	10	2	0	081	251.69
854-120	12	2	0	081	271.37
854-140	14	1	0	082	1047.62
854-160	16	1	0	082	1401.25
854-180	18	1	0	082	2260.02

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with Glass Filled PVC Ring (continued)

Socket

18" flange has 4-section ring

Flange Van Stone Style PVC with Solid Ring

Socket




150 psi Maximum Internal Pressure Rating @73°F (23°C)

S854-020	2	10	0	080	43.95
S854-030	3	10	0	080	75.02
S854-040	4	5	0	080	94.89

Flange Van Stone Style PVC with Glass Filled PVC Solid Ring

Socket



150 psi Maximum Internal Pressure Rating @73°F (23°C)

S854-060	6	5	0	080	149.26
S854-080	8	2	0	080	243.01
S854-100	10	2	0	081	314.60
S854-120	12	2	0	081	339.18

Flange Van Stone Style with Steel Ring

Socket



150 psi Maximum Internal Pressure Rating @73°F (23°C)

854-180FS	18	1	0	083	2110.97
854-200FS	20	1	0	083	2558.03
854-240FS	24	1	0	083	3442.71

Flange Van Stone Style Class 300 Bolt Pattern Fabricated with PVC Ring

Socket



1/2" - 16" molded with fab ring - 150 psi = maximum internal pressure rating @ 73°F (23°C)

18" - 24" fabricated - 50 psi = maximum internal pressure rating @ 73°F (23°C)

854-005CL300	1/2	1	25	083	173.36
854-007CL300	3/4	1	25	083	201.44
854-010CL300	1	1	15	083	316.51
854-012CL300	1-1/4	1	15	083	323.18
854-015CL300	1-1/2	1	20	083	335.72
854-020CL300	2	10	0	083	353.46
854-025CL300	2-1/2	1	10	083	388.12
854-030CL300	3	1	10	083	426.24
854-040CL300	4	3	0	083	722.75
854-060CL300	6	1	4	083	1376.58
854-080CL300	8	1	3	083	1566.92
854-100CL300	10	1	2	083	1844.69
854-120CL300	12	1	0	083	2363.43
854-140CL300	14	1	0	083	2605.91
854-160CL300	16	1	0	083	2713.77
854-180CL300	18	1	0	083	3794.27



Pipe Flanges

Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style Class 300 Bolt Pattern Fabricated with PVC Ring (continued)

Socket

854-200CL300	20	1	0	083	6578.47
854-240CL300	24	1	0	083	9663.20

Flange Van Stone Style with PVC Ring

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

855-005	1/2	25	0	080	25.23
855-007	3/4	25	0	080	29.61
855-010	1	15	0	080	32.38
855-012	1-1/4	15	0	080	44.62
855-015	1-1/2	20	0	080	48.75
855-020	2	10	0	080	49.87
855-025	2-1/2	10	0	080	114.64

Flange Van Stone Style with Glass Filled PVC Ring

Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

855-030	3	10	0	080	117.93
855-040	4	5	0	080	214.41
855-060	6	1	4	080	337.19
855-060F	6	1	4	083	299.72
855-080	8	2	0	080	417.83
855-080F	8	1	2	083	371.85
855-100F	10	1	2	083	418.94
855-120F	12	1	0	083	581.05

Flange Van Stone Style with PVC Ring

Spigot

1/2" - 16" = 150 psi maximum internal pressure rating @ 73°F (23°C)

18" - 24" = 50 psi maximum internal pressure rating @ 73°F (23°C)

856-005	1/2	25	0	080	21.21
856-007	3/4	25	0	080	22.73
856-010	1	15	0	080	25.33
856-012	1-1/4	15	0	080	26.13
856-015	1-1/2	15	0	080	26.65
856-020	2	10	0	080	35.42
856-025	2-1/2	10	0	080	54.75
856P-030	3	10	0	080	60.47
856P-040	4	5	0	080	76.52
856P-060	6	4	0	080	120.37
856P-080	8	2	0	080	215.33
856P-100	10	2	0	081	251.69

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with PVC Ring (continued)

Spigot

856P-120	12	2	0	081	271.37
856-200FP	20	1	0	083	4373.67
856-240FP	24	1	0	083	5949.64

Flange Van Stone Style with Glass Filled PVC Ring

Spigot

3" - 12" molded, 14" - 18" molded/fabricated - 150 psi = maximum internal pressure rating @ 73°F (23°C)

856-030	3	10	0	080	60.47
856-040	4	5	0	080	76.52
856-060	6	4	0	080	120.37
856-080	8	2	0	080	215.33
856-100	10	2	0	081	251.69
856-120	12	2	0	081	271.37
856-140FP	14	1	0	083	2247.51
856-160FP	16	1	0	083	2726.83
856-180FP	18	1	0	083	3575.76

** Fabricated from molded socket flanges with pipe spigot.
18" flange uses 4-piece ring

Flange Van Stone Style with Steel Ring

Spigot

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

856-140FS	14	1	0	083	1137.45
856-160FS	16	1	0	083	1390.31
856-180FS	18	1	0	083	1575.36
856-200FS	20	1	0	083	1897.49
856-240FS	24	1	0	083	2576.60

Flange, One Piece PVC Multi-Bolt Pattern*

ASTM Socket x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M851-100	10	2	0	081	221.32
M851-120	12	2	0	081	381.17

Hubs fit 10" and 12" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 10" and 12" in ANSI Class 150, B.S. 4504 PN10, B.S. 4504 PN16, Table E & JIS 10K for size 10", Table D & E for size 12" Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

Flange Van Stone Style with Multi-Bolt Pattern PVC Ring*

ASTM Socket x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M854-020	2	10	0	080	35.16
----------	---	----	---	-----	-------

Pipe Flanges & Van Stone Style Flange Replacement Split Rings



Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with Multi-Bolt Pattern PVC Ring*

(continued)

ASTM Socket x Multi-bolt Pattern Ring

* Hubs fit 2" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 2" in ANSI Class 150, B.S. 4504 PN10 B.S. 4504 PN16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

Flange Van Stone Style with Multi-Bolt Pattern Glass Filled PVC Ring*

ASTM Socket x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M854-060	6	5	0	080	119.39
M854-080	8	2	0	080	194.40

* Hubs fit 6" and 8" ASTM IPS pipe. Rings are manufactured to accept bolt patterns in size 6" and 8" in ANSI Class 150, B.S. 4504 PN10 B.S. 4504 PN16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

Flange Van Stone Style with Multi-Bolt Pattern PVC Ring*

ASTM Spigot x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M856-020	2	10	0	080	35.42
----------	---	----	---	-----	-------

* Spigots fit 2" ASTM IPS fitting socket. Rings are manufactured to accept bolt patterns in size 2" in ANSI Class 150, B.S. 4504 NP10 B.S. 4504 NP16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

Flange Van Stone Style with Multi-Bolt Pattern Glass Filled PVC Ring*

ASTM Spigot x Multi-bolt Pattern Ring

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

M856-060	6	4	0	080	120.37
M856-080	8	2	0	080	195.87

* Spigots fit 6" and 8" ASTM IPS fitting socket. Rings are manufactured to accept bolt patterns in size 6" and 8" in ANSI Class 150, B.S. 4504 PN10 B.S. 4504 PN16 (except 8"), B.S. 10 Table D and B.S. 10 Table E. Consult Spears® Manufacturing Company Technical Services for additional information. Not for use with wafer valves.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Van Stone Style with Multi-Bolt Pattern Glass Filled PVC Ring* (continued)

ASTM Spigot x Multi-bolt Pattern Ring

Application & Use of Van Stone Style Flange Replacement Split Rings

Designed for easy Van Stone style flange ring replacement in the event of system modification, repair, or improper assembly without having to remove existing flange hub. Split rings are made as a direct replacement of existing one-piece rings used on Spears® brand only of Van Stone style flanges with ANSI Class 150 bolt pattern plastic rings. Remove old ring to be replaced then simply place the split ring sections around hub and install flange bolts (not included) through special designed section overlap to hold in position. Install appropriate user supplied bolts, washers and gasket (see Flange Gasket and Bolt Hardware Kits in this catalog); torque to specifications according to normal flange assembly. Split rings are a set of either 2-pieces or 4-pieces (illustrated) sections depending on size, in regular PVC, Glass Filled PVC, or CPVC for flange type and sizes listed.



Van Stone Style Flange Replacement Split Rings

Flange Replacement Split Rings, PVC

For Spears® flanges with regular PVC Rings



854P-005-1S	1/2	10	0	080	64.13
854P-007-1S	3/4	10	0	080	68.07
854P-010-1S	1	15	0	080	76.14
854P-012-1S	1-1/4	15	0	080	77.62
854P-015-1S	1-1/2	10	0	080	79.53
854P-020-1S	2	10	0	080	105.54
854P-025-1S	2-1/2	10	0	080	122.09
854P-030-1S	3	10	0	080	135.37
854P-040-1S	4	1	10	080	145.12
854P-050-1S	5	5	0	080	196.52
854P-060-1S	6	5	0	080	232.55
854P-080-1S	8	4	0	080	265.69
854P-100-1S	10	4	0	081	335.41
854P-120-1S	12	2	0	081	415.73
854P-140-1S	14	2	0	082	569.41
854P-160-1S	16	4	0	082	707.37
854P-180-1S	18	1	0	082	768.26
854P-200-1S	20	1	0	083	4077.63
854P-240-1S	24	1	0	083	4996.13

Fits 854-xxx Socket, 855-xxx Threaded, and 856-xxx Spigot hub configurations

Flange Replacement Split Rings, Glass Filled PVC

For Spears® flanges with Glass Filled PVC Rings



854-030-1S	3	10	0	080	135.37
854-040-1S	4	10	0	080	145.12



Van Stone Style Flange Replacement Split Rings & Flange Bolt Kits

Van Stone Style Flange Replacement Split Rings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Replacement Split Rings, Glass Filled PVC (continued)

For Spears® flanges with Glass Filled PVC Rings

854-050-1S	5	5	0	080	196.52
854-060-1S	6	5	0	080	232.55
854-080-1S	8	4	0	080	265.69
854-100-1S	10	4	0	081	335.41
854-120-1S	12	2	0	081	415.73
854-140-1S	14	2	0	081	569.41
854-160-1S	16	1	0	082	707.37
854-180-1S	18	1	0	082	768.26

Fits 854-xxx Socket, 855-xxx Threaded, and 856-xxx Spigot hub configurations

Flange Bolt Kits

Flange Bolt Kit Selection Guide

Order Gaskets & Bolt Kits Separately

- Kit Contains All Bolts, Nuts, & Flat Washers for Specified Flange Size
- For Connecting Two (2) Mating Spears® Flanges
- Pre-coated, Anti-seize Lubricated Bolts
- Available in Zinc Coated Steel, Type 304 Stainless Steel or Type 316 Stainless Steel

Flange Size	Bolts* Per Kit	Diameter (in-TPI)	Length (in.)	Hardware Kit Part Numbers		
				Zinc	316 SS	304 SS
1/2	4	1/2-13	2	HK-005	HK1-005	HK2-005
3/4 & 1	4	1/2-13	2-1/4	HK-010	HK1-010	HK2-010
1-1/4 & 1-1/2	4	1/2-13	2-1/2	HK-015	HK1-015	HK2-015
2	4	5/8-11	3	HK-020	HK1-020	HK2-020
2-1/2	4	5/8-11	3-1/4	HK-025	HK1-025	HK2-025
3	4	5/8-11	3-1/2	HK-030	HK1-030	HK2-030
4	8	5/8-11	3-1/2	HK-040	HK1-040	HK2-040
5 & 6	8	3/4-10	4	HK-060	HK1-060	HK2-060
8	8	3/4-10	4-1/2	HK-080	HK1-080	HK2-080
10 & 12	12	7/8-9	5	HK-120	HK1-120	HK2-120

* Each Bolt Includes Nut & Two(2) Flat Washers

Flange Bolt Hardware Kits - Zinc Plated Steel

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts & Flat Washers



HK-005	1/2	1	10	017	11.71
HK-010	3/4 & 1	1	10	017	14.62
HK-015	1-1/4 & 1-1/2	1	10	017	21.98
HK-020	2	1	10	017	29.43

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange Bolt Hardware Kits - Zinc Plated Steel (continued)

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts & Flat Washers

HK-025	2-1/2	1	10	017	35.28
HK-030	3	1	10	017	40.60
HK-040	4	1	5	017	84.13
HK-060	5 & 6	1	5	017	93.55
HK-080	8	1	0	017	109.64
HK-120	10 & 12	1	0	017	148.34

Flange Bolt Hardware Kits - Type 316 Stainless Steel

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts & Flat Washers



HK1-005	1/2	1	10	017	35.12
HK1-010	3/4 & 1	1	10	017	50.58
HK1-015	1-1/4 & 1-1/2	1	10	017	55.73
HK1-020	2	1	10	017	67.01
HK1-025	2-1/2	1	10	017	71.83
HK1-030	3	1	10	017	94.78
HK1-040	4	1	5	017	190.07
HK1-060	5 & 6	1	5	017	247.91
HK1-080	8	1	0	017	311.06
HK1-120	10 & 12	1	0	017	632.84

Flange Bolt Hardware Kits - Type 304 Stainless Steel

For Connection of 2-Spears® Flanges Includes - Bolts, Nuts, & Flat Washers




HK2-005	1/2	1	10	017	30.73
HK2-010	3/4 & 1	1	10	017	43.82
HK2-015	1-1/4 & 1-1/2	1	10	017	51.62
HK2-020	2	1	10	017	60.72
HK2-025	2-1/2	1	10	017	64.39
HK2-030	3	1	10	017	79.96
HK2-040	4	1	5	017	159.91
HK2-060	5 & 6	1	5	017	168.56
HK2-080	8	1	0	017	221.63
HK2-120	10 & 12	1	0	017	392.81

Schedule 40 Fittings Product
Flange Gaskets - Full-Faced



Flange Gaskets - Full-Faced
Gasket Selection Guide



Flange Size	Bolt Holes	Gasket Part Number		
		Buna-N	EPDM	FKM
1/2	4	GK1-005	GK2-005	GK3-005
3/4	4	GK1-007	GK2-007	GK3-007
1	4	GK1-010	GK2-010	GK3-010
1-1/4	4	GK1-012	GK2-012	GK3-012
1-1/2	4	GK1-015	GK2-015	GK3-015
2	4	GK1-020	GK2-020	GK3-020
2-1/2	4	GK1-025	GK2-025	GK3-025
3	4	GK1-030	GK2-030	GK3-030
4	8	GK1-040	GK2-040	GK3-040
5	8	GK1-050	GK2-050	GK3-050
6	8	GK1-060	GK2-060	GK3-060
8	8	GK1-080	GK2-080	GK3-080
10	12	GK1-100	GK2-100	GK3-100
12	12	GK1-120	GK2-120	GK3-120

Order Gaskets & Bolt Kits Separately

- 1/8" Full-Face design with ANSI Class 150 Bolt Patterns
- Pressure rated to 150 psi @ 73°F
- Available in Buna-N, EPDM, or FKM

Flange Gaskets - Full-Faced Buna-N

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
GK1-005	1/2	1	25	017	3.76
GK1-007	3/4	1	25	017	4.29
GK1-010	1	1	25	017	4.62
GK1-012	1-1/4	1	25	017	5.10
GK1-015	1-1/2	1	25	017	5.28
GK1-020	2	1	25	017	7.30
GK1-025	2-1/2	1	25	017	9.53
GK1-030	3	1	25	017	11.54
GK1-040	4	1	25	017	17.70
GK1-050	5	1	25	017	18.74
GK1-060	6	1	25	017	19.06
GK1-080	8	1	25	017	24.94
GK1-100	10	1	25	017	37.31
GK1-120	12	1	25	017	55.84
GK1-140	14	1	25	017	77.35
GK1-160	16	1	25	017	124.40
GK1-180	18	1	25	017	183.69
GK1-240	24	1	25	017	243.55

Flange Gaskets - Full-Faced EPDM

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
GK2-005	1/2	1	25	017	4.98
GK2-007	3/4	1	25	017	5.31
GK2-010	1	1	25	017	5.54
GK2-012	1-1/4	1	25	017	5.82
GK2-015	1-1/2	1	25	017	6.25
GK2-020	2	1	25	017	7.97
GK2-025	2-1/2	1	25	017	10.24
GK2-030	3	1	25	017	12.77
GK2-040	4	1	25	017	18.81
GK2-050	5	1	25	017	25.35
GK2-060	6	1	25	017	25.71
GK2-080	8	1	25	017	38.01
GK2-100	10	1	25	017	41.66
GK2-120	12	1	25	017	57.78
GK2-140	14	1	25	017	96.89
GK2-160	16	1	25	017	131.12
GK2-180	18	1	25	017	197.68
GK2-200	20	1	25	017	230.32
GK2-240	24	1	25	017	255.04

Flange Gaskets - Full-Faced FKM

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
GK3-005	1/2	1	25	017	17.78
GK3-007	3/4	1	25	017	21.12
GK3-010	1	1	25	017	26.60
GK3-012	1-1/4	1	5	017	31.53
GK3-015	1-1/2	1	25	017	42.96
GK3-020	2	1	25	017	57.64
GK3-025	2-1/2	1	25	017	90.70
GK3-030	3	1	25	017	97.23
GK3-040	4	1	25	017	130.47
GK3-050	5	1	25	017	155.17
GK3-060	6	1	25	017	190.21
GK3-080	8	1	25	017	302.02
GK3-100	10	1	25	017	401.72
GK3-120	12	1	25	017	566.01
GK3-140	14	1	25	017	636.88
GK3-160	16	1	25	017	831.53
GK3-180	18	1	25	017	902.05
GK3-240	24	1	10	017	1324.66