



Schedule 40 Fittings Product

PVC White Schedule 40 - Hard to Find Configurations - Pool & Spa Specialties

PVC White Schedule 40 - Hard to Find Configurations - Pool & Spa Specialties



PRODUCT

Contact Spears® for any Information not found.

Schedule 40 Fittings Product
Pool & Spa Fittings



All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140°F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Short Socket Tees

Socket Style Sch 40

Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015	8.73
S401-251	2x2x1-1/2	25	0	015	8.73



Male Thread Tee (Branch)

Socket x Socket x Mipt

402B-010	1	50	0	040	3.83
----------	----------	----	---	-----	------



Spigot Tee, 2"

Spigot x Spigot x Spigot Sch 40

404A-020	2	30	0	015	9.11
----------	----------	----	---	-----	------



90° Ell, 2"x1-1/2" Reducing , Socket/Spigot

2"x2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015	10.96
----------	----------------	----	---	-----	-------



90° Ell 2-1/2"x2" Reducing Socket/Spigot

2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040	12.84
----------	-------------------------------	----	---	-----	-------



90° Spigot Ell, 1-1/2"

Spigot x Spigot Sch 40

422-015	1-1/2	25	0	015	8.80
---------	--------------	----	---	-----	------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

45° Street Ell -Short Spigot

Spigot x Socket Sch 40

Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015	7.77
----------	----------	----	---	-----	------



45° Street Ell

Spigot x Socket

427-005	1/2	50	400	040	1.18
427-007	3/4	50	0	040	1.82
427-010	1	50	0	040	2.19
427-012	1-1/4	25	0	040	3.06
427-015	1-1/2	25	0	040	3.83
427-020	2	25	0	040	5.00
427-025	2-1/2	10	0	040	16.26
427-030	3	10	0	040	20.20
427-040	4	5	0	040	36.21
427-050	5	4	0	040	108.88
427-060	6	4	0	040	111.84
427-080	8	2	0	040	269.01
427-100	10	1	0	041	707.83
427-120	12	1	0	041	1037.75
427-140F	14	1	0	047	773.40
427-160F	16	1	0	047	1051.22
427-180F	18	1	0	047	1147.51
427-200F	20	1	0	047	1456.54
427-240F	24	1	0	047	2294.32



22-1/2° Street Ell

Spigot x Socket

442-005	1/2	50	400	040	1.67
442-007	3/4	50	0	040	2.60
442-010	1	50	0	040	3.12
442-012	1-1/4	20	0	040	4.36
442-015	1-1/2	25	0	040	5.46
442-020	2	20	0	040	7.15
442-025F	2-1/2	1	18	047	40.47
442-030	3	5	0	040	41.75
442-040	4	4	0	040	64.43
442-060	6	4	0	040	159.07
442-060F	6	1	5	047	93.87
442-080	8	1	4	040	382.61
442-080F	8	1	4	047	141.39





Part Number	Size	Std PK	Mstr Ctn	Prod Code	MSRP
-------------	------	-----------	-------------	--------------	------

22-1/2° Street Ell (continued)

Spigot x Socket

442-100F	10	1	0	047	218.80
442-120F	12	1	0	047	328.43

Grated Coupling, 2" Sch 40

Socket Style Sch 40

Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015	4.80
-----------	---	----	---	-----	------

Smooth Barb Adapter

Spigot x Smooth Barb

Special adapter for making connections to Flexible Vinyl Hose

432-007525	3/4X1/2	100	600	015	2.06
432-007775	3/4	50	600	015	3.29
432-010775N	1(3/4)X3/4	50	400	015	3.44

"N" suffix indicates Nesting - Spigot also serves as size smaller socket

Venturied Tee, Multi Configuration - Socket Style Sch 40

1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015	8.66
473-210-3/8	with 3/8" Nozzle	25	0	015	8.66
473-210-1/4	with 1/4" Nozzle	25	0	015	8.66

Venturied Tee, Multi Configuration - Socket Style Sch 40

1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015	7.08
473-825-3/8	with 3/8" Nozzle	50	0	015	7.08
473-825-1/4	with 1/4" Nozzle	50	0	015	7.08

Venturied Tee, Multi Configuration - Socket Style Sch 40

Individual Nozzles Only

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015	2.28
473-2	1/4" Nozzle	100	600	015	2.28

Part Number	Size	Std PK	Mstr Ctn	Prod Code	MSRP
-------------	------	-----------	-------------	--------------	------

Venturied Tee, Multi Configuration - Socket Style Sch 40

(continued)

Individual Nozzles Only

473-3	3/8" Nozzle	100	600	015	2.28
-------	-------------	-----	-----	-----	------

120° Wye, 1-1/2"x1"x1"

Spigot x Socket x Socket Sch 40

Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015	12.33
------------	-----------	----	---	-----	-------

120° Wye, 2"

Socket

475-020120	2	10	0	015	14.47
------------	---	----	---	-----	-------

Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080	68.68
-----------	-------------	---	---	-----	-------

Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080	80.83
-----------	-------------	---	---	-----	-------