



Schedule 40 Fittings Product
Pool & Spa Fittings

All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140°F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Short Socket Tees

Socket Style Sch 40

Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015	8.29
S401-251	2x2x1-1/2	25	0	015	8.29



Male Thread Tee (Branch)

Socket x Socket x Mipt

402B-010	1	50	0	040	3.64
----------	----------	----	---	-----	------



Spigot Tee, 2"

Spigot x Spigot x Spigot Sch 40

404A-020	2	30	0	015	8.65
----------	----------	----	---	-----	------



90° Ell, 2"x1-1/2" Reducing , Socket/Spigot

2"x2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015	10.41
----------	----------------	----	---	-----	-------



90° Ell 2-1/2"x2" Reducing Socket/Spigot

2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040	12.20
----------	-------------------------------	----	---	-----	-------



90° Spigot Ell, 1-1/2"

Spigot x Spigot Sch 40

422-015	1-1/2	25	0	015	8.36
---------	--------------	----	---	-----	------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

45° Street Ell -Short Spigot

Spigot x Socket Sch 40

Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015	7.38
----------	----------	----	---	-----	------



45° Street Ell

Spigot x Socket

427-005	1/2	50	400	040	1.12
427-007	3/4	50	0	040	1.73
427-010	1	50	0	040	2.08
427-012	1-1/4	25	0	040	2.91
427-015	1-1/2	25	0	040	3.64
427-020	2	25	0	040	4.75
427-025	2-1/2	10	0	040	15.45
427-030	3	10	0	040	19.19
427-040	4	5	0	040	34.40
427-050	5	4	0	040	103.44
427-060	6	4	0	040	106.25
427-080	8	2	0	040	255.56
427-100	10	1	0	041	672.44
427-120	12	1	0	041	985.86
427-140F	14	1	0	047	734.73
427-160F	16	1	0	047	998.66
427-180F	18	1	0	047	1090.13
427-200F	20	1	0	047	1383.71
427-240F	24	1	0	047	2179.60



22-1/2° Street Ell

Spigot x Socket

442-005	1/2	50	400	040	1.59
442-007	3/4	50	0	040	2.47
442-010	1	50	0	040	2.96
442-012	1-1/4	20	0	040	4.14
442-015	1-1/2	25	0	040	5.19
442-020	2	20	0	040	6.79
442-025F	2-1/2	1	18	047	38.45
442-030	3	5	0	040	39.66
442-040	4	4	0	040	61.21
442-060	6	4	0	040	151.12
442-060F	6	1	5	047	89.18
442-080	8	1	4	040	363.48
442-080F	8	1	4	047	134.32



Schedule 40 Fittings Product
Pool & Spa Fittings



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
22-1/2° Street Ell (continued)					
Spigot x Socket					
442-100F	10	1	0	047	207.86
442-120F	12	1	0	047	312.01

Grated Coupling, 2" Sch 40

Socket Style Sch 40

Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015	4.56
-----------	----------	----	---	-----	------



Smooth Barb Adapter

Spigot x Smooth Barb

Special adapter for making connections to Flexible Vinyl Hose

432-007525	3/4X1/2	100	600	015	1.96
432-007775	3/4	50	600	015	3.13
432-010775N	1(3/4)X3/4	50	400	015	3.27

"N" suffix indicates Nesting - Spigot also serves as size smaller socket



Venturied Tee, Multi Configuration - Socket Style Sch 40

1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015	8.23
473-210-3/8	with 3/8" Nozzle	25	0	015	8.23
473-210-1/4	with 1/4" Nozzle	25	0	015	8.23



Venturied Tee, Multi Configuration - Socket Style Sch 40

1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015	6.73
473-825-3/8	with 3/8" Nozzle	50	0	015	6.73
473-825-1/4	with 1/4" Nozzle	50	0	015	6.73



Venturied Tee, Multi Configuration - Socket Style Sch 40

Individual Nozzles Only

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015	2.17
473-2	1/4" Nozzle	100	600	015	2.17



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Venturied Tee, Multi Configuration - Socket Style Sch 40 (continued)					
Individual Nozzles Only					
473-3	3/8" Nozzle	100	600	015	2.17

120° Wye, 1-1/2"x1"x1"

Spigot x Socket x Socket Sch 40

Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015	11.71
------------	------------------	----	---	-----	-------



120° Wye, 2"

Socket

475-020120	2	10	0	015	13.75
------------	----------	----	---	-----	-------



Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080	65.25
-----------	--------------------	---	---	-----	-------



Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080	76.79
-----------	--------------------	---	---	-----	-------

