

Schedule 40 Fittings Product
Pool & Spa Fittings



All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140°F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Short Socket Tees

Socket Style Sch 40

Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015	8.73
S401-251	2x2x1-1/2	25	0	015	8.73



Male Thread Tee (Branch)

Socket x Socket x Mipt

402B-010	1	50	0	040	3.83
----------	----------	----	---	-----	------



Spigot Tee, 2"

Spigot x Spigot x Spigot Sch 40

404A-020	2	30	0	015	9.11
----------	----------	----	---	-----	------



90° Ell, 2"x1-1/2" Reducing , Socket/Spigot

2"x2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015	10.96
----------	----------------	----	---	-----	-------



90° Ell 2-1/2"x2" Reducing Socket/Spigot

2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040	12.84
----------	-------------------------------	----	---	-----	-------



90° Spigot Ell, 1-1/2"

Spigot x Spigot Sch 40

422-015	1-1/2	25	0	015	8.80
---------	--------------	----	---	-----	------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

45° Street Ell -Short Spigot

Spigot x Socket Sch 40

Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015	7.77
----------	----------	----	---	-----	------



45° Street Ell

Spigot x Socket

427-005	1/2	50	400	040	1.18
427-007	3/4	50	0	040	1.82
427-010	1	50	0	040	2.19
427-012	1-1/4	25	0	040	3.06
427-015	1-1/2	25	0	040	3.83
427-020	2	25	0	040	5.00
427-025	2-1/2	10	0	040	16.26
427-030	3	10	0	040	20.20
427-040	4	5	0	040	36.21
427-050	5	4	0	040	108.88
427-060	6	4	0	040	111.84
427-080	8	2	0	040	269.01
427-100	10	1	0	041	707.83
427-120	12	1	0	041	1037.75
427-140F	14	1	0	047	773.40
427-160F	16	1	0	047	1051.22
427-180F	18	1	0	047	1147.51
427-200F	20	1	0	047	1456.54
427-240F	24	1	0	047	2294.32



22-1/2° Street Ell

Spigot x Socket

442-005	1/2	50	400	040	1.67
442-007	3/4	50	0	040	2.60
442-010	1	50	0	040	3.12
442-012	1-1/4	20	0	040	4.36
442-015	1-1/2	25	0	040	5.46
442-020	2	20	0	040	7.15
442-025F	2-1/2	1	18	047	40.47
442-030	3	5	0	040	41.75
442-040	4	4	0	040	64.43
442-060	6	4	0	040	159.07
442-060F	6	1	5	047	93.87
442-080	8	1	4	040	382.61
442-080F	8	1	4	047	141.39





Part Number	Size	Std PK	Mstr Ctn	Prod Code	MSRP
-------------	------	-----------	-------------	--------------	------

22-1/2° Street Ell (continued)**Spigot x Socket**

442-100F	10	1	0	047	218.80
442-120F	12	1	0	047	328.43

Grated Coupling, 2" Sch 40**Socket Style Sch 40**

Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015	4.80
-----------	---	----	---	-----	------

Smooth Barb Adapter**Spigot x Smooth Barb**

Special adapter for making connections to Flexible Vinyl Hose

432-007525	3/4X1/2	100	600	015	2.06
432-007775	3/4	50	600	015	3.29
432-010775N	1(3/4)X3/4	50	400	015	3.44

"N" suffix indicates Nesting - Spigot also serves as size smaller socket

Venturied Tee, Multi Configuration - Socket Style Sch 40**1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)**

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015	8.66
473-210-3/8	with 3/8" Nozzle	25	0	015	8.66
473-210-1/4	with 1/4" Nozzle	25	0	015	8.66

Venturied Tee, Multi Configuration - Socket Style Sch 40**1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)**

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015	7.08
473-825-3/8	with 3/8" Nozzle	50	0	015	7.08
473-825-1/4	with 1/4" Nozzle	50	0	015	7.08

Venturied Tee, Multi Configuration - Socket Style Sch 40**Individual Nozzles Only**

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015	2.28
473-2	1/4" Nozzle	100	600	015	2.28

Part Number	Size	Std PK	Mstr Ctn	Prod Code	MSRP
-------------	------	-----------	-------------	--------------	------

Venturied Tee, Multi Configuration - Socket Style Sch 40

(continued)

Individual Nozzles Only

473-3	3/8" Nozzle	100	600	015	2.28
-------	-------------	-----	-----	-----	------

120° Wye, 1-1/2"x1"x1"**Spigot x Socket x Socket Sch 40**

Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015	12.33
------------	-----------	----	---	-----	-------

120° Wye, 2"**Socket**

475-020120	2	10	0	015	14.47
------------	---	----	---	-----	-------

Nesting Union**2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring**

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080	68.68
-----------	-------------	---	---	-----	-------

Nesting Union**2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring**

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080	80.83
-----------	-------------	---	---	-----	-------