

**Standard Abbreviations**

CI	=	Cast Iron Pipe Size
CTS	=	Copper Tube Size
DWV	=	Drain, Waste & Vent
Fipt		
FPT	=	Female Iron Pipe Thread
GSK		
Gasket	=	Elastomer Gasket Sealed Connection
Grv		
Groove	=	Grooved End for Mechanical Coupling
IPS	=	Iron Pipe Size
INS		
Insert	=	Barbed Insert End
Mipt,		
MPT	=	Male Iron Pipe Thread
N	=	Nesting
NPT	=	National Pipe Thread (alternate to above)
PIP	=	Plastic Irrigation Pipe
PSI	=	Pounds Per Square Inch
PSM	=	Plastic Sewer Main
SDR	=	Standard Dimension Ratio (pipe)
Soc		
Socket	=	Solvent Weld Socket
SPG		
Spig		
Spigot	=	Spigot End (pipe O.D. size)
SR Fipt	=	Special Reinforced Plastic Female Iron Pipe Thread

DWV Specific Abbreviations

H		
HUB	=	Solvent Weld Socket
SPG	=	Spigot End (pipe O.D. size)
S&D	=	Sewer & Drain Pipe Size
SLIP	=	Trap End for Receiving Drain Tail Piece

Metric Specific Abbreviations

BAR	=	14.5 psi
BSP	=	British Standard Pipe
Class 10	=	Pressure Rating 10 BAR at 23°C (145 psi at 73°F)
Class 12	=	Pressure Rating 12 BAR at 23°C (174 psi at 73°F)
d	=	Pipe O.D. in millimeters
DN	=	Diameter Nominal for Metric Fittings
Din	=	Deutsche Industrial Norm (German Standards)
JIS	=	Japanese Industrial Standard
MIPT	=	Male Iron Pipe Thread
NPR	=	Not Pressure Rated
PN7	=	Pressure Rating 7 BAR at 23°C (100 psi at 73°F)
PN16	=	Pressure Rating 16 BAR at 23°C (232 psi at 73°F)
SRBSP	=	Special Reinforced BSP Thread
FBSP	=	Female BSP Thread
MBSP	=	Male BSP Thread
mm	=	Millimeter

Packaging Codes

MC (or Mstr Ctn)	=	Master Carton (standard master quantity)
SP (or Std Pk)	=	Standard Pack (standard box quantity)