

**Transition Fittings Product**  
**Special Reinforced (SR) & Metal Threaded Transition Fittings & Adapters**



**CTS CPVC Tan Special Reinforced (SR) Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Drop Ear 90° Ell - CPVC Zinc Reinforced(One Piece Unit)**

**Socket x SR Fipt - Zinc Collar**

NSF® Certified Lead Free

DEZ4107-005SR	1/2	10	150	035	19.44
---------------	-----	----	-----	-----	-------



**Drop Ear 90° Ell - Special Reinforced CPVC Fitting with Bracket**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead Free

DE4107-005SR	1/2	10	200	035	9.57
--------------	-----	----	-----	-----	------



**Female Adapter - CPVC Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead Free

4135-005SR	1/2	25	200	036	7.97
4135-007SR	3/4	25	300	036	8.76
4135-010SR	1	5	100	036	11.11



**Female Adapter - CPVC Reducing Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead Free

4135-131SR	1X3/4	25	150	036	15.47
------------	-------	----	-----	-----	-------



**Male Adapter - Internal Stainless Steel Reinforced**

**R Mipt x Socket - Stainless Steel Sleeve**

NSF® Certified Lead Free

4136-005R	1/2	25	300	036	10.22
4136-007R	3/4	25	300	036	11.36
4136-010R	1	10	120	036	16.93



**Union - Special Reinforced**

**Socket x SR Fipt - Stainless Steel Collar**

100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

4199-005SR	1/2	20	120	036	14.59
4199-007SR	3/4	10	60	036	25.04
4199-010SR	1	10	40	036	41.58



**CTS CPVC Tan Gasket Sealed Brass Thread Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Female Adapter - Gasket Sealed Brass Thread Transition**

**Socket x Gasket Fipt - Use NO Thread Sealant**

NSF® Certified Lead Free

4135-005BRG	1/2	25	150	033	14.93
4135-007BRG	3/4	25	150	033	19.77
4135-010BRG	1	15	90	033	68.26
4135-012BRG	1-1/4	15	60	033	114.43
4135-015BRG	1-1/2	10	40	033	130.28
4135-020BRG	2	8	32	033	203.66



**Female Adapter - Reducing Gasket Sealed Brass Thread Transition**

**Socket x Gasket Fipt - Use NO Thread Sealant**

NSF® Certified Lead Free

4135-101BRG	3/4X1/2	25	150	033	29.18
4135-130BRG	1X1/2	50	0	033	49.49



**Male Adapter - Transition with CPVC Lined Brass Thread**

**Brass Mipt x Socket**

NSF® Certified Lead Free

4136-005BR	1/2	60	360	033	17.91
4136-007BR	3/4	40	160	033	23.72
4136-010BR	1	10	60	033	81.92
4136-012BR	1-1/4	10	60	033	137.32
4136-015BR	1-1/2	10	40	033	156.34
4136-020BR	2	8	32	033	244.38



**Union - Gasket Sealed Brass Thread Transition**

**Socket x Gasket Fipt - Use No Thread Sealant**

100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

4199-005BRG	1/2	20	120	033	24.00
4199-007BRG	3/4	10	60	033	36.18
4199-010BRG	1	10	40	033	62.37

