



Transition Fittings Product
CPVC Orange Brass Thread Fittings & CPVC Orange Brass Grooved Coupling Adapter & Special Reinforced (SR) & Metal Threaded Transition Fittings & Adapters

CPVC Orange Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Sprinkler Head Adapter - Brass Thread Insert Style

Socket x Fipt



4235-101	3/4X1/2	50	0	076	12.35
4235-130	1X1/2	50	0	076	13.05
4235-131	1X3/4	50	0	076	18.81

Not intended to convey or dispense water for human consumption through drinking or cooking

Female Sprinkler Head Adapter - Brass Thread Insert Style with Long Body

Socket x Fipt



L4235-130	1X1/2	50	0	076	16.87
-----------	-------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Female Sprinkler Head Adapter - Brass Thread Insert Style with Positioning Ring

Socket x Fipt



R4235-101	3/4X1/2	50	0	076	11.16
-----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Male Adapter

MIPT x Socket



NSF® Certified Lead-Free

4236-007	3/4	40	160	076	45.94
4236-010	1	10	60	076	70.23
4236-012	1-1/4	10	40	076	83.99
4236-015	1-1/2	10	40	076	152.43
4236-020	2	8	32	076	202.84

Spigot Female Sprinkler Head Adapters - Brass Thread Insert Style

Spigot x Fipt



4238-101	3/4X1/2	50	200	076	11.16
4238-130	1X1/2	50	0	076	11.91

Not intended to convey or dispense water for human consumption through drinking or cooking

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

TorqueSafe™ Female Spigot Sprinkler Head Adapters - Gasket Sealed Brass Thread Insert Style

Spigot x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant



4238-101 G	3/4X1/2	50	200	076	11.16
4238-130 G	1X1/2	50	0	076	11.91

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking

Bushing - with Brass Thread Insert

Spigot x Fipt



4238-130BR	1X1/2	50	200	076	15.41
------------	-------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Spigot Female Adapter - Brass Thread Insert Style

Spigot x Fipt



4278-007	3/4	25	150	076	19.09
4278-010	1	15	90	076	34.01

Not intended to convey or dispense water for human consumption through drinking or cooking

CPVC Orange Brass Grooved Coupling Adapter

Grooved Coupling Adapter

Brass Groove End x Socket



4233-012	1-1/4	10	40	076	115.49
4233-015	1-1/2	10	40	076	122.41
4233-020	2	8	32	076	141.77
4233-025	2-1/2	5	0	076	181.85
4233-030	3	5	0	076	202.16

Not intended to convey or dispense water for human consumption through drinking or cooking

CTS CPVC Tan Special Reinforced (SR) Fittings

90° Ell - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead Free

4107-005SR	1/2	50	300	035	9.28
------------	-----	----	-----	-----	------

Transition Fittings Product

Special Reinforced (SR) & Metal Threaded Transition Fittings & Adapters



CTS CPVC Tan Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Drop Ear 90° Ell - CPVC Zinc Reinforced(One Piece Unit)

Socket x SR Fipt - Zinc Collar

NSF® Certified Lead Free

DEZ4107-005SR	1/2	10	150	035	19.44
---------------	-----	----	-----	-----	-------



Drop Ear 90° Ell - Special Reinforced CPVC Fitting with Bracket

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

DE4107-005SR	1/2	10	200	035	9.57
--------------	-----	----	-----	-----	------



Female Adapter - CPVC Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

4135-005SR	1/2	25	200	036	7.97
4135-007SR	3/4	25	300	036	8.76
4135-010SR	1	5	100	036	11.11



Female Adapter - CPVC Reducing Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

4135-131SR	1X3/4	25	150	036	15.47
------------	-------	----	-----	-----	-------



Male Adapter - Internal Stainless Steel Reinforced

R Mipt x Socket - Stainless Steel Sleeve

NSF® Certified Lead Free

4136-005R	1/2	25	300	036	10.22
4136-007R	3/4	25	300	036	11.36
4136-010R	1	10	120	036	16.93



Union - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

4199-005SR	1/2	20	120	036	14.59
4199-007SR	3/4	10	60	036	25.04
4199-010SR	1	10	40	036	41.58



CTS CPVC Tan Gasket Sealed Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Gasket Sealed Brass Thread Transition

Socket x Gasket Fipt - Use NO Thread Sealant

NSF® Certified Lead Free

4135-005BRG	1/2	25	150	033	14.93
4135-007BRG	3/4	25	150	033	19.77
4135-010BRG	1	15	90	033	68.26
4135-012BRG	1-1/4	15	60	033	114.43
4135-015BRG	1-1/2	10	40	033	130.28
4135-020BRG	2	8	32	033	203.66



Female Adapter - Reducing Gasket Sealed Brass Thread Transition

Socket x Gasket Fipt - Use NO Thread Sealant

NSF® Certified Lead Free

4135-101BRG	3/4X1/2	25	150	033	29.18
4135-130BRG	1X1/2	50	0	033	49.49



Male Adapter - Transition with CPVC Lined Brass Thread

Brass Mipt x Socket

NSF® Certified Lead Free

4136-005BR	1/2	60	360	033	17.91
4136-007BR	3/4	40	160	033	23.72
4136-010BR	1	10	60	033	81.92
4136-012BR	1-1/4	10	60	033	137.32
4136-015BR	1-1/2	10	40	033	156.34
4136-020BR	2	8	32	033	244.38



Union - Gasket Sealed Brass Thread Transition

Socket x Gasket Fipt - Use No Thread Sealant

100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

4199-005BRG	1/2	20	120	033	24.00
4199-007BRG	3/4	10	60	033	36.18
4199-010BRG	1	10	40	033	62.37

