

Transition Fittings Product

Special Reinforced (SR) & Metal Threaded Transition Fittings & Adapters



CTS CPVC Tan Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Drop Ear 90° Ell - CPVC Zinc Reinforced(One Piece Unit)

Socket x SR Fipt - Zinc Collar

NSF® Certified Lead Free

DEZ4107-005SR	1/2	10	150	035	20.46
---------------	-----	----	-----	-----	-------



Drop Ear 90° Ell - Special Reinforced CPVC Fitting with Bracket

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

DE4107-005SR	1/2	10	200	035	10.07
--------------	-----	----	-----	-----	-------



Female Adapter - CPVC Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

4135-005SR	1/2	25	200	036	8.39
4135-007SR	3/4	25	300	036	9.22
4135-010SR	1	5	100	036	11.69



Female Adapter - CPVC Reducing Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead Free

4135-131SR	1X3/4	25	150	036	16.28
------------	-------	----	-----	-----	-------



Male Adapter - Internal Stainless Steel Reinforced

R Mipt x Socket - Stainless Steel Sleeve

NSF® Certified Lead Free

4136-005R	1/2	25	300	036	10.76
4136-007R	3/4	25	300	036	11.96
4136-010R	1	10	120	036	17.82



Union - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

4199-005SR	1/2	20	120	036	15.36
4199-007SR	3/4	10	60	036	26.36
4199-010SR	1	10	40	036	43.77



CTS CPVC Tan Gasket Sealed Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Gasket Sealed Brass Thread Transition

Socket x Gasket Fipt - Use NO Thread Sealant

NSF® Certified Lead Free

4135-005BRG	1/2	25	150	033	15.72
4135-007BRG	3/4	25	150	033	20.81
4135-010BRG	1	15	90	033	71.85
4135-012BRG	1-1/4	15	60	033	120.45
4135-015BRG	1-1/2	10	40	033	137.14
4135-020BRG	2	8	32	033	214.38



Female Adapter - Reducing Gasket Sealed Brass Thread Transition

Socket x Gasket Fipt - Use NO Thread Sealant

NSF® Certified Lead Free

4135-101BRG	3/4X1/2	25	150	033	30.72
4135-130BRG	1X1/2	50	0	033	52.09



Male Adapter - Transition with CPVC Lined Brass Thread

Brass Mipt x Socket

NSF® Certified Lead Free

4136-005BR	1/2	60	240	033	18.85
4136-007BR	3/4	40	160	033	24.97
4136-010BR	1	10	60	033	86.23
4136-012BR	1-1/4	10	60	033	144.55
4136-015BR	1-1/2	10	40	033	164.57
4136-020BR	2	8	32	033	257.24



Union - Gasket Sealed Brass Thread Transition

Socket x Gasket Fipt - Use No Thread Sealant

100 psi Maximum Internal Pressure @ 180°F (82°C) -

NSF® Certified Lead Free

4199-005BRG	1/2	20	120	033	25.26
4199-007BRG	3/4	10	60	033	38.08
4199-010BRG	1	10	40	033	65.65

