#### **Transition Fittings Product**

### **CPVC Orange Brass Thread Fittings**



#### **CPVC Orange Brass Thread Fittings**

The CPVC Orange fittings in this section (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these systems, installation must be made in accordance with Spears® publication FG-3, FlameGuard® CPVC Fire Sprinkler Products Installation Instructions, and local codes. However, these fittings can also be used in many other types of installations, such as hot water distribution. CPVC fittings may also be used on PVC pipe when installed with a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings.

| Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings. |      |  |  |              |      |  |  |
|---|------|--|--|--------------|------|--|--|
| Part Number   | Size |  |  | Prod<br>Code | MSRP |  |  |

# Part Number Size Std Mstr Prod Code MSRP

TorqueSafe™ Sprinkler Head Tee - Gasket Sealed Brass Thread Insert Style

Socket x Gasket Fipt x Socket With Elastomer Seal - Use NO Thread Sealant

| 4203-122 G             | 1X1/2X1                | 50      | 0   | 076     | 27.46     |
|------------------------|------------------------|---------|-----|---------|-----------|
| FIPT With Elastomer Se | eal - Use NO Thread Se | alant   |     |         |           |
| Not intended to con    | vey or dispense wa     | ter for | hum | ian coi | nsumption |
| through drinking or co | ooking                 |         |     |         |           |

#### Sprinkler Head 90° Ell - Brass Thread Insert Style

#### Socket x Fipt

| 4207-101 | 3/4X1/2   | 20 | 120 | 076 | 10.23 |
|----------|-----------|----|-----|-----|-------|
| 4207-130 | 1X1/2     | 15 | 90  | 076 | 14.38 |
| 4207-131 | 1X3/4     | 25 | 0   | 076 | 17.40 |
| 4207-166 | 1-1/4X1/2 | 10 | 60  | 076 | 20.02 |
|          |           |    |     |     |       |

Not intended to convey or dispense water for human consumption through drinking or cooking

### TorqueSafe™ 90° Sprinkler Head Elbow - Gasket Sealed Brass Thread Insert Style

### Socket x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant

| 4207-101 G | 3/4X1/2   | 20 | 120 | 076 | 10.23 |
|------------|-----------|----|-----|-----|-------|
| 4207-130 G | 1X1/2     | 15 | 90  | 076 | 14.38 |
| 4207-166 G | 1-1/4X1/2 | 10 | 60  | 076 | 20.02 |

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking

#### Sprinkler Head Tee - Brass Thread Insert Style

#### Socket x Socket x Fipt

| 4202-101 | 3/4X1/2         | 50 | 0  | 076 | 15.48 |
|----------|-----------------|----|----|-----|-------|
| 4202-124 | 1X3/4X1/2       | 50 | 0  | 076 | 16.72 |
| 4202-130 | 1X1/2           | 50 | 0  | 076 | 16.72 |
| 4202-010 | 1               | 10 | 40 | 076 | 42.99 |
| 4202-156 | 1-1/4X1X1/2     | 15 | 0  | 076 | 27.87 |
| 4202-166 | 1-1/4X1/2       | 15 | 0  | 076 | 27.87 |
| 4202-199 | 1-1/2X1-1/4X1/2 | 10 | 0  | 076 | 36.72 |
| 4202-209 | 1-1/2X1/2       | 10 | 0  | 076 | 36.72 |
| 4202-237 | 2X1-1/2X1/2     | 10 | 0  | 076 | 51.78 |
| 4202-247 | 2X1/2           | 10 | 0  | 076 | 51.78 |

Not intended to convey or dispense water for human consumption through drinking or cooking

#### Sprinkler Head Tee - Brass Thread Insert Style

#### Socket x Fipt x Socket

| 4203-122               | 1X1/2X1               | 50     | 0   | 076    | 27.46     |
|------------------------|-----------------------|--------|-----|--------|-----------|
|                        | vey or dispense water | er for | hum | an coi | nsumption |
| through drinking or co | ooking                |        |     |        |           |

# TorqueSafe™ Sprinkler Head Tee - Gasket Sealed Brass Thread Insert Style

### Socket x Socket x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant

| 4202-101 G | 3/4X1/2   | 50 | 0 | 076 | 15.48 |
|------------|-----------|----|---|-----|-------|
| 4202-124 G | 1X3/4X1/2 | 50 | 0 | 076 | 16.72 |
| 4202-130 G | 1X1/2     | 50 | 0 | 076 | 16.72 |
| 4202-166 G | 1-1/4X1/2 | 15 | 0 | 076 | 27.87 |
| 4202-209 G | 1-1/2X1/2 | 10 | 0 | 076 | 36.72 |
| 4202-247 G | 2X1/2     | 10 | 0 | 076 | 51.78 |

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking

#### Female Adapter - Brass Thread Insert Style


#### Socket x Fipt

| 4235-007 | 3/4   | 15 | 90 | 076 | 20.41 |
|----------|-------|----|----|-----|-------|
| 4235-010 | 1     | 15 | 90 | 076 | 35.82 |
| 4235-012 | 1-1/4 | 15 | 60 | 076 | 58.40 |
| 4235-015 | 1-1/2 | 10 | 40 | 076 | 77.91 |
| 4235-020 | 2     | 8  | 32 | 076 | 97.64 |

Not intended to convey or dispense water for human consumption through drinking or cooking

## TorqueSafe™ Female Sprinkler Head Adapter - Gasket Sealed Brass Thread Insert Style

Socket x Gasket Fipt With Elastomer Seal - Use



| 4235-130GS             | 1X1/2                  | 50    | 0 | 076 | 14.12 |
|------------------------|------------------------|-------|---|-----|-------|
| FIPT With Elastomer Se | al - Use NO Thread Sea | lant. |   |     |       |

Not intended to convey or dispense water for human consumption through drinking or cooking





#### **Transition Fittings Product**

# CPVC Orange Brass Thread Fittings & CPVC Orange Brass Grooved Coupling Adapter & Special Reinforced (SR) & Metal Threaded Transition Fittings & Adapters

**CPVC Orange Brass Thread Fittings** 

| Part Number | Size |  |  | Prod<br>Code |  |
|-------------|------|--|--|--------------|--|
|-------------|------|--|--|--------------|--|

# Female Sprinkler Head Adapter - Brass Thread Insert Style



#### Socket x Fipt

| 4235-101 | 3/4X1/2 | 50 | 0 | 076 | 12.35 |
|----------|---------|----|---|-----|-------|
| 4235-130 | 1X1/2   | 50 | 0 | 076 | 13.05 |
| 4235-131 | 1X3/4   | 50 | 0 | 076 | 18.81 |

Not intended to convey or dispense water for human consumption through drinking or cooking

# Female Sprinkler Head Adapter - Brass Thread Insert Style with Long Body



#### Socket x Fipt

| L4235-130        |            | 1X1/2    | 5     | 50  | 0   | 076    | 16.87    |
|------------------|------------|----------|-------|-----|-----|--------|----------|
| Not intended to  | convey or  | dispense | water | for | hum | an con | sumption |
| through drinking | or cooking |          |       |     |     |        |          |

# Female Sprinkler Head Adapter - Brass Thread Insert Style with Positioning Ring



#### Socket x Fipt

| R4235-101            | 3/4X1/2              | 50    | 0   | 076    | 11.16     |
|----------------------|----------------------|-------|-----|--------|-----------|
| Not intended to con- | vev or dispense wate | r for | hum | an cor | nsumption |

Not intended to convey or dispense water for human consumption through drinking or cooking

#### Male Adapter



#### MIPT x Socket

| $NSF_{\mathbb{R}}$ | Certified | Lead-Free |
|--------------------|-----------|-----------|
|                    |           |           |

| 4236-007 | 3/4   | 40 | 160 | 076 | 45.94  |
|----------|-------|----|-----|-----|--------|
| 4236-010 | 1     | 10 | 60  | 076 | 70.23  |
| 4236-012 | 1-1/4 | 10 | 40  | 076 | 83.99  |
| 4236-015 | 1-1/2 | 10 | 40  | 076 | 152.43 |
| 4236-020 | 2     | 8  | 32  | 076 | 202.84 |

# Spigot Female Sprinkler Head Adapters - Brass Thread Insert Style



#### **Spigot x Fipt**

| 4238-130 <b>1X1/2</b> 50 0 07     | 76 11.91 |
|-----------------------------------|----------|
|                                   |          |
| 4238-101 <b>3/4X1/2</b> 50 200 07 | 76 11.16 |

Not intended to convey or dispense water for human consumption through drinking or cooking

## Part Number Size Std Mstr Prod Pk Ctn Code MSRP

TorqueSafe™ Female Spigot Sprinkler Head Adapters - Gasket Sealed Brass Thread Insert Style

Spigot x Gasket Fipt With Elastomer Seal - Use NO Thread Sealant

| 4238-101 G | 3/4X1/2 | 50 | 200 | 076 | 11.16 |
|------------|---------|----|-----|-----|-------|
| 4238-130 G | 1X1/2   | 50 | 0   | 076 | 11.91 |

FIPT With Elastomer Seal - Use NO Thread Sealant.

Not intended to convey or dispense water for human consumption through drinking or cooking

#### **Bushing - with Brass Thread Insert**



#### Spigot x Fipt

| 4238-1  | 130BR     |    |           |    | 1X1/2    |      | 50    | 200   | 076   | 15.41     |
|---------|-----------|----|-----------|----|----------|------|-------|-------|-------|-----------|
|         |           |    | •         |    | dispense | wate | er fo | r hum | an co | nsumption |
| through | i ariiiki | ng | or cookii | ıg |          |      |       |       |       |           |

#### Spigot Female Adapter - Brass Thread Insert Style



#### Spigot x Fipt

| 4278-007             | 3/4 | 25    | 150   | 076     | 19.09     |
|----------------------|-----|-------|-------|---------|-----------|
| 4278-010             | 1   | 15    | 90    | 076     | 34.01     |
| Not intended to con- |     | er fo | r hun | nan coi | nsumption |

#### **CPVC Orange Brass Grooved Coupling Adapter**

#### **Grooved Coupling Adapter**



#### **Brass Groove End x Socket**

| 4233-012 | 1-1/4 | 10 | 40 | 076 | 115.49 |
|----------|-------|----|----|-----|--------|
| 4233-015 | 1-1/2 | 10 | 40 | 076 | 122.41 |
| 4233-020 | 2     | 8  | 32 | 076 | 141.77 |
| 4233-025 | 2-1/2 | 5  | 0  | 076 | 181.85 |
| 4233-030 | 3     | 5  | 0  | 076 | 202.16 |

Not intended to convey or dispense water for human consumption through drinking or cooking

#### CTS CPVC Tan Special Reinforced (SR) Fittings





Socket x SR Fipt - Stainless Steel Collar

NSF<sub>®</sub> Certified Lead Free

| Troi & Columba Load Froo |     |    |     |     |      |  |  |
|--------------------------|-----|----|-----|-----|------|--|--|
| 4107-005SR               | 1/2 | 50 | 300 | 035 | 9.28 |  |  |