

**Transition Fittings Product**  
**CPVC Gray Brass Thread Fittings & CPVC Orange Special Reinforced (SR) Fittings**



**CPVC Gray Brass Thread Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**90° Ell - Brass Transition Reducing**

**Socket x Fipt With Brass Thread Insert**



807-101CBR	3/4X1/2	20	120	096	74.87
<b>Not intended to convey or dispense water for human consumption through drinking or cooking</b>					

**Female Adapter - Brass Transition**

**Socket x Fipt With Brass Thread Insert**



835-005CBR	1/2	25	150	096	36.91
835-007CBR	3/4	15	90	096	76.38
835-010CBR	1	15	90	096	134.04
835-012CBR	1-1/4	15	60	096	218.66
835-015CBR	1-1/2	10	40	096	288.29
835-020CBR	2	8	32	096	360.07
<b>Not intended to convey or dispense water for human consumption through drinking or cooking</b>					

**Female Adapter - Stainless Steel Transition**

**Socket x Fipt With Type 316 Stainless Steel Thread Insert**



NSF® Certified Lead Free

835-005CSS	1/2	25	150	096	72.46
835-007CSS	3/4	15	90	096	101.18
835-010CSS	1	15	90	096	177.06
835-012CSS	1-1/4	25	0	096	287.77
835-015CSS	1-1/2	10	40	096	375.41
835-020CSS	2	8	32	096	439.35

**Male Adapter - CPVC Lined Brass Transition**

**Brass Mipt x Socket**



NSF® Certified Lead Free

836-005CBR	1/2	40	160	096	81.81
836-007CBR	3/4	40	160	096	115.18
836-010CBR	1	10	60	096	200.60
836-012CBR	1-1/4	10	40	096	326.29
836-015CBR	1-1/2	10	40	096	424.21
836-020CBR	2	8	32	096	497.09

**Union - Socket/Brass Fipt/FKM**

**Socket x Fipt with Brass Thread Insert & FKM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007CBR	3/4	10	20	096	170.48
859-010CBR	1	10	0	096	189.88

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Union - Socket/Brass Fipt/FKM (continued)**

**Socket x Fipt with Brass Thread Insert & FKM O-ring Seal**

859-012CBR	1-1/4	5	0	096	318.31
859-015CBR	1-1/2	5	0	096	361.72
859-020CBR	2	5	0	096	408.82

**Not intended to convey or dispense water for human consumption through drinking or cooking**

**Union - Socket/Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007CBR	3/4	10	40	096	167.59
899-010CBR	1	10	0	096	187.55
899-012CBR	1-1/4	5	20	096	314.28
899-015CBR	1-1/2	5	0	096	357.09
899-020CBR	2	5	0	096	403.80

**Not intended to convey or dispense water for human consumption through drinking or cooking**

**CPVC Orange Special Reinforced (SR) Fittings**

The CPVC Orange fittings in this section (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these systems, installation must be made in accordance with Spears® publication FG-3, *FlameGuard® CPVC Fire Sprinkler Products Installation Instructions*, and local codes. However, these fittings can also be used in many other types of installations, such as hot water distribution. CPVC fittings may also be used on PVC pipe when installed with a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings.

**Sprinkler Head Tee - Special Reinforced Plastic Thread Style**

**Socket x Socket x SR Fipt - Stainless Steel Collar**



NSF® Certified Lead-Free

4202-010SR	1	15	0	076	22.84
4202-101SR	3/4X1/2	50	0	076	8.24
4202-124SR	1X3/4X1/2	50	0	076	8.91
4202-130SR	1X1/2	50	0	076	8.91
4202-156SR	1-1/4X1X1/2	15	0	076	14.84
4202-166SR	1-1/4X1/2	15	0	076	14.84
4202-168SR	1-1/4X1	15	0	076	31.89
4202-199SR	1-1/2X1-1/4X1/2	10	0	076	19.53
4202-209SR	1-1/2X1/2	25	0	076	19.53
4202-211SR	1-1/2X1-1/2X1	10	0	076	19.53
4202-237SR	2X1-1/2X1/2	10	0	076	27.56
4202-247SR	2X1/2	10	0	076	27.56
4202-287SR	2-1/2X1/2	10	0	076	37.77



Transition Fittings Product  
**CPVC Orange Special Reinforced (SR) Fittings**

**CPVC Orange Special Reinforced (SR) Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Sprinkler Head Tee - Special Reinforced Plastic Thread Style**

**Socket x SR Fipt x Socket - Stainless Steel Collar**

NSF® Certified Lead-Free

4203-122SR	1X1/2X1	50	0	076	9.57
------------	---------	----	---	-----	------



**Sprinkler Head 90° Ell - Special Reinforced Plastic Thread Style**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead-Free

4207-101SR	3/4X1/2	20	180	076	5.43
4207-130SR	1X1/2	10	150	076	7.66
4207-131SR	1X3/4	50	0	076	9.26
4207-166SR	1-1/4X1/2	25	0	076	9.73



**Female Adapter - Special Reinforced Plastic Thread Style**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead-Free

4235-007SR	3/4	25	300	076	9.68
4235-010SR	1	25	200	076	17.03
4235-012SR	1-1/4	10	60	076	27.73



**SofTorque™ SR Female Sprinkler Head Adapter - Gasket Sealed Special Reinforced Plastic Thread Style**

**Socket x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant**

NSF® Certified Lead-Free

4235-130GSR	1X1/2	50	0	076	11.60
-------------	-------	----	---	-----	-------



**Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead-Free

4235-101SR	3/4X1/2	50	200	076	5.92
4235-130SR	1X1/2	50	0	076	6.33
4235-131SR	1X3/4	50	0	076	10.02



**Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Socket Body Wrench Flats**

**Socket x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead-Free

W4235-101SR	3/4X1/2	50	0	076	6.75
W4235-130SR	1X1/2	50	0	076	7.22



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Positioning Ring**

**Socket x SR Fipt - Stainless Steel Collar**

R4235-101SR	3/4X1/2	25	300	076	6.68
-------------	---------	----	-----	-----	------



**Spigot Female Sprinkler Head Adapters - Special Reinforced Plastic Thread Style**

**Spigot x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead-Free

4238-101SR	3/4X1/2	50	400	076	5.92
4238-130SR	1X1/2	50	0	076	6.41



Part Number	Size	L - Max	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	---------	--------	----------	-----------	------

**Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style**

**Socket x SR Fipt - Stainless Steel Collar TRAVEL = 1-9/16"**

NSF® Certified Lead-Free

42001SR	3/4X1/2	8-1/4	12	0	076	15.11
42011SR	1X1/2	8-3/8	12	0	076	15.11

**L-Max = Maximum Adjustable Length**



**Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style**

**Spigot x SR Fipt - Stainless Steel Collar TRAVEL = 1-5/8"**

NSF® Certified Lead-Free

42004SR	3/4X1/2	8-1/4	12	0	076	15.11
42014SR	1X1/2	8-1/4	12	0	076	15.11

**L-Max = Maximum Adjustable Length**



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Spigot Female Adapter - Special Reinforced Plastic Thread Style**

**Spigot x SR Fipt - Stainless Steel Collar**

NSF® Certified Lead-Free

4278-007SR	3/4	25	300	076	10.17
4278-010SR	1	50	0	076	18.11

