

Transition Fittings Product
CPVC Gray Brass Thread Fittings & CPVC Orange Special Reinforced (SR) Fittings



CPVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

90° Ell - Brass Transition Reducing

Socket x Fipt With Brass Thread Insert



807-101CBR	3/4X1/2	20	120	096	71.13
Not intended to convey or dispense water for human consumption through drinking or cooking					

Female Adapter - Brass Transition

Socket x Fipt With Brass Thread Insert



835-005CBR	1/2	25	150	096	35.06
835-007CBR	3/4	15	90	096	72.56
835-010CBR	1	15	90	096	127.34
835-012CBR	1-1/4	15	60	096	207.73
835-015CBR	1-1/2	10	40	096	273.88
835-020CBR	2	8	32	096	342.07
Not intended to convey or dispense water for human consumption through drinking or cooking					

Female Adapter - Stainless Steel Transition

Socket x Fipt With Type 316 Stainless Steel Thread Insert



NSF® Certified Lead Free

835-005CSS	1/2	25	150	096	68.84
835-007CSS	3/4	15	90	096	96.12
835-010CSS	1	15	90	096	168.21
835-012CSS	1-1/4	25	0	096	273.38
835-015CSS	1-1/2	10	40	096	356.64
835-020CSS	2	8	32	096	417.38

Male Adapter - CPVC Lined Brass Transition

Brass Mipt x Socket



NSF® Certified Lead Free

836-005CBR	1/2	40	160	096	77.72
836-007CBR	3/4	40	160	096	109.42
836-010CBR	1	10	60	096	190.57
836-012CBR	1-1/4	10	40	096	309.98
836-015CBR	1-1/2	10	40	096	403.00
836-020CBR	2	8	32	096	472.24

Union - Socket/Brass Fipt/FKM

Socket x Fipt with Brass Thread Insert & FKM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007CBR	3/4	10	20	096	161.96
859-010CBR	1	10	0	096	180.39

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Socket/Brass Fipt/FKM (continued)

Socket x Fipt with Brass Thread Insert & FKM O-ring Seal

859-012CBR	1-1/4	5	0	096	302.39
859-015CBR	1-1/2	5	0	096	343.63
859-020CBR	2	5	0	096	388.38

Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007CBR	3/4	10	40	096	159.21
899-010CBR	1	10	0	096	178.17
899-012CBR	1-1/4	5	20	096	298.57
899-015CBR	1-1/2	5	0	096	339.24
899-020CBR	2	5	0	096	383.61

Not intended to convey or dispense water for human consumption through drinking or cooking

CPVC Orange Special Reinforced (SR) Fittings

The CPVC Orange fittings in this section (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these systems, installation must be made in accordance with Spears® publication FG-3, *FlameGuard® CPVC Fire Sprinkler Products Installation Instructions*, and local codes. However, these fittings can also be used in many other types of installations, such as hot water distribution. CPVC fittings may also be used on PVC pipe when installed with a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings.

Sprinkler Head Tee - Special Reinforced Plastic Thread Style

Socket x Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4202-010SR	1	15	0	076	22.84
4202-101SR	3/4X1/2	50	0	076	8.24
4202-124SR	1X3/4X1/2	50	0	076	8.91
4202-130SR	1X1/2	50	0	076	8.91
4202-156SR	1-1/4X1X1/2	15	0	076	14.84
4202-166SR	1-1/4X1/2	15	0	076	14.84
4202-168SR	1-1/4X1	15	0	076	31.89
4202-199SR	1-1/2X1-1/4X1/2	10	0	076	19.53
4202-209SR	1-1/2X1/2	25	0	076	19.53
4202-211SR	1-1/2X1-1/2X1	10	0	076	19.53
4202-237SR	2X1-1/2X1/2	10	0	076	27.56
4202-247SR	2X1/2	10	0	076	27.56
4202-287SR	2-1/2X1/2	10	0	076	37.77



Transition Fittings Product
CPVC Orange Special Reinforced (SR) Fittings

CPVC Orange Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Sprinkler Head Tee - Special Reinforced Plastic Thread Style

Socket x SR Fipt x Socket - Stainless Steel Collar



NSF® Certified Lead-Free

4203-122SR	1X1/2X1	50	0	076	9.57
------------	---------	----	---	-----	------

Sprinkler Head 90° Ell - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4207-101SR	3/4X1/2	20	180	076	5.43
4207-130SR	1X1/2	10	150	076	7.66
4207-131SR	1X3/4	50	0	076	9.26
4207-166SR	1-1/4X1/2	25	0	076	9.73

Female Adapter - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4235-007SR	3/4	25	300	076	9.68
4235-010SR	1	25	200	076	17.03
4235-012SR	1-1/4	10	60	076	27.73

SofTorque™ SR Female Sprinkler Head Adapter - Gasket Sealed Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant



NSF® Certified Lead-Free

4235-130GSR	1X1/2	50	0	076	11.60
-------------	-------	----	---	-----	-------

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4235-101SR	3/4X1/2	50	200	076	5.92
4235-130SR	1X1/2	50	0	076	6.33
4235-131SR	1X3/4	50	0	076	10.02

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Socket Body Wrench Flats

Socket x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

W4235-101SR	3/4X1/2	50	0	076	6.75
W4235-130SR	1X1/2	50	0	076	7.22

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Positioning Ring

Socket x SR Fipt - Stainless Steel Collar



R4235-101SR	3/4X1/2	25	300	076	6.68
-------------	---------	----	-----	-----	------

Spigot Female Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4238-101SR	3/4X1/2	50	400	076	5.92
4238-130SR	1X1/2	50	0	076	6.41

Part Number	Size	L - Max	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	---------	--------	----------	-----------	------

Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar TRAVEL = 1-9/16"



NSF® Certified Lead-Free

42001SR	3/4X1/2	8-1/4	12	0	076	15.11
42011SR	1X1/2	8-7/16	12	0	076	15.11

L-Max = Maximum Adjustable Length

Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar TRAVEL = 1-5/8"



NSF® Certified Lead-Free

42004SR	3/4X1/2	8-1/4	12	0	076	15.11
42014SR	1X1/2	8-1/4	12	0	076	15.11

L-Max = Maximum Adjustable Length

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Spigot Female Adapter - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar



NSF® Certified Lead-Free

4278-007SR	3/4	25	300	076	10.17
4278-010SR	1	50	0	076	18.11