

Transition Fittings Product
CPVC Gray Brass Thread Fittings & CPVC Orange Special Reinforced (SR) Fittings



CPVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Stainless Steel Transition (continued)

Socket x Fipt With Type 316 Stainless Steel Thread Insert

835-007CSS	3/4	15	90	096	91.31
835-010CSS	1	15	90	096	159.80
835-012CSS	1-1/4	25	0	096	259.71
835-015CSS	1-1/2	10	40	096	338.81
835-020CSS	2	8	32	096	396.51

Male Adapter - CPVC Lined Brass Transition



Brass Mipt x Socket

NSF® Certified Lead Free

836-005CBR	1/2	40	160	096	73.83
836-007CBR	3/4	40	160	096	103.95
836-010CBR	1	10	60	096	181.04
836-012CBR	1-1/4	10	40	096	294.48
836-015CBR	1-1/2	10	40	096	382.85
836-020CBR	2	8	32	096	448.63

Union - Socket/Brass Fipt/FKM



Socket x Fipt with Brass Thread Insert & FKM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007CBR	3/4	10	20	096	153.86
859-010CBR	1	10	0	096	171.37
859-012CBR	1-1/4	5	0	096	287.27
859-015CBR	1-1/2	5	0	096	326.45
859-020CBR	2	5	0	096	368.96

Not intended to convey or dispense water for human consumption through drinking or cooking

Union - Socket/Brass Fipt/EPDM



Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007CBR	3/4	10	40	096	151.25
899-010CBR	1	10	0	096	169.26
899-012CBR	1-1/4	5	20	096	283.64
899-015CBR	1-1/2	5	0	096	322.28
899-020CBR	2	5	0	096	364.43

Not intended to convey or dispense water for human consumption through drinking or cooking

CPVC Orange Special Reinforced (SR) Fittings

The CPVC Orange fittings in this section (4200 series part numbers) are approved by Underwriters Laboratories, FM Global, and LPCB for use in CPVC Fire Sprinkler Systems. When installed in these systems, installation must be made in accordance with Spears® publication FG-3, *FlameGuard® CPVC Fire Sprinkler Products Installation Instructions*, and local codes. However, these fittings can also be used in many other types of installations, such as hot water distribution. CPVC fittings may also be used on PVC pipe when installed with a quality CPVC solvent cement meeting the requirements of ASTM F 493, Standard Specification for Solvent Cements for Chlorinated Poly (Vinyl Chloride) (CPVC) Plastic Pipe and Fittings.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Sprinkler Head Tee - Special Reinforced Plastic Thread Style



Socket x Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4202-010SR	1	15	0	076	21.70
4202-101SR	3/4X1/2	50	0	076	7.83
4202-124SR	1X3/4X1/2	50	0	076	8.46
4202-130SR	1X1/2	50	0	076	8.46
4202-156SR	1-1/4X1X1/2	15	0	076	14.10
4202-166SR	1-1/4X1/2	15	0	076	14.10
4202-168SR	1-1/4X1	15	0	076	30.30
4202-199SR	1-1/2X1-1/4X1/2	10	0	076	18.55
4202-209SR	1-1/2X1/2	25	0	076	18.55
4202-211SR	1-1/2X1-1/2X1	10	0	076	18.55
4202-237SR	2X1-1/2X1/2	10	0	076	26.18
4202-247SR	2X1/2	10	0	076	26.18
4202-287SR	2-1/2X1/2	10	0	076	35.88

Sprinkler Head Tee - Special Reinforced Plastic Thread Style



Socket x SR Fipt x Socket - Stainless Steel Collar

NSF® Certified Lead-Free

4203-122SR	1X1/2X1	50	0	076	9.09
------------	---------	----	---	-----	------

Sprinkler Head 90° Ell - Special Reinforced Plastic Thread Style



Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4207-101SR	3/4X1/2	20	180	076	5.16
4207-130SR	1X1/2	10	150	076	7.28
4207-131SR	1X3/4	50	0	076	8.80
4207-166SR	1-1/4X1/2	25	0	076	9.24



Transition Fittings Product
CPVC Orange Special Reinforced (SR) Fittings

CPVC Orange Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4235-007SR	3/4	25	300	076	9.20
4235-010SR	1	25	200	076	16.18
4235-012SR	1-1/4	10	60	076	26.34



SofTorque™ SR Female Sprinkler Head Adapter - Gasket Sealed Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar With Elastomer Seal - Use NO Thread Sealant

NSF® Certified Lead-Free

4235-130GSR	1X1/2	50	0	076	11.02
-------------	-------	----	---	-----	-------



Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4235-101SR	3/4X1/2	50	200	076	5.62
4235-130SR	1X1/2	50	0	076	6.01
4235-131SR	1X3/4	50	0	076	9.52



Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Socket Body Wrench Flats

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

W4235-101SR	3/4X1/2	50	0	076	6.41
W4235-130SR	1X1/2	50	0	076	6.86



Female Sprinkler Head Adapter - Special Reinforced Plastic Thread Style with Positioning Ring

Socket x SR Fipt - Stainless Steel Collar

R4235-101SR	3/4X1/2	25	300	076	6.35
-------------	---------	----	-----	-----	------



Spigot Female Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4238-101SR	3/4X1/2	50	400	076	5.62
4238-130SR	1X1/2	50	0	076	6.09



Part Number	Size	L - Max	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	---------	--------	----------	-----------	------


Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Socket x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

42001SR	3/4X1/2	8-11/32	12	0	076	14.35
42011SR	1X1/2	8-7/16	12	0	076	14.35

L-Max = Maximum Adjustable Length




Adjustable Sprinkler Head Adapters - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

42004SR	3/4X1/2	8-11/32	12	0	076	14.35
42014SR	1X1/2	8-13/32	12	0	076	14.35

L-Max = Maximum Adjustable Length



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Spigot Female Adapter - Special Reinforced Plastic Thread Style

Spigot x SR Fipt - Stainless Steel Collar

NSF® Certified Lead-Free

4278-007SR	3/4	25	300	076	9.66
4278-010SR	1	50	0	076	17.20

