



Transition Fittings Product

PVC Gray Brass Thread Fittings & CPVC Gray Special Reinforced (SR) Fittings

PVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007BR	3/4	10	60	086	55.94
899-010BR	1	10	0	086	75.43
899-012BR	1-1/4	5	20	086	126.86
899-015BR	1-1/2	5	0	086	167.92
899-020BR	2	5	0	086	223.81

Not intended to convey or dispense water for human consumption through drinking or cooking

CPVC Gray Special Reinforced (SR) Fittings

Tee - Special Reinforced

Socket x Socket x SR Fipt - Stainless Steel Collar



802-005CSR	1/2	50	0	096	22.95
802-007CSR	3/4	15	120	096	33.53
802-010CSR	1	15	0	096	42.18
802-012CSR	1-1/4	15	0	096	48.94
802-015CSR	1-1/2	10	0	096	48.94
802-020CSR	2	10	0	096	80.00
802-030CSR	3	5	0	096	115.21
802-040CSR	4	5	0	096	217.04

Tee - Special Reinforced

SR Fipt x SR Fipt x SR Fipt - Stainless Steel Collar



805-002CSR	1/4	25	150	096	20.54
805-003CSR	3/8	25	150	096	20.54
805-005CSR	1/2	25	150	096	27.46
805-007CSR	3/4	25	100	096	31.46
805-010CSR	1	15	0	096	46.99
805-015CSR	1-1/2	10	0	096	49.89
805-020CSR	2	10	0	096	59.41

Tee - Special Reinforced Reducing

Socket x Socket x SR Fipt - Stainless Steel Collar



802-072CSR	1/2X1/4	25	200	096	22.95
802-098CSR	3/4X1/4	25	100	096	30.66
802-101CSR	3/4X1/2	50	0	096	30.66
802-128CSR ¹	1X1/4	15	0	096	47.36
802-130CSR	1X1/2	50	0	096	18.74
802-131CSR	1X3/4	15	0	096	47.36
802-164CSR ¹	1-1/4X1/4	5	0	096	62.97
802-166CSR	1-1/4X1/2	15	0	096	49.88

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tee - Special Reinforced Reducing (continued)

Socket x Socket x SR Fipt - Stainless Steel Collar

802-168CSR	1-1/4X1	10	0	096	50.91
802-207CSR ¹	1-1/2X1/4	15	0	096	90.17
802-211CSR	1-1/2X1	10	0	096	59.77
802-212CSR	1-1/2X1-1/4	10	0	096	59.77
802-245CSR ¹	2X1/4	10	0	096	103.57
802-247CSR	2X1/2	10	0	096	93.23
802-248CSR	2X3/4	10	0	096	103.57
802-287CSR	2-1/2X1/2	10	0	096	71.22
802-331CSR ¹	3X1/4	5	0	096	197.84
802-413CSR ¹	4X1/4	5	0	096	214.68

¹ Sized with Bushing

Tee - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar x Socket



(See also Gauge & Instrument Fittings for additional configurations)

803-095CSR	3/4X1/2X3/4	15	0	096	18.89
------------	-------------	----	---	-----	-------

90° Ell - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



807-005CSR	1/2	20	240	096	11.14
807-007CSR	3/4	75	0	096	13.08
807-010CSR	1	50	0	096	15.76
807-012CSR	1-1/4	25	0	096	32.54
807-015CSR	1-1/2	10	0	096	39.11
807-020CSR	2	10	0	096	48.93

90° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



808-003CSR	3/8	25	150	096	6.73
808-005CSR	1/2	20	120	096	6.73
808-007CSR	3/4	20	160	096	9.85
808-010CSR	1	50	0	096	12.63
808-012CSR	1-1/4	25	0	096	24.31
808-015CSR	1-1/2	10	0	096	28.62
808-020CSR	2	10	0	096	38.34

90° Ell - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar



807-101CSR	3/4X1/2	50	0	096	14.19
807-130CSR	1X1/2	50	0	096	15.31

Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings



CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

45° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar

819-007CSR	3/4	10	120	096	15.38
------------	-----	----	-----	-----	-------



Coupling - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar

830-005CSR	1/2	25	150	096	10.86
830-007CSR	3/4	25	150	096	17.54
830-010CSR	1	25	200	096	19.93
830-012CSR	1-1/4	10	120	096	21.18
830-015CSR	1-1/2	10	80	096	22.69
830-020CSR	2	10	0	096	26.82



Coupling - Special Reinforced Reducer

SR Fipt x SR Fipt - Stainless Steel Collar

830-101CSR	3/4X1/2	50	200	096	19.45
830-130CSR	1X1/2	50	0	096	23.49
830-131CSR	1X3/4	25	200	096	23.49
830-168CSR	1-1/4X1	25	0	096	31.95
830-210CSR	1-1/2X3/4	25	0	096	45.68
830-211CSR	1-1/2X1	10	80	096	45.68
830-212CSR	1-1/2X1-1/4	10	80	096	45.68
830-249CSR	2X1	25	0	096	112.45
830-251CSR	2X1-1/2	15	0	096	112.45



Female Adapter - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

835-002CSR	1/4	25	450	096	15.23
835-003CSR	3/8	25	300	096	15.23
835-005CSR	1/2	25	150	096	6.55
835-007CSR	3/4	25	150	096	7.07
835-010CSR	1	25	200	096	16.13
835-012CSR	1-1/4	10	60	096	16.55
835-015CSR	1-1/2	10	80	096	19.20
835-020CSR	2	10	0	096	27.28
835-025CSR	2-1/2	5	0	096	63.43
835-030CSR	3	15	0	096	130.34
835-040CSR	4	5	0	096	216.93
835-060CSR	6	6	0	096	338.88



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Encapsulated Special Reinforced

Socket x ESR Fipt

835-002CESR	1/4	25	450	096	19.33
835-003CESR	3/8	25	300	096	19.33
835-005CESR	1/2	25	300	096	10.03
835-007CESR	3/4	25	300	096	10.59
835-010CESR	1	25	200	096	23.34
835-012CESR	1-1/4	10	80	096	23.88
835-015CESR	1-1/2	10	80	096	30.94
835-020CESR	2	10	0	096	48.07



Female Spigot Adapter - Special Reinforced

Spigot x SR Fipt - Stainless Steel Collar

878-005CSR	1/2	50	600	096	6.97
878-007CSR	3/4	25	300	096	7.36
878-010CSR	1	50	0	096	16.56
878-012CSR	1-1/4	25	0	096	17.12
878-015CSR	1-1/2	25	0	096	19.87
878-020CSR	2	15	0	096	36.20
878-030CSR	3	5	0	096	131.98
878-040CSR	4	5	0	096	221.55



Female Adapter - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar

835-074CSR	1/2X3/4	50	400	096	7.07
835-101CSR	3/4X1/2	50	400	096	7.07
835-102CSR	3/4X1	50	0	096	16.13
835-130CSR	1X1/2	50	0	096	16.13
835-131CSR	1X3/4	25	200	096	16.13



Female Spigot Adapter - Encapsulated Special Reinforced

Spigot x ESR Fipt

878-005CESR	1/2	50	600	096	10.33
878-007CESR	3/4	25	300	096	10.99
878-010CESR	1	50	0	096	23.56
878-012CESR	1-1/4	25	0	096	24.20
878-015CESR	1-1/2	25	0	096	31.55
878-020CESR	2	15	0	096	48.77



Female Spigot Adapter - Special Reinforced Reducing

Spigot x SR Fipt - Stainless Steel Collar

878-072CSR	1/2X1/4	25	450	096	19.99
878-098CSR	3/4X1/4	50	300	096	23.27
878-128CSR	1X1/4	50	400	096	26.05





Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Male Adapter - Internal Reinforced

R Mipt x Socket - Stainless Steel Sleeve



NSF® Certified Lead Free

836-005CR	1/2	25	150	096	10.05
836-007CR	3/4	25	300	096	11.52
836-010CR	1	10	120	096	13.66
836-012CR	1-1/4	10	60	096	27.97
836-015CR	1-1/2	10	120	096	37.73
836-020CR	2	10	0	096	51.04

Reducer Bushing - Special Reinforced Reducing Flush Style

Mipt x SR Fipt - Stainless Steel Collar



839-209CSR	1-1/2X1/2	25	300	096	25.78
839-210CSR	1-1/2X3/4	25	300	096	25.78
839-247CSR	2X1/2	10	60	096	28.49
839-248CSR	2X3/4	10	60	096	28.49
839-249CSR	2X1	10	120	096	28.49
839-420CSR	4X2	6	0	096	158.23

Reducer Bushing - Special Reinforced

Spigot x SR Fipt - Stainless Steel Collar



838-128CSR	1X1/4	25	150	096	14.86
838-207CSR	1-1/2X1/4	25	200	096	25.13
838-209CSR	1-1/2X1/2	10	120	096	26.19
838-210CSR	1-1/2X3/4	10	120	096	26.19
838-247CSR	2X1/2	10	80	096	35.99
838-248CSR	2X3/4	10	80	096	35.99
838-249CSR	2X1	10	120	096	35.99
838-334CSR	3X3/4	10	0	096	152.42
838-335CSR	3X1	10	0	096	152.42
838-336CSR	3X1-1/4	10	0	096	152.42
838-337CSR	3X1-1/2	10	0	096	152.42
838-528CSR	6X2	5	0	096	524.01
838-530CSR	6X3	5	0	096	524.01

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar



848-002CSR	1/4	25	500	096	8.23
848-003CSR	3/8	25	450	096	8.23
848-007CSR	3/4	25	300	096	12.83
848-030CSR	3	5	0	096	143.22

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	120	096	18.44
8099-007CSR	3/4	20	160	096	32.75
8099-010CSR	1	15	90	096	45.34
8099-012CSR	1-1/4	10	0	096	85.89
8099-015CSR	1-1/2	10	0	096	93.42
8099-020CSR	2	5	0	096	98.37
8099-025CSR	2-1/2	5	0	096	168.72
8099-030CSR	3	5	0	096	274.04
8099-040CSR	4	4	0	096	321.83
8099-060CSR	6	1	0	096	715.20

Union 2000 - Special Reinforced

Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	25	200	096	18.81
8059-007CSR	3/4	20	160	096	33.19
8059-010CSR	1	15	90	096	45.72
8059-012CSR	1-1/4	10	0	096	87.17
8059-015CSR	1-1/2	10	0	096	94.76
8059-020CSR	2	5	0	096	98.65
8059-030CSR	3	5	0	096	277.52
8059-040CSR	4	4	0	096	323.78

Union 2000 - Special Reinforced Fipt/FKM

SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	120	096	19.31
8058-007CSR	3/4	20	80	096	33.65
8058-010CSR	1	15	90	096	46.25
8058-012CSR	1-1/4	10	0	096	87.17
8058-015CSR	1-1/2	10	0	096	95.13
8058-020CSR	2	5	0	096	100.23
8058-030CSR	3	5	0	096	283.24
8058-040CSR	4	4	0	096	331.83
8058-060CSR	6	1	0	096	747.32

Union 2000 - Special Reinforced Fipt/EPDM

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar



1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	18.66
-------------	-----	----	-----	-----	-------

Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings



CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/EPDM (continued)

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

8098-007CSR	3/4	20	80	096	33.34
8098-010CSR	1	15	90	096	45.72
8098-012CSR	1-1/4	10	0	096	86.33
8098-015CSR	1-1/2	10	0	096	94.39
8098-020CSR	2	5	0	096	99.24
8098-025CSR	2-1/2	5	0	096	171.52
8098-030CSR	3	5	0	096	278.86
8098-040CSR	4	4	0	096	322.83
8098-060CSR	6	1	0	096	171.41

Union (Old Style) - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	29.41
899-003CSR	3/8	25	100	096	29.41
899-005CSR	1/2	10	60	096	18.44
899-007CSR	3/4	10	40	096	32.75
899-010CSR	1	10	40	096	45.34
899-012CSR	1-1/4	5	20	096	85.89
899-015CSR	1-1/2	5	0	096	93.42
899-020CSR	2	5	0	096	98.37
899-030CSR	3	5	0	096	274.04
899-040CSR	4	4	0	096	321.83

Union (Old Style) - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	29.61
859-003CSR	3/8	25	100	096	29.61
859-005CSR	1/2	10	60	096	18.81
859-007CSR	3/4	10	60	096	33.19
859-010CSR	1	10	40	096	45.72
859-012CSR	1-1/4	5	20	096	87.17
859-015CSR	1-1/2	5	0	096	94.76
859-020CSR	2	5	0	096	98.65
859-030CSR	3	5	0	096	277.52
859-040CSR	4	4	0	096	323.78

Flange - Special Reinforced One Piece Threaded

SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	24.08
852-007CSR	3/4	25	0	096	29.22
852-010CSR	1	15	0	096	31.97
852-012CSR	1-1/4	15	0	096	44.24

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange - Special Reinforced One Piece Threaded (continued)

SR Fipt - Stainless Steel Collar

852-015CSR	1-1/2	15	0	096	46.91
852-020CSR	2	10	0	096	48.04
852-025CSR	2-1/2	10	0	096	77.29
852-030CSR	3	10	0	096	76.69
852-040CSR	4	5	0	096	143.73

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets



Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	58.08
8171-003CSR	3/8	25	200	101	58.08
8171-005CSR	1/2	25	0	101	58.08
8171-007CSR	3/4	25	0	101	69.52
8171-010CSR	1	25	0	101	78.64
8171-012CSR	1-1/4	20	0	101	101.44
8171-015CSR	1-1/2	20	0	101	113.88
8171-020CSR	2	15	0	101	157.48
8171-025CSR	2-1/2	4	0	101	239.56
8171-030CSR	3	4	0	101	285.13
8171-040CSR	4	2	0	101	458.24
8171-060CSR	6	1	0	101	1210.26

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets



Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	65.83
8171E-003CSR	3/8	25	200	101	65.83
8171E-005CSR	1/2	25	0	101	65.83
8171E-007CSR	3/4	25	0	101	74.40
8171E-010CSR	1	25	0	101	88.96
8171E-012CSR	1-1/4	20	0	101	111.18
8171E-015CSR	1-1/2	20	0	101	120.28
8171E-020CSR	2	15	0	101	170.04
8171E-025CSR	2-1/2	4	0	101	249.88
8171E-030CSR	3	4	0	101	297.47
8171E-040CSR	4	2	0	101	476.96
8171E-060CSR	6	2	0	101	1259.58

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets



Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	85.77
8171V-003CSR	3/8	25	200	101	85.77
8171V-005CSR	1/2	25	0	101	85.77
8171V-007CSR	3/4	25	0	101	99.15
8171V-010CSR	1	25	0	101	115.34
8171V-012CSR	1-1/4	20	0	101	142.98



Transition Fittings Product

CPVC Gray Special Reinforced (SR) Fittings & CPVC Gray Brass Thread Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets (continued)					
Socket x SR Fipt - Stainless Steel Collar					
8171V-015CSR	1-1/2	20	0	101	152.68
8171V-020CSR	2	15	0	101	227.36
8171V-025CSR	2-1/2	4	0	101	335.04
8171V-030CSR	3	4	0	101	398.95
8171V-040CSR	4	2	0	101	851.85
8171V-060CSR	6	2	0	101	2103.19

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	76.94
8172-003CSR	3/8	25	200	101	76.94
8172-005CSR	1/2	25	0	101	76.94
8172-007CSR	3/4	25	0	101	89.35
8172-010CSR	1	25	0	101	98.45
8172-012CSR	1-1/4	20	0	101	139.66
8172-015CSR	1-1/2	20	0	101	156.03
8172-020CSR	2	15	0	101	192.92
8172-025CSR	2-1/2	4	0	101	279.98
8172-030CSR	3	4	0	101	333.32
8172-040CSR	4	2	0	101	511.95
8172-060CSR	6	2	0	101	1371.59

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	79.96
8172E-003CSR	3/8	25	200	101	79.96
8172E-005CSR	1/2	25	0	101	79.96
8172E-007CSR	3/4	25	0	101	94.67
8172E-010CSR	1	25	0	101	102.78
8172E-012CSR	1-1/4	20	0	101	145.07
8172E-015CSR	1-1/2	20	0	101	168.65
8172E-020CSR	2	15	0	101	207.00
8172E-025CSR	2-1/2	4	0	101	312.27
8172E-030CSR	3	4	0	101	371.76
8172E-040CSR	4	2	0	101	601.83
8172E-060CSR	6	2	0	101	1391.88

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	122.77
8172V-003CSR	3/8	25	200	101	122.77



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172V-005CSR	1/2	25	0	101	122.77
8172V-007CSR	3/4	25	0	101	138.89
8172V-010CSR	1	25	0	101	160.41
8172V-012CSR	1-1/4	20	0	101	198.05
8172V-015CSR	1-1/2	20	0	101	208.58
8172V-020CSR	2	15	0	101	320.57
8172V-025CSR	2-1/2	4	0	101	463.20
8172V-030CSR	3	4	0	101	551.43
8172V-040CSR	4	2	0	101	1407.11
8172V-060CSR	6	2	0	101	2554.93

Elastomer Expansion Joint - CPVC

CPVC with EPDM Bellows SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007CSR	3/4	10	0	085	242.86
EJ21-010CSR	1	10	0	085	279.28
EJ21-012CSR	1-1/4	15	0	085	308.62
EJ21-015CSR	1-1/2	10	0	085	393.38
EJ21-020CSR	2	8	0	085	519.97
EJ21-025CSR	2-1/2	4	0	085	722.13
EJ21-030CSR	3	2	0	085	961.77



CPVC Gray Brass Thread Fittings

Tee - Brass Transition

Socket x Socket x Fipt With Brass Thread Insert

802-005CBR	1/2	20	140	096	68.08
802-007CBR	3/4	20	80	096	136.17

Not intended to convey or dispense water for human consumption through drinking or cooking

Tee - Brass Transition Reducing

Socket x Socket x Fipt With Brass Thread Insert

802-101CBR	3/4X1/2	50	0	096	84.40
------------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

90° EII - Brass Transition

Socket x Fipt With Brass Thread Insert

807-005CBR	1/2	20	240	096	59.86
807-007CBR	3/4	20	160	096	104.52

Not intended to convey or dispense water for human consumption through drinking or cooking

