



Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tee - Special Reinforced

Socket x Socket x SR Fipt - Stainless Steel Collar



802-005CSR	1/2	50	0	096	20.71
802-007CSR	3/4	15	120	096	30.26
802-010CSR	1	15	0	096	38.07
802-012CSR	1-1/4	15	0	096	44.17
802-015CSR	1-1/2	10	0	096	44.17
802-020CSR	2	10	0	096	72.20
802-030CSR	3	5	0	096	103.98
802-040CSR	4	5	0	096	195.88

Tee - Special Reinforced

SR Fipt x SR Fipt x SR Fipt - Stainless Steel Collar



805-002CSR	1/4	20	160	096	18.53
805-003CSR	3/8	25	150	096	18.53
805-005CSR	1/2	25	150	096	24.79
805-007CSR	3/4	25	100	096	28.40
805-010CSR	1	15	0	096	42.41
805-015CSR	1-1/2	10	0	096	45.03
805-020CSR	2	10	0	096	53.62

Tee - Special Reinforced Reducing

Socket x Socket x SR Fipt - Stainless Steel Collar



802-072CSR	1/2X1/4	25	200	096	20.71
802-098CSR	3/4X1/4	25	100	096	27.67
802-101CSR	3/4X1/2	50	0	096	27.67
802-128CSR ¹	1X1/4	15	0	096	42.74
802-130CSR	1X1/2	50	0	096	16.91
802-131CSR	1X3/4	15	0	096	42.74
802-164CSR ¹	1-1/4X1/4	5	0	096	56.83
802-166CSR	1-1/4X1/2	15	0	096	45.02
802-168CSR	1-1/4X1	10	0	096	45.94
802-207CSR ¹	1-1/2X1/4	15	0	096	81.38
802-211CSR	1-1/2X1	10	0	096	53.94
802-212CSR	1-1/2X1-1/4	10	0	096	53.94
802-245CSR ¹	2X1/4	10	0	096	93.47
802-247CSR	2X1/2	10	0	096	84.14
802-248CSR	2X3/4	10	0	096	93.47
802-287CSR	2-1/2X1/2	10	0	096	64.28
802-331CSR ¹	3X1/4	5	0	096	178.55
802-413CSR ¹	4X1/4	5	0	096	193.75

¹ Sized with Bushing

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tee - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar x Socket



(See also Gauge & Instrument Fittings for additional configurations)

803-095CSR	3/4X1/2X3/4	15	0	096	17.05
------------	-------------	----	---	-----	-------

90° Ell - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



807-005CSR	1/2	20	240	096	10.05
807-007CSR	3/4	75	0	096	11.81
807-010CSR	1	50	0	096	14.22
807-012CSR	1-1/4	25	0	096	29.36
807-015CSR	1-1/2	10	0	096	35.29
807-020CSR	2	10	0	096	44.16

90° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



808-003CSR	3/8	25	150	096	6.07
808-005CSR	1/2	20	120	096	6.07
808-007CSR	3/4	20	160	096	8.89
808-010CSR	1	50	0	096	11.40
808-012CSR	1-1/4	25	0	096	21.94
808-015CSR	1-1/2	10	0	096	25.83
808-020CSR	2	10	0	096	34.60

90° Ell - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar



807-101CSR	3/4X1/2	50	0	096	12.81
807-130CSR	1X1/2	50	0	096	13.81

45° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



819-007CSR	3/4	10	120	096	13.88
------------	-----	----	-----	-----	-------

Coupling - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



830-005CSR	1/2	25	150	096	9.80
830-007CSR	3/4	25	150	096	15.83
830-010CSR	1	25	200	096	17.98
830-012CSR	1-1/4	10	120	096	19.11
830-015CSR	1-1/2	10	80	096	20.48
830-020CSR	2	10	0	096	24.21

Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings



CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Coupling - Special Reinforced Reducer



SR Fipt x SR Fipt - Stainless Steel Collar

830-101CSR	3/4X1/2	50	200	096	17.56
830-130CSR	1X1/2	50	0	096	21.20
830-131CSR	1X3/4	25	200	096	21.20
830-168CSR	1-1/4X1	25	0	096	28.83
830-210CSR	1-1/2X3/4	25	0	096	41.23
830-211CSR	1-1/2X1	10	80	096	41.23
830-212CSR	1-1/2X1-1/4	10	80	096	41.23
830-249CSR	2X1	25	0	096	101.49
830-251CSR	2X1-1/2	15	0	096	101.49

Female Adapter - Special Reinforced



Socket x SR Fipt - Stainless Steel Collar

835-002CSR	1/4	25	450	096	13.75
835-003CSR	3/8	25	300	096	13.75
835-005CSR	1/2	25	150	096	5.91
835-007CSR	3/4	25	150	096	6.38
835-010CSR	1	25	200	096	14.55
835-012CSR	1-1/4	10	60	096	14.93
835-015CSR	1-1/2	10	80	096	17.33
835-020CSR	2	10	0	096	24.62
835-025CSR	2-1/2	5	0	096	57.25
835-030CSR	3	15	0	096	117.63
835-040CSR	4	5	0	096	195.78
835-060CSR	6	6	0	096	305.84

Female Adapter - Encapsulated Special Reinforced



Socket x ESR Fipt

835-002CESR	1/4	25	450	096	17.44
835-003CESR	3/8	25	300	096	17.44
835-005CESR	1/2	25	300	096	9.05
835-007CESR	3/4	25	300	096	9.56
835-010CESR	1	25	200	096	21.06
835-012CESR	1-1/4	10	80	096	21.56
835-015CESR	1-1/2	10	80	096	27.92
835-020CESR	2	10	0	096	43.39

Female Spigot Adapter - Special Reinforced



Spigot x SR Fipt - Stainless Steel Collar

878-005CSR	1/2	50	600	096	6.29
878-007CSR	3/4	25	300	096	6.64
878-010CSR	1	50	0	096	14.94
878-012CSR	1-1/4	25	0	096	15.45

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Spigot Adapter - Special Reinforced (continued)

Spigot x SR Fipt - Stainless Steel Collar

878-015CSR	1-1/2	25	0	096	17.94
878-020CSR	2	15	0	096	32.67
878-030CSR	3	5	0	096	119.11
878-040CSR	4	5	0	096	199.95

Female Adapter - Special Reinforced Reducing



Socket x SR Fipt - Stainless Steel Collar

835-074CSR	1/2X3/4	50	400	096	6.38
835-101CSR	3/4X1/2	50	400	096	6.38
835-102CSR	3/4X1	50	0	096	14.55
835-130CSR	1X1/2	50	0	096	14.55
835-131CSR	1X3/4	25	200	096	14.55

Female Spigot Adapter - Encapsulated Special Reinforced



Spigot x ESR Fipt

878-005CESR	1/2	50	600	096	9.32
878-007CESR	3/4	25	300	096	9.92
878-010CESR	1	50	0	096	21.26
878-012CESR	1-1/4	25	0	096	21.84
878-015CESR	1-1/2	25	0	096	28.47
878-020CESR	2	15	0	096	44.01

Female Spigot Adapter - Special Reinforced Reducing



Spigot x SR Fipt - Stainless Steel Collar

878-072CSR	1/2X1/4	25	450	096	18.04
878-098CSR	3/4X1/4	50	300	096	21.00
878-128CSR	1X1/4	50	400	096	23.51

Male Adapter - Internal Reinforced



R Mipt x Socket - Stainless Steel Sleeve

NSF® Certified Lead Free

836-005CR	1/2	25	150	096	9.07
836-007CR	3/4	25	300	096	10.39
836-010CR	1	10	120	096	12.33

Reducer Bushing - Special Reinforced Reducing Flush Style



Mipt x SR Fipt - Stainless Steel Collar

839-209CSR	1-1/2X1/2	25	300	096	23.27
839-210CSR	1-1/2X3/4	25	300	096	23.27
839-247CSR	2X1/2	10	60	096	25.72
839-248CSR	2X3/4	10	60	096	25.72
839-249CSR	2X1	10	120	096	25.72
839-420CSR	4X2	6	0	096	142.80



Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Reducer Bushing - Special Reinforced



Spigot x SR Fipt - Stainless Steel Collar

838-128CSR	1X1/4	25	150	096	13.41
838-207CSR	1-1/2X1/4	25	200	096	22.68
838-209CSR	1-1/2X1/2	10	120	096	23.64
838-210CSR	1-1/2X3/4	10	120	096	23.64
838-247CSR	2X1/2	10	80	096	32.48
838-248CSR	2X3/4	10	80	096	32.48
838-249CSR	2X1	10	120	096	32.48
838-334CSR	3X3/4	10	0	096	137.56
838-335CSR	3X1	10	0	096	137.56
838-336CSR	3X1-1/4	10	0	096	137.56
838-337CSR	3X1-1/2	10	0	096	137.56
838-528CSR	6X2	5	0	096	472.92
838-530CSR	6X3	5	0	096	472.92

Cap - Special Reinforced



SR Fipt - Stainless Steel Collar

848-002CSR	1/4	25	500	096	7.43
848-003CSR	3/8	25	450	096	7.43
848-007CSR	3/4	25	300	096	11.58
848-030CSR	3	5	0	096	129.26

Union 2000 - Socket/Special Reinforced Fipt/EPDM



Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	120	096	16.64
8099-007CSR	3/4	20	160	096	29.55
8099-010CSR	1	15	90	096	40.92
8099-012CSR	1-1/4	10	0	096	77.52
8099-015CSR	1-1/2	10	0	096	84.31
8099-020CSR	2	5	0	096	88.78
8099-025CSR	2-1/2	5	0	096	152.27
8099-030CSR	3	5	0	096	247.32
8099-040CSR	4	4	0	096	290.45
8099-060CSR	6	1	0	096	645.47

Union 2000 - Special Reinforced



Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	25	200	096	16.98
8059-007CSR	3/4	20	160	096	29.95
8059-010CSR	1	15	90	096	41.26
8059-012CSR	1-1/4	10	0	096	78.67

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced (continued)

Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar

8059-015CSR	1-1/2	10	0	096	85.52
8059-020CSR	2	5	0	096	89.03
8059-030CSR	3	5	0	096	250.46
8059-040CSR	4	4	0	096	292.21

Union 2000 - Special Reinforced Fipt/FKM



SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	120	096	17.42
8058-007CSR	3/4	20	80	096	30.37
8058-010CSR	1	15	90	096	41.74
8058-012CSR	1-1/4	10	0	096	78.67
8058-015CSR	1-1/2	10	0	096	85.85
8058-020CSR	2	5	0	096	90.46
8058-030CSR	3	5	0	096	255.63
8058-040CSR	4	4	0	096	299.48
8058-060CSR	6	1	0	096	674.45

Union 2000 - Special Reinforced Fipt/EPDM



SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	16.84
8098-007CSR	3/4	20	80	096	30.09
8098-010CSR	1	15	90	096	41.26
8098-012CSR	1-1/4	10	0	096	77.91
8098-015CSR	1-1/2	10	0	096	85.19
8098-020CSR	2	5	0	096	89.57
8098-025CSR	2-1/2	5	0	096	154.79
8098-030CSR	3	5	0	096	251.67
8098-040CSR	4	4	0	096	291.36
8098-060CSR	6	1	0	096	647.46

Union (Old Style) - Socket/Special Reinforced Fipt/EPDM



Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	26.54
899-003CSR	3/8	25	100	096	26.54
899-005CSR	1/2	10	60	096	16.64
899-007CSR	3/4	10	40	096	29.55
899-010CSR	1	10	40	096	40.92
899-012CSR	1-1/4	5	20	096	77.52
899-015CSR	1-1/2	5	0	096	84.31
899-020CSR	2	5	0	096	88.78
899-030CSR	3	5	0	096	247.32
899-040CSR	4	4	0	096	290.45

Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings



CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union (Old Style) - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	26.72
859-003CSR	3/8	25	100	096	26.72
859-005CSR	1/2	10	60	096	16.98
859-007CSR	3/4	10	60	096	29.95
859-010CSR	1	10	40	096	41.26
859-012CSR	1-1/4	5	20	096	78.67
859-015CSR	1-1/2	5	0	096	85.52
859-020CSR	2	5	0	096	89.03
859-030CSR	3	5	0	096	250.46
859-040CSR	4	4	0	096	292.21

Flange - Special Reinforced One Piece Threaded

SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	21.74
852-007CSR	3/4	25	0	096	26.37
852-010CSR	1	15	0	096	28.85
852-012CSR	1-1/4	15	0	096	39.93
852-015CSR	1-1/2	15	0	096	42.33
852-020CSR	2	10	0	096	43.36
852-025CSR	2-1/2	10	0	096	69.76
852-030CSR	3	10	0	096	69.22
852-040CSR	4	5	0	096	129.71

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Socket x SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	52.42
8171-003CSR	3/8	25	200	101	52.42
8171-005CSR	1/2	25	0	101	52.42
8171-007CSR	3/4	25	0	101	62.74
8171-010CSR	1	25	0	101	70.97
8171-012CSR	1-1/4	20	0	101	91.55
8171-015CSR	1-1/2	20	0	101	102.78
8171-020CSR	2	15	0	101	142.13
8171-025CSR	2-1/2	4	0	101	216.20
8171-030CSR	3	4	0	101	257.33
8171-040CSR	4	2	0	101	413.56
8171-060CSR	6	1	0	101	1092.26

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Socket x SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	59.41
8171E-003CSR	3/8	25	200	101	59.41
8171E-005CSR	1/2	25	0	101	59.41
8171E-007CSR	3/4	25	0	101	67.15
8171E-010CSR	1	25	0	101	80.28
8171E-012CSR	1-1/4	20	0	101	100.34
8171E-015CSR	1-1/2	20	0	101	108.56
8171E-020CSR	2	15	0	101	153.46
8171E-025CSR	2-1/2	4	0	101	225.52
8171E-030CSR	3	4	0	101	268.47
8171E-040CSR	4	2	0	101	430.45
8171E-060CSR	6	2	0	101	1136.77

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Socket x SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	77.41
8171V-003CSR	3/8	25	200	101	77.41
8171V-005CSR	1/2	25	0	101	77.41
8171V-007CSR	3/4	25	0	101	89.48
8171V-010CSR	1	25	0	101	104.09
8171V-012CSR	1-1/4	20	0	101	129.04
8171V-015CSR	1-1/2	20	0	101	137.80
8171V-020CSR	2	15	0	101	205.19
8171V-025CSR	2-1/2	4	0	101	302.38
8171V-030CSR	3	4	0	101	360.05
8171V-040CSR	4	2	0	101	768.80
8171V-060CSR	6	2	0	101	1898.13

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	69.44
8172-003CSR	3/8	25	200	101	69.44
8172-005CSR	1/2	25	0	101	69.44
8172-007CSR	3/4	25	0	101	80.64
8172-010CSR	1	25	0	101	88.85
8172-012CSR	1-1/4	20	0	101	126.05
8172-015CSR	1-1/2	20	0	101	140.82
8172-020CSR	2	15	0	101	174.11
8172-025CSR	2-1/2	4	0	101	252.68
8172-030CSR	3	4	0	101	300.82
8172-040CSR	4	2	0	101	462.03
8172-060CSR	6	2	0	101	1237.86



Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings & CPVC Gray Brass Thread Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	72.16
8172E-003CSR	3/8	25	200	101	72.16
8172E-005CSR	1/2	25	0	101	72.16
8172E-007CSR	3/4	25	0	101	85.44
8172E-010CSR	1	25	0	101	92.76
8172E-012CSR	1-1/4	20	0	101	130.93
8172E-015CSR	1-1/2	20	0	101	152.21
8172E-020CSR	2	15	0	101	186.82
8172E-025CSR	2-1/2	4	0	101	281.83
8172E-030CSR	3	4	0	101	335.51
8172E-040CSR	4	2	0	101	543.15
8172E-060CSR	6	2	0	101	1256.18



Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	110.80
8172V-003CSR	3/8	25	200	101	110.80
8172V-005CSR	1/2	25	0	101	110.80
8172V-007CSR	3/4	25	0	101	125.35
8172V-010CSR	1	25	0	101	144.77
8172V-012CSR	1-1/4	20	0	101	178.74
8172V-015CSR	1-1/2	20	0	101	188.24
8172V-020CSR	2	15	0	101	289.31
8172V-025CSR	2-1/2	4	0	101	418.04
8172V-030CSR	3	4	0	101	497.67
8172V-040CSR	4	2	0	101	1269.91
8172V-060CSR	6	2	0	101	2305.82



Elastomer Expansion Joint - CPVC

CPVC with EPDM Bellows SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007CSR	3/4	10	0	085	219.18
EJ21-010CSR	1	10	0	085	252.05
EJ21-012CSR	1-1/4	15	0	085	278.53
EJ21-015CSR	1-1/2	10	0	085	355.02
EJ21-020CSR	2	8	0	085	469.27
EJ21-025CSR	2-1/2	4	0	085	651.72
EJ21-030CSR	3	2	0	085	868.00



CPVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tee - Brass Transition

Socket x Socket x Fipt With Brass Thread Insert



802-005CBR	1/2	20	140	096	61.45
802-007CBR	3/4	20	80	096	122.89

Not intended to convey or dispense water for human consumption through drinking or cooking

Tee - Brass Transition Reducing

Socket x Socket x Fipt With Brass Thread Insert



802-101CBR	3/4X1/2	50	0	096	76.17
------------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

90° Ell - Brass Transition

Socket x Fipt With Brass Thread Insert



807-005CBR	1/2	20	240	096	54.03
807-007CBR	3/4	20	160	096	94.33

Not intended to convey or dispense water for human consumption through drinking or cooking

90° Ell - Brass Transition Reducing

Socket x Fipt With Brass Thread Insert



807-101CBR	3/4X1/2	20	120	096	67.57
------------	---------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

Female Adapter - Brass Transition

Socket x Fipt With Brass Thread Insert



835-005CBR	1/2	25	150	096	33.31
835-007CBR	3/4	15	90	096	68.93
835-010CBR	1	15	90	096	120.97
835-012CBR	1-1/4	15	60	096	197.34
835-015CBR	1-1/2	10	40	096	260.19
835-020CBR	2	8	32	096	324.97

Not intended to convey or dispense water for human consumption through drinking or cooking

Female Adapter - Stainless Steel Transition

Socket x Fipt With Type 316 Stainless Steel Thread Insert



NSF® Certified Lead Free

835-005CSS	1/2	25	150	096	65.40
------------	-----	----	-----	-----	-------