



Transition Fittings Product

**PVC Gray Special Reinforced (SR) Fittings & PVC Gray Brass Thread Fittings**

**PVC Gray Special Reinforced (SR) Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Tank Adapters, PVC New Style Special Reinforced (SR)**

Threaded with FKM Gaskets (continued)

**Socket x SR Fipt - Stainless Steel Collar**

8171V-025SR	2-1/2	4	0	100	250.53
8171V-030SR	3	4	0	100	298.23
8171V-040SR	4	2	0	100	716.54
8171V-060SR	6	1	0	100	1269.92

**Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets**

**Fipt x SR Fipt - Stainless Steel Collar**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002SR	1/4	25	150	100	50.07
8172-003SR	3/8	25	200	100	50.07
8172-005SR	1/2	25	0	100	50.07
8172-007SR	3/4	25	0	100	55.43
8172-010SR	1	25	0	100	61.31
8172-012SR	1-1/4	20	0	100	82.56
8172-015SR	1-1/2	20	0	100	93.04
8172-020SR	2	15	0	100	120.56
8172-025SR	2-1/2	4	0	100	183.55
8172-030SR	3	4	0	100	218.52
8172-040SR	4	2	0	100	389.02
8172-060SR	6	1	0	100	752.51

**Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets**

**Fipt x SR Fipt - Stainless Steel Collar**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002SR	1/4	25	150	100	51.52
8172E-003SR	3/8	25	200	100	51.52
8172E-005SR	1/2	25	0	100	51.52
8172E-007SR	3/4	25	0	100	56.47
8172E-010SR	1	25	0	100	67.57
8172E-012SR	1-1/4	20	0	100	89.69
8172E-015SR	1-1/2	20	0	100	100.06
8172E-020SR	2	15	0	100	129.05
8172E-025SR	2-1/2	4	0	100	189.65
8172E-030SR	3	4	0	100	225.75
8172E-040SR	4	2	0	100	398.29
8172E-060SR	6	1	0	100	778.59

**Tank Adapters, PVC New Style Special Reinforced (SR) Threaded with FKM Gaskets**

**Fipt x SR Fipt - Stainless Steel Collar**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002SR	1/4	25	150	100	76.62
8172V-003SR	3/8	25	200	100	76.62
8172V-005SR	1/2	25	0	100	76.62
8172V-007SR	3/4	25	0	100	82.26

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Tank Adapters, PVC New Style Special Reinforced (SR)**

Threaded with FKM Gaskets (continued)

**Fipt x SR Fipt - Stainless Steel Collar**

8172V-010SR	1	25	0	100	94.51
8172V-012SR	1-1/4	20	0	100	108.64
8172V-015SR	1-1/2	20	0	100	126.82
8172V-020SR	2	15	0	100	184.59
8172V-025SR	2-1/2	4	0	100	271.04
8172V-030SR	3	4	0	100	322.76
8172V-040SR	4	2	0	100	752.51
8172V-060SR	6	2	0	100	1420.94

**Elastomer Expansion Joint - PVC**

**PVC with Neoprene Bellows SR Fipt - Stainless Steel Collar**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ01-007SR	3/4	10	0	085	211.18
EJ01-010SR	1	10	0	085	240.49
EJ01-012SR	1-1/4	15	0	085	261.57
EJ01-015SR	1-1/2	10	0	085	333.93
EJ01-020SR	2	8	0	085	401.19
EJ01-025SR	2-1/2	4	0	085	584.64
EJ01-030SR	3	2	0	085	786.25

**Elastomer Expansion Joint - PVC**

**PVC with EPDM Bellows SR Fipt - Stainless Steel Collar**

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007SR	3/4	10	0	085	215.46
EJ21-010SR	1	10	0	085	245.41
EJ21-012SR	1-1/4	15	0	085	266.94
EJ21-015SR	1-1/2	10	0	085	340.72
EJ21-020SR	2	8	0	085	409.39
EJ21-025SR	2-1/2	4	0	085	593.25
EJ21-030SR	3	2	0	085	802.29

**PVC Gray Brass Thread Fittings**

**Tee - Brass Transition**

**Socket x Socket x Fipt With Brass Thread Insert**

802-005BR	1/2	20	120	086	34.65
802-007BR	3/4	20	80	086	69.44

**Not intended to convey or dispense water for human consumption through drinking or cooking**

Transition Fittings Product  
**PVC Gray Brass Thread Fittings**



**PVC Gray Brass Thread Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Tee - Brass Transition Reducing**

**Socket x Socket x Fipt With Brass Thread Insert**

802-072BR	1/2X1/4	20	120	086	37.35
802-101BR	3/4X1/2	50	0	086	43.24

Not intended to convey or dispense water for human consumption through drinking or cooking



**90° Ell - Brass Transition**

**Socket x Fipt With Brass Thread Insert**

807-005BR	1/2	20	240	086	30.44
807-007BR	3/4	20	160	086	53.88

Not intended to convey or dispense water for human consumption through drinking or cooking



**90° Ell - Brass Transition Reducing**

**Socket x Fipt With Brass Thread Insert**

807-101BR	3/4X1/2	20	120	086	37.99
-----------	---------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking



**Female Adapter - Brass Transition**

**Socket x Fipt With Brass Thread Insert**

835-005BR	1/2	25	150	086	26.28
835-007BR	3/4	15	90	086	37.75
835-010BR	1	15	90	086	65.05
835-012BR	1-1/4	15	60	086	107.13
835-015BR	1-1/2	10	40	086	140.73
835-020BR	2	8	32	086	174.31

Not intended to convey or dispense water for human consumption through drinking or cooking



**Female Spigot Adapter - Brass Transition**

**Spigot x Fipt With Brass Thread Insert**

878-005BR	1/2	25	150	086	22.11
878-010BR	1	15	90	086	70.33

Not intended to convey or dispense water for human consumption through drinking or cooking



**Female Adapter - Brass Transition Reducing**

**Socket x Fipt With Brass Thread Insert**

835-101BR	3/4X1/2	50	0	086	39.02
-----------	---------	----	---	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Female Adapter - Brass Transition Reducing (continued)**  
**Socket x Fipt With Brass Thread Insert**

Not intended to convey or dispense water for human consumption through drinking or cooking

**Female Adapter - Stainless Steel Transition**

**Socket x Fipt With 316 Stainless Steel Thread Insert**

NSF® Certified Lead Free

835-005SS	1/2	25	150	086	51.51
835-007SS	3/4	15	90	086	74.02
835-010SS	1	15	90	086	125.95
835-012SS	1-1/4	25	0	086	210.35
835-015SS	1-1/2	10	40	086	274.78
835-020SS	2	8	32	086	352.49



**Male Adapter - PVC Lined Brass Transition**

**Brass Mipt x Socket**

NSF® Certified Lead Free

836-005BR	1/2	40	160	086	28.93
836-007BR	3/4	40	160	086	43.62
836-010BR	1	10	60	086	70.94
836-012BR	1-1/4	10	40	086	119.49
836-015BR	1-1/2	10	40	086	158.56
836-020BR	2	8	32	086	196.98



**Union - Socket/Brass Fipt/FKM**

**Socket x Fipt with Brass Thread Insert & FKM O-ring Seal**

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007BR	3/4	10	40	086	55.99
859-010BR	1	10	0	086	69.09
859-012BR	1-1/4	5	20	086	119.25
859-015BR	1-1/2	5	0	086	157.83
859-020BR	2	5	0	086	209.75

Not intended to convey or dispense water for human consumption through drinking or cooking



**Union - Socket/Brass Fipt/EPDM**

**Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal**

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007BR	3/4	10	60	086	50.48
899-010BR	1	10	0	086	68.08
899-012BR	1-1/4	5	20	086	114.49
899-015BR	1-1/2	5	0	086	151.54
899-020BR	2	5	0	086	201.99

Not intended to convey or dispense water for human consumption through drinking or cooking

