

Transition Fittings Product  
**PVC Gray Brass Thread Fittings**



**PVC Gray Brass Thread Fittings**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Tee - Brass Transition**

**Socket x Socket x Fipt With Brass Thread Insert**

802-005BR	1/2	20	120	086	38.39
802-007BR	3/4	20	80	086	76.94

Not intended to convey or dispense water for human consumption through drinking or cooking



**Tee - Brass Transition Reducing**

**Socket x Socket x Fipt With Brass Thread Insert**

802-072BR	1/2X1/4	20	120	086	41.39
802-101BR	3/4X1/2	50	0	086	47.92

Not intended to convey or dispense water for human consumption through drinking or cooking



**90° Ell - Brass Transition**

**Socket x Fipt With Brass Thread Insert**

807-005BR	1/2	20	240	086	33.73
807-007BR	3/4	20	160	086	59.71

Not intended to convey or dispense water for human consumption through drinking or cooking



**90° Ell - Brass Transition Reducing**

**Socket x Fipt With Brass Thread Insert**

807-101BR	3/4X1/2	20	120	086	42.09
-----------	---------	----	-----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking



**Female Adapter - Brass Transition**

**Socket x Fipt With Brass Thread Insert**

835-005BR	1/2	25	150	086	29.12
835-007BR	3/4	15	90	086	41.83
835-010BR	1	15	90	086	72.07
835-012BR	1-1/4	15	60	086	118.71
835-015BR	1-1/2	10	40	086	155.94
835-020BR	2	8	32	086	193.14

Not intended to convey or dispense water for human consumption through drinking or cooking



**Female Spigot Adapter - Brass Transition**

**Spigot x Fipt With Brass Thread Insert**

878-005BR	1/2	25	150	086	24.49
-----------	-----	----	-----	-----	-------



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**Female Spigot Adapter - Brass Transition (continued)**

**Spigot x Fipt With Brass Thread Insert**

878-010BR	1	15	90	086	77.93
-----------	---	----	----	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

**Female Adapter - Brass Transition Reducing**

**Socket x Fipt With Brass Thread Insert**

835-101BR	3/4X1/2	50	0	086	43.23
-----------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking



**Female Adapter - Stainless Steel Transition**

**Socket x Fipt With 316 Stainless Steel Thread Insert**

NSF® Certified Lead Free

835-005SS	1/2	25	150	086	57.07
835-007SS	3/4	15	90	086	82.02
835-010SS	1	15	90	086	139.56
835-012SS	1-1/4	25	0	086	233.07
835-015SS	1-1/2	10	40	086	304.46
835-020SS	2	8	32	086	390.57



**Male Adapter - PVC Lined Brass Transition**

**Brass Mipt x Socket**

NSF® Certified Lead Free

836-005BR	1/2	40	160	086	32.05
836-007BR	3/4	40	160	086	48.34
836-010BR	1	10	60	086	78.60
836-012BR	1-1/4	10	40	086	132.40
836-015BR	1-1/2	10	40	086	175.69
836-020BR	2	8	32	086	218.26



**Union - Socket/Brass Fipt/FKM**

**Socket x Fipt with Brass Thread Insert & FKM O-ring Seal**

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-007BR	3/4	10	40	086	62.04
859-010BR	1	10	0	086	76.56
859-012BR	1-1/4	5	20	086	132.14
859-015BR	1-1/2	5	0	086	174.88
859-020BR	2	5	0	086	232.41

Not intended to convey or dispense water for human consumption through drinking or cooking





Transition Fittings Product

PVC Gray Brass Thread Fittings & CPVC Gray Special Reinforced (SR) Fittings

PVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007BR	3/4	10	60	086	55.94
899-010BR	1	10	0	086	75.43
899-012BR	1-1/4	5	20	086	126.86
899-015BR	1-1/2	5	0	086	167.92
899-020BR	2	5	0	086	223.81

Not intended to convey or dispense water for human consumption through drinking or cooking

CPVC Gray Special Reinforced (SR) Fittings

Tee - Special Reinforced

Socket x Socket x SR Fipt - Stainless Steel Collar



802-005CSR	1/2	50	0	096	22.95
802-007CSR	3/4	15	120	096	33.53
802-010CSR	1	15	0	096	42.18
802-012CSR	1-1/4	15	0	096	48.94
802-015CSR	1-1/2	10	0	096	48.94
802-020CSR	2	10	0	096	80.00
802-030CSR	3	5	0	096	115.21
802-040CSR	4	5	0	096	217.04

Tee - Special Reinforced

SR Fipt x SR Fipt x SR Fipt - Stainless Steel Collar



805-002CSR	1/4	25	150	096	20.54
805-003CSR	3/8	25	150	096	20.54
805-005CSR	1/2	25	150	096	27.46
805-007CSR	3/4	25	100	096	31.46
805-010CSR	1	15	0	096	46.99
805-015CSR	1-1/2	10	0	096	49.89
805-020CSR	2	10	0	096	59.41

Tee - Special Reinforced Reducing

Socket x Socket x SR Fipt - Stainless Steel Collar



802-072CSR	1/2X1/4	25	200	096	22.95
802-098CSR	3/4X1/4	25	100	096	30.66
802-101CSR	3/4X1/2	50	0	096	30.66
802-128CSR <sup>1</sup>	1X1/4	15	0	096	47.36
802-130CSR	1X1/2	50	0	096	18.74
802-131CSR	1X3/4	15	0	096	47.36
802-164CSR <sup>1</sup>	1-1/4X1/4	5	0	096	62.97
802-166CSR	1-1/4X1/2	15	0	096	49.88

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tee - Special Reinforced Reducing (continued)

Socket x Socket x SR Fipt - Stainless Steel Collar

802-168CSR	1-1/4X1	10	0	096	50.91
802-207CSR <sup>1</sup>	1-1/2X1/4	15	0	096	90.17
802-211CSR	1-1/2X1	10	0	096	59.77
802-212CSR	1-1/2X1-1/4	10	0	096	59.77
802-245CSR <sup>1</sup>	2X1/4	10	0	096	103.57
802-247CSR	2X1/2	10	0	096	93.23
802-248CSR	2X3/4	10	0	096	103.57
802-287CSR	2-1/2X1/2	10	0	096	71.22
802-331CSR <sup>1</sup>	3X1/4	5	0	096	197.84
802-413CSR <sup>1</sup>	4X1/4	5	0	096	214.68

<sup>1</sup> Sized with Bushing

Tee - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar x Socket



(See also Gauge & Instrument Fittings for additional configurations)

803-095CSR	3/4X1/2X3/4	15	0	096	18.89
------------	-------------	----	---	-----	-------

90° Ell - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



807-005CSR	1/2	20	240	096	11.14
807-007CSR	3/4	75	0	096	13.08
807-010CSR	1	50	0	096	15.76
807-012CSR	1-1/4	25	0	096	32.54
807-015CSR	1-1/2	10	0	096	39.11
807-020CSR	2	10	0	096	48.93

90° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



808-003CSR	3/8	25	150	096	6.73
808-005CSR	1/2	20	120	096	6.73
808-007CSR	3/4	20	160	096	9.85
808-010CSR	1	50	0	096	12.63
808-012CSR	1-1/4	25	0	096	24.31
808-015CSR	1-1/2	10	0	096	28.62
808-020CSR	2	10	0	096	38.34

90° Ell - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar



807-101CSR	3/4X1/2	50	0	096	14.19
807-130CSR	1X1/2	50	0	096	15.31