

**Wafer Butterfly Valves & High Purity TFM-Lined Butterfly Valves**



**Wafer Butterfly Valves**

**CPVC**

Size	EPDM Seat	FKM Seat	Std Pk	Mstr Pk	Prod Code
------	-----------	----------	--------	---------	-----------

**Gear Operator**

2	<a href="#">752321-020C</a> <b>1067.75</b>	<a href="#">753321-020C</a> <b>1454.24</b>	1	0	252
2-1/2	<a href="#">752321-025C</a> <b>1083.78</b>	<a href="#">753321-025C</a> <b>1528.19</b>	1	0	252
3	<a href="#">752321-030C</a> <b>1099.42</b>	<a href="#">753321-030C</a> <b>1596.92</b>	1	0	252
4	<a href="#">752321-040C</a> <b>1179.02</b>	<a href="#">753321-040C</a> <b>1850.64</b>	1	0	252
6	<a href="#">752321-060C</a> <b>1467.57</b>	<a href="#">753321-060C</a> <b>2606.80</b>	1	0	252
8	<a href="#">752321-080C</a> <b>2074.47</b>	<a href="#">753321-080C</a> <b>4004.73</b>	1	0	252
10	<a href="#">752321-100C</a> <b>2905.27</b>	<a href="#">753321-100C</a> <b>7422.37</b>	1	0	252
12	<a href="#">752321-120C</a> <b>4104.19</b>	<a href="#">753321-120C</a> <b>9648.59</b>	1	0	252

**Valve Only**

2	<a href="#">752301-020C</a> <b>415.41</b>	<a href="#">753301-020C</a> <b>798.44</b>	1	0	252
2-1/2	<a href="#">752301-025C</a> <b>432.80</b>	<a href="#">753301-025C</a> <b>833.28</b>	1	0	252
3	<a href="#">752301-030C</a> <b>467.64</b>	<a href="#">753301-030C</a> <b>910.38</b>	1	0	252
4	<a href="#">752301-040C</a> <b>542.25</b>	<a href="#">753301-040C</a> <b>1149.22</b>	1	0	252
6	<a href="#">752301-060C</a> <b>815.85</b>	<a href="#">753301-060C</a> <b>1855.58</b>	1	0	252
8	<a href="#">752301-080C</a> <b>1412.81</b>	<a href="#">753301-080C</a> <b>3134.18</b>	1	0	252
10	<a href="#">752301-100C</a> <b>2825.69</b>	<a href="#">753301-100C</a> <b>6283.18</b>	1	0	252
12	<a href="#">752301-120C</a> <b>3671.39</b>	<a href="#">753301-120C</a> <b>8166.14</b>	1	0	252

**High Purity TFM-Lined Butterfly Valves**



Pressure Rating @ 73°F (23°C), Water  
2" - 6" 150 psi

Maximum Service Temperature  
200°F (93°C)

**TFM-Lined**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**FKM O-ring Seal**

TFM PTFE Lined with backing O-rings, no fluid contact with elastomers or body

<a href="#">253322-020</a>	<b>2</b>	1	0	254	3191.97
<a href="#">253322-030</a>	<b>3</b>	1	0	254	3489.07
<a href="#">253322-040</a>	<b>4</b>	1	0	254	4469.01
<a href="#">253322-060</a>	<b>6</b>	1	0	254	5982.15