

**Valves Product**  
**Wafer Butterfly Valves & High Purity TFM-Lined Butterfly Valves**



**Wafer Butterfly Valves**

**CPVC**

Size	EPDM Seat	FKM Seat	Std Pk	Mstr Pk	Prod Code
------	-----------	----------	--------	---------	-----------

**Gear Operator**

2	752321-020C 1014.36	753321-020C 1381.53	1	0	252
2-1/2	752321-025C 1029.59	753321-025C 1451.78	1	0	252
3	752321-030C 1044.45	753321-030C 1517.07	1	0	252
4	752321-040C 1120.07	753321-040C 1758.11	1	0	252
6	752321-060C 1394.19	753321-060C 2476.46	1	0	252
8	752321-080C 1970.75	753321-080C 3804.49	1	0	252
10	752321-100C 2760.01	753321-100C 7051.25	1	0	252
12	752321-120C 3898.98	753321-120C 9166.16	1	0	252

**Valve Only**

2	752301-020C 394.64	753301-020C 758.52	1	0	252
2-1/2	752301-025C 411.16	753301-025C 791.62	1	0	252
3	752301-030C 444.26	753301-030C 864.86	1	0	252
4	752301-040C 515.14	753301-040C 1091.76	1	0	252
6	752301-060C 775.06	753301-060C 1762.80	1	0	252
8	752301-080C 1342.17	753301-080C 2977.47	1	0	252
10	752301-100C 2684.41	753301-100C 5969.02	1	0	252
12	752301-120C 3487.82	753301-120C 7757.83	1	0	252

**High Purity TFM-Lined Butterfly Valves**



Pressure Rating @ 73°F (23°C), Water  
2" - 6" 150 psi

Maximum Service Temperature  
200°F (93°C)

**TFM-Lined**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**FKM O-ring Seal**

TFM PTFE Lined with backing O-rings, no fluid contact with elastomers or body

253322-020	2	1	0	254	3032.37
253322-030	3	1	0	254	3314.62
253322-040	4	1	0	254	4245.56
253322-060	6	1	0	254	5683.04