

**Wafer Butterfly Valves & High Purity TFM-Lined Butterfly Valves**



**Wafer Butterfly Valves**

**CPVC**

Size	EPDM Seat	FKM Seat	Std Pk	Mstr Pk	Prod Code
------	-----------	----------	--------	---------	-----------

**Gear Operator**

2	<a href="#">752321-020C</a> <b>1123.95</b>	<a href="#">753321-020C</a> <b>1530.78</b>	1	0	252
2-1/2	<a href="#">752321-025C</a> <b>1140.82</b>	<a href="#">753321-025C</a> <b>1608.62</b>	1	0	252
3	<a href="#">752321-030C</a> <b>1157.28</b>	<a href="#">753321-030C</a> <b>1680.97</b>	1	0	252
4	<a href="#">752321-040C</a> <b>1241.07</b>	<a href="#">753321-040C</a> <b>1948.04</b>	1	0	252
6	<a href="#">752321-060C</a> <b>1544.81</b>	<a href="#">753321-060C</a> <b>2744.00</b>	1	0	252
8	<a href="#">752321-080C</a> <b>2183.65</b>	<a href="#">753321-080C</a> <b>4215.51</b>	1	0	252
10	<a href="#">752321-100C</a> <b>3058.18</b>	<a href="#">753321-100C</a> <b>7813.02</b>	1	0	252
12	<a href="#">752321-120C</a> <b>4320.20</b>	<a href="#">753321-120C</a> <b>10156.41</b>	1	0	252

**Valve Only**

2	<a href="#">752301-020C</a> <b>437.27</b>	<a href="#">753301-020C</a> <b>840.46</b>	1	0	252
2-1/2	<a href="#">752301-025C</a> <b>455.58</b>	<a href="#">753301-025C</a> <b>877.14</b>	1	0	252
3	<a href="#">752301-030C</a> <b>492.25</b>	<a href="#">753301-030C</a> <b>958.29</b>	1	0	252
4	<a href="#">752301-040C</a> <b>570.79</b>	<a href="#">753301-040C</a> <b>1209.71</b>	1	0	252
6	<a href="#">752301-060C</a> <b>858.79</b>	<a href="#">753301-060C</a> <b>1953.24</b>	1	0	252
8	<a href="#">752301-080C</a> <b>1487.17</b>	<a href="#">753301-080C</a> <b>3299.14</b>	1	0	252
10	<a href="#">752301-100C</a> <b>2974.41</b>	<a href="#">753301-100C</a> <b>6613.87</b>	1	0	252
12	<a href="#">752301-120C</a> <b>3864.62</b>	<a href="#">753301-120C</a> <b>8595.94</b>	1	0	252

**High Purity TFM-Lined Butterfly Valves**



Pressure Rating @ 73°F (23°C), Water  
2" - 6" 150 psi

Maximum Service Temperature  
200°F (93°C)

**TFM-Lined**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

**FKM O-ring Seal**

TFM PTFE Lined with backing O-rings, no fluid contact with elastomers or body

<a href="#">253322-020</a>	<b>2</b>	1	0	254	3359.97
<a href="#">253322-030</a>	<b>3</b>	1	0	254	3672.71
<a href="#">253322-040</a>	<b>4</b>	1	0	254	4704.22
<a href="#">253322-060</a>	<b>6</b>	1	0	254	6297.00