

Wafer Butterfly Valves & High Purity TFM-Lined Butterfly Valves



Wafer Butterfly Valves

CPVC

Size	EPDM Seat	FKM Seat	Std Pk	Mstr Pk	Prod Code
------	-----------	----------	--------	---------	-----------

Gear Operator

2	752321-020C 1067.75	753321-020C 1454.24	1	0	252
2-1/2	752321-025C 1083.78	753321-025C 1528.19	1	0	252
3	752321-030C 1099.42	753321-030C 1596.92	1	0	252
4	752321-040C 1179.02	753321-040C 1850.64	1	0	252
6	752321-060C 1467.57	753321-060C 2606.80	1	0	252
8	752321-080C 2074.47	753321-080C 4004.73	1	0	252
10	752321-100C 2905.27	753321-100C 7422.37	1	0	252
12	752321-120C 4104.19	753321-120C 9648.59	1	0	252

Valve Only

2	752301-020C 415.41	753301-020C 798.44	1	0	252
2-1/2	752301-025C 432.80	753301-025C 833.28	1	0	252
3	752301-030C 467.64	753301-030C 910.38	1	0	252
4	752301-040C 542.25	753301-040C 1149.22	1	0	252
6	752301-060C 815.85	753301-060C 1855.58	1	0	252
8	752301-080C 1412.81	753301-080C 3134.18	1	0	252
10	752301-100C 2825.69	753301-100C 6283.18	1	0	252
12	752301-120C 3671.39	753301-120C 8166.14	1	0	252

High Purity TFM-Lined Butterfly Valves



Pressure Rating @ 73°F (23°C), Water
2" - 6" 150 psi

Maximum Service Temperature
200°F (93°C)

TFM-Lined

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

FKM O-ring Seal

TFM PTFE Lined with backing O-rings, no fluid contact with elastomers or body

253322-020	2	1	0	254	3191.97
253322-030	3	1	0	254	3489.07
253322-040	4	1	0	254	4469.01
253322-060	6	1	0	254	5982.15