



Valves Product

Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Flanged Ends

1-1/2	6623-015 104.34	6633-015 113.41	1	4	210
2	6623-020 139.23	6633-020 145.34	1	0	210

CPVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005C 26.24	6632-005C 29.20	10	120	212
3/4	6622-007C 34.61	6632-007C 38.89	10	80	212
1	6622-010C 43.25	6632-010C 48.64	10	0	212
1-1/4	6622-012C 70.79	6632-012C 87.49	6	0	212
1-1/2	6622-015C 87.56	6632-015C 97.28	5	0	212
2	6622-020C 114.71	6632-020C 128.87	8	0	212

Threaded Ends

1/2	6621-005C 26.24	6631-005C 29.20	10	120	212
3/4	6621-007C 34.61	6631-007C 38.89	10	80	212
1	6621-010C 43.25	6631-010C 48.64	10	0	212
1-1/4	6621-012C 70.79	6631-012C 87.49	6	0	212
1-1/2	6621-015C 87.56	6631-015C 97.28	5	0	212
2	6621-020C 114.71	6631-020C 128.87	8	0	212

Flanged Ends

1/2	6623-005C 71.80	6633-005C 74.02	1	0	212
3/4	6623-007C 84.87	6633-007C 88.62	1	0	212
1	6623-010C 111.69	6633-010C 118.28	1	8	212
1-1/4	6623-012C 140.49	6633-012C 148.03	1	0	212
1-1/2	6623-015C 177.51	6633-015C 188.14	1	4	212
2	6623-020C 247.32	6633-020C 254.62	1	0	212

Compact Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi

3" - 6" 150 psi

Flanged 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)

CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

Socket/Threaded Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	2122-005 23.44	2132-005 26.40	10	80	210
3/4	2122-007 32.00	2132-007 32.77	10	0	210
1	2122-010 34.92	2132-010 39.20	10	0	210
1-1/4	2122-012 62.61	2132-012 69.61	6	0	210
1-1/2	2122-015 77.53	2132-015 81.01	5	0	210
2	2122-020 83.56	2132-020 93.89	6	0	210
3	2122-030 271.59	2132-030 305.12	1	4	211
4	2122-040 417.84	2132-040 601.45	1	0	211
6 (Lever Handle)	2122-060 542.64	2132-060 781.11	1	0	211
6 (Tee Handle)	21226-060 542.64	21326-060 781.11	1	0	211

Threaded Ends

1/2	2121-005 23.44	2131-005 26.40	10	80	210
3/4	2121-007 32.00	2131-007 32.77	10	0	210

Valves Product
Compact Ball Valves (Regular Style)



Compact Ball Valves (Regular Style)

PVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Threaded Ends					
1	2121-010 34.92	2131-010 39.20	10	0	210
1-1/4	2121-012 62.61	2131-012 69.61	6	0	210
1-1/2	2121-015 77.53	2131-015 81.01	5	0	210
2	2121-020 83.56	2131-020 93.89	6	0	210
3	2121-030 271.59	2131-030 305.12	1	4	211
4	2121-040 417.84	2131-040 601.45	1	0	211

Flanged Ends

1/2	2123-005 51.83	2133-005 55.21	1	8	210
3/4	2123-007 62.72	2133-007 65.21	1	8	210
1	2123-010 69.19	2133-010 73.45	1	8	210
1-1/4	2123-012 97.95	2133-012 104.94	1	8	210
1-1/2	2123-015 113.33	2133-015 118.66	1	4	210
2	2123-020 131.55	2133-020 141.78	1	0	210
3	2123-030 353.40	2133-030 386.94	1	0	211
4	2123-040 521.28	2133-040 704.88	1	0	211
6 (Lever Handle)	2123-060 1003.69	2133-060 1104.81	1	0	211
6 (Tee Handle)	21236-060 1003.69	21336-060 1104.81	1	0	211

CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Socket Ends					
1/2	2122-005C 27.62	2132-005C 30.72	10	80	212
3/4	2122-007C 36.43	2132-007C 40.96	10	0	212
1	2122-010C 45.55	2132-010C 51.20	10	0	212
1-1/4	2122-012C 92.17	2132-012C 102.37	6	0	212
1-1/2	2122-015C 113.87	2132-015C 119.72	5	0	212
2	2122-020C 120.76	2132-020C 135.67	6	0	212
3	2122-030C 367.41	2132-030C 409.80	1	4	213

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Socket Ends					
4	2122-040C 679.20	2132-040C 763.09	1	0	213
6 (Lever Handle)	2122-060C 1110.01	2132-060C 1182.76	1	0	213
6 (Tee Handle)	21226-060C 1110.01	21326-060C 1182.76	1	0	213

Threaded Ends

1/2	2121-005C 27.62	2131-005C 30.72	10	80	212
3/4	2121-007C 36.43	2131-007C 40.96	10	0	212
1	2121-010C 45.55	2131-010C 51.20	10	0	212
1-1/4	2121-012C 92.17	2131-012C 102.37	6	0	212
1-1/2	2121-015C 113.87	2131-015C 119.72	5	0	212
2	2121-020C 120.76	2131-020C 135.67	6	0	212
3	2121-030C 367.41	2131-030C 409.80	1	4	213
4	2121-040C 679.20	2131-040C 763.09	1	0	213

Flanged Ends

1/2	2123-005C 77.00	2133-005C 80.12	1	8	212
3/4	2123-007C 89.40	2133-007C 93.92	1	8	212
1	2123-010C 105.71	2133-010C 111.38	1	8	212
1-1/4	2123-012C 166.57	2133-012C 176.80	1	8	212
1-1/2	2123-015C 208.31	2133-015C 214.75	1	4	212
2	2123-020C 235.91	2133-020C 250.82	1	0	212
3	2123-030C 564.93	2133-030C 607.32	1	0	213
4	2123-040C 882.49	2133-040C 966.37	1	0	213
6 (Lever Handle)	2123-060C 1676.23	2133-060C 1798.24	1	0	213
6 (Tee Handle)	21236-060C 1676.23	21336-060C 1798.24	1	0	213