



Valves Product

Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Flanged Ends

1-1/2	6623-015 115.61	6633-015 125.66	1	4	210
2	6623-020 154.27	6633-020 161.04	1	0	210

CPVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005C 29.07	6632-005C 32.36	10	120	212
3/4	6622-007C 38.35	6632-007C 43.09	10	80	212
1	6622-010C 47.93	6632-010C 53.89	10	0	212
1-1/4	6622-012C 78.44	6632-012C 96.94	6	0	212
1-1/2	6622-015C 97.02	6632-015C 107.79	5	0	212
2	6622-020C 127.11	6632-020C 142.79	8	0	212

Threaded Ends

1/2	6621-005C 29.07	6631-005C 32.36	10	120	212
3/4	6621-007C 38.35	6631-007C 43.09	10	80	212
1	6621-010C 47.93	6631-010C 53.89	10	0	212
1-1/4	6621-012C 78.44	6631-012C 96.94	6	0	212
1-1/2	6621-015C 97.02	6631-015C 107.79	5	0	212
2	6621-020C 127.11	6631-020C 142.79	8	0	212

Flanged Ends

1/2	6623-005C 79.56	6633-005C 82.02	1	0	212
3/4	6623-007C 94.04	6633-007C 98.19	1	0	212
1	6623-010C 123.76	6633-010C 131.06	1	8	212
1-1/4	6623-012C 155.66	6633-012C 164.02	1	0	212
1-1/2	6623-015C 196.68	6633-015C 208.46	1	4	212
2	6623-020C 274.04	6633-020C 282.13	1	0	212

Compact Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water

1/2" - 2"	235 psi
3" - 6"	150 psi
Flanged	150 psi

Maximum Service Temperature

PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply
Rated for Vacuum Service

Socket/Threaded Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section
for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	2122-005 25.97	2132-005 29.25	10	80	210
3/4	2122-007 35.45	2132-007 36.31	10	0	210
1	2122-010 38.69	2132-010 43.43	10	0	210
1-1/4	2122-012 69.38	2132-012 77.13	6	0	210
1-1/2	2122-015 85.91	2132-015 89.76	5	0	210
2	2122-020 92.59	2132-020 104.03	6	0	210
3	2122-030 300.93	2132-030 338.08	1	4	211
4	2122-040 462.98	2132-040 666.43	1	0	211
6 (Lever Handle)	2122-060 601.26	2132-060 865.49	1	0	211
6 (Tee Handle)	21226-060 601.26	21326-060 865.49	1	0	211

Threaded Ends

1/2	2121-005 25.97	2131-005 29.25	10	80	210
3/4	2121-007 35.45	2131-007 36.31	10	0	210

Valves Product
Compact Ball Valves (Regular Style)



Compact Ball Valves (Regular Style)

PVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Threaded Ends					
1	2121-010 38.69	2131-010 43.43	10	0	210
1-1/4	2121-012 69.38	2131-012 77.13	6	0	210
1-1/2	2121-015 85.91	2131-015 89.76	5	0	210
2	2121-020 92.59	2131-020 104.03	6	0	210
3	2121-030 300.93	2131-030 338.08	1	4	211
4	2121-040 462.98	2131-040 666.43	1	0	211

Flanged Ends

1/2	2123-005 57.43	2133-005 61.18	1	8	210
3/4	2123-007 69.49	2133-007 72.25	1	8	210
1	2123-010 76.66	2133-010 81.39	1	8	210
1-1/4	2123-012 108.54	2133-012 116.27	1	8	210
1-1/2	2123-015 125.57	2133-015 131.48	1	4	210
2	2123-020 145.76	2133-020 157.09	1	0	210
3	2123-030 391.58	2133-030 428.75	1	0	211
4	2123-040 577.60	2133-040 781.03	1	0	211
6 (Lever Handle)	2123-060 1112.13	2133-060 1224.17	1	0	211
6 (Tee Handle)	21236-060 1112.13	21336-060 1224.17	1	0	211

CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Socket Ends					
1/2	2122-005C 30.60	2132-005C 34.04	10	80	212
3/4	2122-007C 40.37	2132-007C 45.39	10	0	212
1	2122-010C 50.47	2132-010C 56.73	10	0	212
1-1/4	2122-012C 102.13	2132-012C 113.43	6	0	212
1-1/2	2122-015C 126.17	2132-015C 132.65	5	0	212
2	2122-020C 133.81	2132-020C 150.33	6	0	212
3	2122-030C 407.11	2132-030C 454.07	1	4	213

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
Socket Ends					
4	2122-040C 752.58	2132-040C 845.53	1	0	213
6 (Lever Handle)	2122-060C 1229.93	2132-060C 1310.54	1	0	213
6 (Tee Handle)	21226-060C 1229.93	21326-060C 1310.54	1	0	213

Threaded Ends

1/2	2121-005C 30.60	2131-005C 34.04	10	80	212
3/4	2121-007C 40.37	2131-007C 45.39	10	0	212
1	2121-010C 50.47	2131-010C 56.73	10	0	212
1-1/4	2121-012C 102.13	2131-012C 113.43	6	0	212
1-1/2	2121-015C 126.17	2131-015C 132.65	5	0	212
2	2121-020C 133.81	2131-020C 150.33	6	0	212
3	2121-030C 407.11	2131-030C 454.07	1	4	213
4	2121-040C 752.58	2131-040C 845.53	1	0	213

Flanged Ends

1/2	2123-005C 85.32	2133-005C 88.78	1	8	212
3/4	2123-007C 99.06	2133-007C 104.06	1	8	212
1	2123-010C 117.13	2133-010C 123.41	1	8	212
1-1/4	2123-012C 184.57	2133-012C 195.91	1	8	212
1-1/2	2123-015C 230.81	2133-015C 237.95	1	4	212
2	2123-020C 261.40	2133-020C 277.92	1	0	212
3	2123-030C 625.96	2133-030C 672.93	1	0	213
4	2123-040C 977.83	2133-040C 1070.77	1	0	213
6 (Lever Handle)	2123-060C 1857.32	2133-060C 1992.51	1	0	213
6 (Tee Handle)	21236-060C 1857.32	21336-060C 1992.51	1	0	213