

Valves Product
Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 461.55	2422-040W 508.51	2432-040W 552.78	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 21.98	2421-005G 24.37	2431-005G 27.11	10	120	240
3/4	2411-007G 27.69	2421-007G 30.80	2431-007G 34.20	10	80	240
1	2411-010G 32.58	2421-010G 36.16	2431-010G 40.19	10	0	240
1-1/4	2411-012G 45.24	2421-012G 50.29	2431-012G 55.81	6	0	240
1-1/2	2411-015G 56.96	2421-015G 66.72	2431-015G 74.19	5	0	240
2	2411-020G 65.95	2421-020G 73.28	2431-020G 81.39	5	0	240
3	2411-030G 229.86	2421-030G 285.08	2431-030G 328.75	1	0	240
4	2411-040G 485.82	2421-040G 535.29	2431-040G 581.85	1	0	240

Socket Ends

1/2	2412-005G 21.98	2422-005G 24.37	2432-005G 27.11	10	120	240
3/4	2412-007G 27.69	2422-007G 30.80	2432-007G 34.20	10	80	240
1	2412-010G 32.58	2422-010G 36.16	2432-010G 40.19	10	0	240
1-1/4	2412-012G 45.24	2422-012G 50.29	2432-012G 55.81	5	0	240
1-1/2	2412-015G 57.02	2422-015G 66.72	2432-015G 74.19	5	0	240
2	2412-020G 65.95	2422-020G 73.28	2432-020G 81.39	5	0	240
3	2412-030G 229.86	2422-030G 285.08	2432-030G 328.75	1	0	240
4	2412-040G 485.82	2422-040G 535.29	2432-040G 581.85	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit
 (non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options
 and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 22.28	6632-005 25.08	10	120	210
3/4	6622-007 30.40	6632-007 31.13	10	80	210
1	6622-010 33.19	6632-010 37.22	10	0	210
1-1/4	6622-012 49.93	6632-012 57.69	6	0	210
1-1/2	6622-015 59.46	6632-015 66.14	5	0	210
2	6622-020 79.39	6632-020 89.20	8	0	210

Threaded Ends

1/2	6621-005 22.28	6631-005 25.08	10	120	210
3/4	6621-007 30.40	6631-007 31.13	10	80	210
1	6621-010 33.19	6631-010 37.22	10	0	210
1-1/4	6621-012 54.65	6631-012 57.69	6	0	210
1-1/2	6621-015 59.46	6631-015 66.14	5	0	210
2	6621-020 79.39	6631-020 89.20	8	0	210

Flanged Ends

1/2	6623-005 46.93	6633-005 49.31	10	0	210
3/4	6623-007 53.00	6633-007 54.85	10	120	210
1	6623-010 69.06	6633-010 72.77	10	0	210
1-1/4	6623-012 86.24	6633-012 92.52	10	0	210



Valves Product

Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Flanged Ends

1-1/2	6623-015 104.34	6633-015 113.41	1	4	210
2	6623-020 139.23	6633-020 145.34	1	0	210

CPVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005C 26.24	6632-005C 29.20	10	120	212
3/4	6622-007C 34.61	6632-007C 38.89	10	80	212
1	6622-010C 43.25	6632-010C 48.64	10	0	212
1-1/4	6622-012C 70.79	6632-012C 87.49	6	0	212
1-1/2	6622-015C 87.56	6632-015C 97.28	5	0	212
2	6622-020C 114.71	6632-020C 128.87	8	0	212

Threaded Ends

1/2	6621-005C 26.24	6631-005C 29.20	10	120	212
3/4	6621-007C 34.61	6631-007C 38.89	10	80	212
1	6621-010C 43.25	6631-010C 48.64	10	0	212
1-1/4	6621-012C 70.79	6631-012C 87.49	6	0	212
1-1/2	6621-015C 87.56	6631-015C 97.28	5	0	212
2	6621-020C 114.71	6631-020C 128.87	8	0	212

Flanged Ends

1/2	6623-005C 71.80	6633-005C 74.02	1	0	212
3/4	6623-007C 84.87	6633-007C 88.62	1	0	212
1	6623-010C 111.69	6633-010C 118.28	1	8	212
1-1/4	6623-012C 140.49	6633-012C 148.03	1	0	212
1-1/2	6623-015C 177.51	6633-015C 188.14	1	4	212
2	6623-020C 247.32	6633-020C 254.62	1	0	212

Compact Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi

3" - 6" 150 psi

Flanged 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)

CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

Socket/Threaded Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	2122-005 23.44	2132-005 26.40	10	80	210
3/4	2122-007 32.00	2132-007 32.77	10	0	210
1	2122-010 34.92	2132-010 39.20	10	0	210
1-1/4	2122-012 62.61	2132-012 69.61	6	0	210
1-1/2	2122-015 77.53	2132-015 81.01	5	0	210
2	2122-020 83.56	2132-020 93.89	6	0	210
3	2122-030 271.59	2132-030 305.12	1	4	211
4	2122-040 417.84	2132-040 601.45	1	0	211
6 (Lever Handle)	2122-060 542.64	2132-060 781.11	1	0	211
6 (Tee Handle)	21226-060 542.64	21326-060 781.11	1	0	211

Threaded Ends

1/2	2121-005 23.44	2131-005 26.40	10	80	210
3/4	2121-007 32.00	2131-007 32.77	10	0	210