

Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 511.41	2422-040W 563.44	2432-040W 612.49	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 24.36	2421-005G 27.00	2431-005G 30.04	10	120	240
3/4	2411-007G 30.68	2421-007G 34.13	2431-007G 37.89	10	80	240
1	2411-010G 36.09	2421-010G 40.06	2431-010G 44.54	10	0	240
1-1/4	2411-012G 50.13	2421-012G 55.73	2431-012G 61.84	6	0	240
1-1/2	2411-015G 63.12	2421-015G 73.93	2431-015G 82.20	5	0	240
2	2411-020G 73.07	2421-020G 81.20	2431-020G 90.18	5	0	240
3	2411-030G 254.69	2421-030G 315.87	2431-030G 364.26	1	0	240
4	2411-040G 538.31	2421-040G 593.12	2431-040G 644.71	1	0	240

Socket Ends

1/2	2412-005G 24.36	2422-005G 27.00	2432-005G 30.04	10	120	240
3/4	2412-007G 30.68	2422-007G 34.13	2432-007G 37.89	10	80	240
1	2412-010G 36.09	2422-010G 40.06	2432-010G 44.54	10	0	240
1-1/4	2412-012G 50.13	2422-012G 55.73	2432-012G 61.84	5	0	240
1-1/2	2412-015G 63.18	2422-015G 73.93	2432-015G 82.20	5	0	240
2	2412-020G 73.07	2422-020G 81.20	2432-020G 90.18	5	0	240
3	2412-030G 254.69	2422-030G 315.87	2432-030G 364.26	1	0	240
4	2412-040G 538.31	2422-040G 593.12	2432-040G 644.71	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 2" 235 psi
Flanged 150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit
(non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options
and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 24.68	6632-005 27.79	10	120	210
3/4	6622-007 33.68	6632-007 34.49	10	80	210
1	6622-010 36.78	6632-010 41.24	10	0	210
1-1/4	6622-012 55.33	6632-012 63.93	6	0	210
1-1/2	6622-015 65.88	6632-015 73.28	5	0	210
2	6622-020 87.97	6632-020 98.83	8	0	210

Threaded Ends

1/2	6621-005 24.68	6631-005 27.79	10	120	210
3/4	6621-007 33.68	6631-007 34.49	10	80	210
1	6621-010 36.78	6631-010 41.24	10	0	210
1-1/4	6621-012 60.56	6631-012 63.93	6	0	210
1-1/2	6621-015 65.88	6631-015 73.28	5	0	210
2	6621-020 87.97	6631-020 98.83	8	0	210

Flanged Ends

1/2	6623-005 52.00	6633-005 54.64	10	0	210
3/4	6623-007 58.73	6633-007 60.78	10	120	210
1	6623-010 76.52	6633-010 80.63	10	0	210
1-1/4	6623-012 95.56	6633-012 102.52	10	0	210



Valves Product

Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Flanged Ends

1-1/2	6623-015 115.61	6633-015 125.66	1	4	210
2	6623-020 154.27	6633-020 161.04	1	0	210

CPVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005C 29.07	6632-005C 32.36	10	120	212
3/4	6622-007C 38.35	6632-007C 43.09	10	80	212
1	6622-010C 47.93	6632-010C 53.89	10	0	212
1-1/4	6622-012C 78.44	6632-012C 96.94	6	0	212
1-1/2	6622-015C 97.02	6632-015C 107.79	5	0	212
2	6622-020C 127.11	6632-020C 142.79	8	0	212

Threaded Ends

1/2	6621-005C 29.07	6631-005C 32.36	10	120	212
3/4	6621-007C 38.35	6631-007C 43.09	10	80	212
1	6621-010C 47.93	6631-010C 53.89	10	0	212
1-1/4	6621-012C 78.44	6631-012C 96.94	6	0	212
1-1/2	6621-015C 97.02	6631-015C 107.79	5	0	212
2	6621-020C 127.11	6631-020C 142.79	8	0	212

Flanged Ends

1/2	6623-005C 79.56	6633-005C 82.02	1	0	212
3/4	6623-007C 94.04	6633-007C 98.19	1	0	212
1	6623-010C 123.76	6633-010C 131.06	1	8	212
1-1/4	6623-012C 155.66	6633-012C 164.02	1	0	212
1-1/2	6623-015C 196.68	6633-015C 208.46	1	4	212
2	6623-020C 274.04	6633-020C 282.13	1	0	212

Compact Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi
3" - 6" 150 psi
Flanged 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply
Rated for Vacuum Service

Socket/Threaded Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section
for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	2122-005 25.97	2132-005 29.25	10	80	210
3/4	2122-007 35.45	2132-007 36.31	10	0	210
1	2122-010 38.69	2132-010 43.43	10	0	210
1-1/4	2122-012 69.38	2132-012 77.13	6	0	210
1-1/2	2122-015 85.91	2132-015 89.76	5	0	210
2	2122-020 92.59	2132-020 104.03	6	0	210
3	2122-030 300.93	2132-030 338.08	1	4	211
4	2122-040 462.98	2132-040 666.43	1	0	211
6 (Lever Handle)	2122-060 601.26	2132-060 865.49	1	0	211
6 (Tee Handle)	21226-060 601.26	21326-060 865.49	1	0	211

Threaded Ends

1/2	2121-005 25.97	2131-005 29.25	10	80	210
3/4	2121-007 35.45	2131-007 36.31	10	0	210