

Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 485.84	2422-040W 535.27	2432-040W 581.87	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 23.14	2421-005G 25.65	2431-005G 28.54	10	120	240
3/4	2411-007G 29.15	2421-007G 32.42	2431-007G 36.00	10	80	240
1	2411-010G 34.29	2421-010G 38.06	2431-010G 42.31	10	0	240
1-1/4	2411-012G 47.62	2421-012G 52.94	2431-012G 58.75	6	0	240
1-1/2	2411-015G 59.96	2421-015G 70.23	2431-015G 78.09	5	0	240
2	2411-020G 69.42	2421-020G 77.14	2431-020G 85.67	5	0	240
3	2411-030G 241.96	2421-030G 300.08	2431-030G 346.05	1	0	240
4	2411-040G 511.39	2421-040G 563.46	2431-040G 612.47	1	0	240

Socket Ends

1/2	2412-005G 23.14	2422-005G 25.65	2432-005G 28.54	10	120	240
3/4	2412-007G 29.15	2422-007G 32.42	2432-007G 36.00	10	80	240
1	2412-010G 34.29	2422-010G 38.06	2432-010G 42.31	10	0	240
1-1/4	2412-012G 47.62	2422-012G 52.94	2432-012G 58.75	5	0	240
1-1/2	2412-015G 60.02	2422-015G 70.23	2432-015G 78.09	5	0	240
2	2412-020G 69.42	2422-020G 77.14	2432-020G 85.67	5	0	240
3	2412-030G 241.96	2422-030G 300.08	2432-030G 346.05	1	0	240
4	2412-040G 511.39	2422-040G 563.46	2432-040G 612.47	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water  
1/2" - 2" 235 psi  
Flanged 150 psi

Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)  
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.  
Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit  
(non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options  
and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 23.45	6632-005 26.40	10	120	210
3/4	6622-007 32.00	6632-007 32.77	10	80	210
1	6622-010 34.94	6632-010 39.18	10	0	210
1-1/4	6622-012 52.56	6632-012 60.73	6	0	210
1-1/2	6622-015 62.59	6632-015 69.62	5	0	210
2	6622-020 83.57	6632-020 93.89	8	0	210

Threaded Ends

1/2	6621-005 23.45	6631-005 26.40	10	120	210
3/4	6621-007 32.00	6631-007 32.77	10	80	210
1	6621-010 34.94	6631-010 39.18	10	0	210
1-1/4	6621-012 57.53	6631-012 60.73	6	0	210
1-1/2	6621-015 62.59	6631-015 69.62	5	0	210
2	6621-020 83.57	6631-020 93.89	8	0	210

Flanged Ends

1/2	6623-005 49.40	6633-005 51.91	10	0	210
3/4	6623-007 55.79	6633-007 57.74	10	120	210
1	6623-010 72.69	6633-010 76.60	10	0	210
1-1/4	6623-012 90.78	6633-012 97.39	10	0	210



Valves Product

**Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)**

**Compact 2000 Ball Valves**

**PVC 2000 Compact Ball Valve (continued)**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

**Flanged Ends**

1-1/2	6623-015 109.83	6633-015 119.38	1	4	210
2	6623-020 146.56	6633-020 152.99	1	0	210

**CPVC 2000 Compact Ball Valve**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

**Socket Ends**

1/2	6622-005C 27.62	6632-005C 30.74	10	120	212
3/4	6622-007C 36.43	6632-007C 40.94	10	80	212
1	6622-010C 45.53	6632-010C 51.20	10	0	212
1-1/4	6622-012C 74.52	6632-012C 92.09	6	0	212
1-1/2	6622-015C 92.17	6632-015C 102.40	5	0	212
2	6622-020C 120.75	6632-020C 135.65	8	0	212

**Threaded Ends**

1/2	6621-005C 27.62	6631-005C 30.74	10	120	212
3/4	6621-007C 36.43	6631-007C 40.94	10	80	212
1	6621-010C 45.53	6631-010C 51.20	10	0	212
1-1/4	6621-012C 74.52	6631-012C 92.09	6	0	212
1-1/2	6621-015C 92.17	6631-015C 102.40	5	0	212
2	6621-020C 120.75	6631-020C 135.65	8	0	212

**Flanged Ends**

1/2	6623-005C 75.58	6633-005C 77.92	1	0	212
3/4	6623-007C 89.34	6633-007C 93.28	1	0	212
1	6623-010C 117.57	6633-010C 124.51	1	8	212
1-1/4	6623-012C 147.88	6633-012C 155.82	1	0	212
1-1/2	6623-015C 186.85	6633-015C 198.04	1	4	212
2	6623-020C 260.34	6633-020C 268.02	1	0	212

**Compact Ball Valves (Regular Style)**



**Pressure Rating @ 73°F (23°C), Water**

1/2" - 2"	235 psi
3" - 6"	150 psi
Flanged	150 psi

**Maximum Service Temperature**

PVC	= 140°F (60°C)
CPVC	= 200°F (93°C)

**Temperature/Pressure De-ratings Apply**  
Rated for Vacuum Service

**Socket/Threaded Style**

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section  
for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

**PVC**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

**Socket Ends**

1/2	2122-005 24.67	2132-005 27.79	10	80	210
3/4	2122-007 33.68	2132-007 34.49	10	0	210
1	2122-010 36.76	2132-010 41.26	10	0	210
1-1/4	2122-012 65.91	2132-012 73.27	6	0	210
1-1/2	2122-015 81.61	2132-015 85.27	5	0	210
2	2122-020 87.96	2132-020 98.83	6	0	210
3	2122-030 285.88	2132-030 321.18	1	4	211
4	2122-040 439.83	2132-040 633.11	1	0	211
6 (Lever Handle)	2122-060 571.20	2132-060 822.22	1	0	211
6 (Tee Handle)	21226-060 571.20	21326-060 822.22	1	0	211

**Threaded Ends**

1/2	2121-005 24.67	2131-005 27.79	10	80	210
3/4	2121-007 33.68	2131-007 34.49	10	0	210