

Valves Product  
**Utility Ball Valves & CWV Ball Valves**



**Utility Ball Valves**

**PVC w/EPDM O-ring Seal (continued)**

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
<b>PVC Gray</b>					
1	2621-010G 16.76	2622-010G 16.76	25	0	215
1-1/4	2621-012G 22.19	2622-012G 22.19	20	0	215
1-1/2	2621-015G 33.87	2622-015G 33.87	20	0	215
2	2621-020G 42.81	2622-020G 42.81	8	0	215
2-1/2	2621-025G 73.28	2622-025G 73.28	6	0	214
3	2621-030G 131.43	2622-030G 131.43	1	4	214
4	2621-040G 240.89	2622-040G 240.89	1	0	214
6	---	2622-060G 388.65	1	0	214

**CPVC w/EPDM O-ring Seal**

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
<b>CPVC</b>					
1/2	2621-005C 13.68	2622-005C 13.68	50	0	216
3/4	2621-007C 17.39	2622-007C 17.39	25	0	216
1	2621-010C 18.89	2622-010C 18.89	25	0	216
1-1/4	2621-012C 26.62	2622-012C 26.62	20	0	216
1-1/2	2621-015C 41.28	2622-015C 41.28	20	0	216
2	2621-020C 51.36	2622-020C 51.36	8	0	216
2-1/2	---	2622-025C 104.54	6	0	216
3	---	2622-030C 152.62	1	4	216

**CWV Ball Valves**



A Combination of Economy & Quality  
- Made in the U.S.A.

For Greater Value in a General  
Purpose Cold Water Valve

Pressure Rating @ 73°F (23°C), Water  
150 psi

You don't have to go overseas to find an economical general purpose ball valve! Spears® CWV BALL VALVES are produced in the U.S.A. with Spears® high quality construction and NSF® Certified for potable water service. Designed for use with cold water, these PVC valves may be suitable for some applications previously handled by Spears® Utility Valves. Available in IPS sizes 1/2" through 4" with a Full 1-Year Warranty.

**CWV PVC Ball Valve**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Threaded Ends</b>					
8721-005	1/2	50	0	204	9.34
8721-007	3/4	25	0	204	11.08
8721-010	1	25	0	204	15.07
8721-012	1-1/4	20	0	204	19.98
8721-015	1-1/2	20	0	204	30.49
8721-020	2	10	0	204	38.54
8721-025	2-1/2	6	0	205	65.96
8721-030	3	1	4	205	118.29
8721-040	4	1	0	205	216.81

**CWV PVC Ball Valve**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Socket Ends</b>					
8722-005	1/2	50	0	204	9.34
8722-007	3/4	25	0	204	11.08
8722-010	1	25	0	204	15.07
8722-012	1-1/4	20	0	204	19.98
8722-015	1-1/2	20	0	204	30.49
8722-020	2	10	0	204	38.54
8722-025	2-1/2	6	0	205	65.96
8722-030	3	1	4	205	118.29
8722-040	4	1	0	205	216.81