

Valves Product  
**Utility Ball Valves & CWV Ball Valves**



**Utility Ball Valves**

**PVC w/EPDM O-ring Seal (continued)**

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
<b>PVC Gray</b>					
1	2621-010G 15.92	2622-010G 15.92	25	0	215
1-1/4	2621-012G 21.08	2622-012G 21.08	20	0	215
1-1/2	2621-015G 32.18	2622-015G 32.18	20	0	215
2	2621-020G 40.67	2622-020G 40.67	8	0	215
2-1/2	2621-025G 69.62	2622-025G 69.62	6	0	214
3	2621-030G 124.86	2622-030G 124.86	1	4	214
4	2621-040G 228.85	2622-040G 228.85	1	0	214
6	2622-060G 369.22	---	1	0	214

**CPVC w/EPDM O-ring Seal**

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
<b>CPVC</b>					
1/2	2621-005C 13.00	2622-005C 13.00	50	0	216
3/4	2621-007C 16.52	2622-007C 16.52	25	0	216
1	2621-010C 17.95	2622-010C 17.95	25	0	216
1-1/4	2621-012C 25.29	2622-012C 25.29	20	0	216
1-1/2	2621-015C 39.22	2622-015C 39.22	20	0	216
2	2621-020C 48.79	2622-020C 48.79	8	0	216
2-1/2	---	2622-025C 99.31	6	0	216
3	---	2622-030C 144.99	1	4	216

**CWV Ball Valves**



**A Combination of Economy & Quality  
- Made in the U.S.A.  
For Greater Value in a General  
Purpose Cold Water Valve**

Pressure Rating @ 73°F (23°C), Water  
150 psi

You don't have to go overseas to find an economical general purpose ball valve! Spears® CWV BALL VALVES are produced in the U.S.A. with Spears® high quality construction and NSF® Certified for potable water service. Designed for use with cold water, these PVC valves may be suitable for some applications previously handled by Spears® Utility Valves. Available in IPS sizes 1/2" through 4" with a Full 1-Year Warranty.

**CWV PVC Ball Valve**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Threaded Ends</b>					
8721-005	1/2	50	0	204	8.87
8721-007	3/4	25	0	204	10.53
8721-010	1	25	0	204	14.32
8721-012	1-1/4	20	0	204	18.98
8721-015	1-1/2	20	0	204	28.97
8721-020	2	10	0	204	36.61
8721-025	2-1/2	6	0	205	62.66
8721-030	3	1	4	205	112.38
8721-040	4	1	0	205	205.97

**CWV PVC Ball Valve**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Socket Ends</b>					
8722-005	1/2	50	0	204	8.87
8722-007	3/4	25	0	204	10.53
8722-010	1	25	0	204	14.32
8722-012	1-1/4	20	0	204	18.98
8722-015	1-1/2	20	0	204	28.97
8722-020	2	10	0	204	36.61
8722-025	2-1/2	6	0	205	62.66
8722-030	3	1	4	205	112.38
8722-040	4	1	0	205	205.97