



## Valves Product Lab Ball Valves & Utility Ball Valves

### Lab Ball Valves



Socket/Threaded Valve Only



Valve & Adapters

**Valve & Adapters includes:**

- Pressure Rating @ 73°F (23°C), Water  
1/4" - 3/8" 150 psi
- Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- Rated for Vacuum Service
- 1 - Threaded 1/4" Valve
  - 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
  - 2 - EPDM or FKM O-rings (AS568-013 size)
  - 1 - End Connector Wrench
  - 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
  - OR -
  - 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters

### PVC Lab Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

#### Valve & Adapters Threaded Ends

1/4X1/4T	1529-002A 27.11	1539-002A 28.34	1	25	218
1/4X3/8T	1529-002 27.11	1539-002 28.34	1	25	218

#### Valve only Threaded Ends

1/4	1521-002 21.66	1531-002 24.12	50	200	218
3/8	1521-003 30.45	1531-003 33.76	50	200	218

#### Valve only Socket Ends

1/4	1522-002 21.66	1532-002 24.51	50	200	218
3/8	1522-003 30.45	1532-003 33.76	50	200	218

### CPVC Lab Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

#### Valve & Adapters Threaded Ends

1/4X1/4T	1529-002CA 32.54	1539-002CA 33.17	1	25	219
1/4X3/8T	1529-002C 32.54	1539-002C 33.17	1	25	219

### CPVC Lab Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

#### Valve only Threaded Ends

1/4	1521-002C 26.05	1531-002C 28.64	50	200	219
3/8	1521-003C 36.54	1531-003C 34.24	50	200	219

#### Valve only Socket Ends

1/4	1522-002C 26.05	1532-002C 31.00	50	200	219
3/8	1522-003C 36.54	1532-003C 40.56	50	200	219

### Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water  
1/2" - 6" 150 psi

Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

**Note:** Standard 6" Valve uses Lever-Style Handle for proper leverage.

### PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
------	---------------	-------------	--------	---------	-----------

#### PVC White

1/2	2621-005 9.86	2622-005 9.86	50	0	215
3/4	2621-007 11.71	2622-007 11.71	25	0	215
1	2621-010 15.92	2622-010 15.92	25	0	215
1-1/4	2621-012 21.08	2622-012 21.08	20	0	215
1-1/2	2621-015 32.18	2622-015 32.18	20	0	215
2	2621-020 40.67	2622-020 40.67	8	0	215
2-1/2	2621-025 69.62	2622-025 69.62	6	0	214
3	2621-030 124.86	2622-030 124.86	1	4	214
4	2621-040 228.85	2622-040 228.85	1	0	214
6 (Lever Handle)	---	2622-060 369.22	1	0	214

#### PVC Gray

1/2	2621-005G 9.86	2622-005G 9.86	50	0	215
3/4	2621-007G 11.71	2622-007G 11.71	25	0	215