



Valves Product

Lab Ball Valves & Utility Ball Valves

Lab Ball Valves



Socket/Threaded Valve Only



Valve & Adapters

Valve & Adapters includes:

- Pressure Rating @ 73°F (23°C), Water  
1/8" - 3/8" 150 psi
- Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- Rated for Vacuum Service
- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or FKM O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters

Lab Valve - PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002A 28.54	1539-002A 29.83	1	25	218
1/4X3/8T	1529-002 28.54	1539-002 29.83	1	25	218

Valve only Threaded Ends

1/4	1521-002 22.80	1531-002 25.39	50	200	218
3/8	1521-003 32.05	1531-003 35.54	50	200	218

Valve Only Female x Male Thread Ends

1/8	152FM-001 28.54	153FM-001 29.83	25	200	218
1/4	152FM-002 28.54	153FM-002 29.83	25	200	218

Valve only Socket Ends

1/4	1522-002 22.80	---	50	200	218
3/8	1522-003 32.05	---	50	200	218

Lab Valve - CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002CA 34.25	1539-002CA 34.92	1	25	219
1/4X3/8T	1529-002C 34.25	1539-002C 34.92	1	25	219

Valve only Threaded Ends

1/4	1521-002C 27.42	1531-002C 30.15	50	200	219
3/8	1521-003C 38.46	1531-003C 36.04	50	200	219

Valve Only Female x Male Thread Ends

1/8	152FM-001C 34.25	---	25	200	219
1/4	152FM-002C 34.25	---	25	200	219

Valve only Socket Ends

1/4	1522-002C 27.42	1532-002C 32.63	50	200	219
3/8	1522-003C 38.46	1532-003C 42.69	50	200	219

Utility Ball Valves



- Pressure Rating @ 73°F (23°C), Water  
1/2" - 6" 150 psi
- Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- All Valves Assembled with Silicone-Free, Water Soluble Lubricant
- Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
------	---------------	-------------	--------	---------	-----------

PVC White

1/2	2621-005 10.38	2622-005 10.38	50	0	215
3/4	2621-007 12.33	2622-007 12.33	25	0	215
1	2621-010 16.76	2622-010 16.76	25	0	215
1-1/4	2621-012 22.19	2622-012 22.19	20	0	215
1-1/2	2621-015 33.87	2622-015 33.87	20	0	215
2	2621-020 42.81	2622-020 42.81	8	0	215
2-1/2	2621-025 73.28	2622-025 73.28	6	0	214
3	2621-030 131.43	2622-030 131.43	1	4	214