



Valves Product

Lab Ball Valves & Utility Ball Valves

Lab Ball Valves



Socket/Threaded Valve Only



Valve & Adapters

Valve & Adapters includes:

- Pressure Rating @ 73°F (23°C), Water
1/8" - 3/8" 150 psi
- Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- Rated for Vacuum Service
- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or FKM O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters

Lab Valve - PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002A 30.04	1539-002A 31.40	1	25	218
1/4X3/8T	1529-002 30.04	1539-002 31.40	1	25	218

Valve only Threaded Ends

1/4	1521-002 24.00	1531-002 26.73	50	200	218
3/8	1521-003 33.74	1531-003 37.41	50	200	218

Valve Only Female x Male Thread Ends

1/8	152FM-001 30.04	153FM-001 31.40	25	200	218
1/4	152FM-002 30.04	153FM-002 31.40	25	200	218

Valve only Socket Ends

1/4	1522-002 24.00	---	50	200	218
3/8	1522-003 33.74	---	50	200	218

Lab Valve - CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002CA 36.05	1539-002CA 36.76	1	25	219
1/4X3/8T	1529-002C 36.05	1539-002C 36.76	1	25	219

Valve only Threaded Ends

1/4	1521-002C 28.86	1531-002C 31.74	50	200	219
3/8	1521-003C 40.48	1531-003C 37.94	50	200	219

Valve Only Female x Male Thread Ends

1/8	152FM-001C 36.05	---	25	200	219
1/4	152FM-002C 36.05	---	25	200	219

Valve only Socket Ends

1/4	1522-002C 28.86	1532-002C 34.35	50	200	219
3/8	1522-003C 40.48	1532-003C 44.94	50	200	219

Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 6" 150 psi
Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply
All Valves Assembled with Silicone-Free, Water Soluble Lubricant
Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
------	---------------	-------------	--------	---------	-----------

PVC White

1/2	2621-005 10.93	2622-005 10.93	50	0	215
3/4	2621-007 12.98	2622-007 12.98	25	0	215
1	2621-010 17.64	2622-010 17.64	25	0	215
1-1/4	2621-012 23.36	2622-012 23.36	20	0	215
1-1/2	2621-015 35.65	2622-015 35.65	20	0	215
2	2621-020 45.06	2622-020 45.06	8	0	215
2-1/2	2621-025 77.14	2622-025 77.14	6	0	214
3	2621-030 138.35	2622-030 138.35	1	4	214