



Valves Product

True Union Ball Valves (Regular Style) & Single Entry Ball Valves

True Union Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Venturied Ends

6 VENTURIED	2322-060C 2116.77	2332-060C 2196.29	1	0	233
--------------------	-----------------------------	-----------------------------	---	---	-----

Threaded Ends

2-1/2	2321-025C 600.57	2331-025C 667.27	1	0	232
3	2321-030C 702.22	2331-030C 780.26	1	0	232
4	2321-040C 1272.43	2331-040C 1413.82	1	0	232

Flanged Ends

1/2	2323-005C 142.08	2333-005C 145.15	6	0	232
3/4	2323-007C 174.18	2333-007C 181.44	5	0	232
1	2323-010C 199.43	2333-010C 211.69	5	0	232
1-1/4	2323-012C 297.94	2333-012C 308.40	2	0	232
1-1/2	2323-015C 327.75	2333-015C 338.62	3	0	232
2	2323-020C 456.06	2333-020C 543.15	2	0	232
2-1/2	2323-025C 808.64	2333-025C 970.62	1	0	232
3	2323-030C 1182.59	2333-030C 1209.54	1	0	232
4	2323-040C 2074.05	2333-040C 2157.00	1	0	232

Flanged Venturied Ends

6 VENTURIED	2323-060C 3214.87	2333-060C 3326.28	1	0	233
--------------------	-----------------------------	-----------------------------	---	---	-----

Single Entry Ball Valves



PVC White – Socket/Threaded Style PVC Gray – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 4" 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 21.07	2421-005W 23.37	2431-005W 25.99	10	120	240
3/4	2411-007W 28.54	2421-007W 29.42	2431-007W 32.69	10	80	240
1	2411-010W 31.15	2421-010W 34.59	2431-010W 38.47	10	0	240
1-1/4	2411-012W 43.31	2421-012W 48.16	2431-012W 53.49	6	0	240
1-1/2	2411-015W 56.14	2421-015W 65.18	2431-015W 70.67	5	0	240
2	2411-020W 63.19	2421-020W 70.15	2431-020W 77.97	5	0	240
3	2411-030W 229.83	2421-030W 285.12	2431-030W 328.73	1	0	240
4	2411-040W 485.84	2421-040W 535.27	2431-040W 581.87	1	0	240

Socket Ends

1/2	2412-005W 21.07	2422-005W 23.37	2432-005W 25.99	10	120	240
3/4	2412-007W 28.54	2422-007W 29.42	2432-007W 32.69	10	80	240
1	2412-010W 31.15	2422-010W 34.59	2432-010W 38.47	10	0	240
1-1/4	2412-012W 43.31	2422-012W 48.16	2432-012W 53.49	6	0	240
1-1/2	2412-015W 56.14	2422-015W 65.18	2432-015W 70.68	5	0	240
2	2412-020W 63.19	2422-020W 70.15	2432-020W 77.97	5	0	240
3	2412-030W 229.83	2422-030W 285.12	2432-030W 328.73	1	0	240

Valves Product
Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 485.84	2422-040W 535.27	2432-040W 581.87	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 23.14	2421-005G 25.65	2431-005G 28.54	10	120	240
3/4	2411-007G 29.15	2421-007G 32.42	2431-007G 36.00	10	80	240
1	2411-010G 34.29	2421-010G 38.06	2431-010G 42.31	10	0	240
1-1/4	2411-012G 47.62	2421-012G 52.94	2431-012G 58.75	6	0	240
1-1/2	2411-015G 59.96	2421-015G 70.23	2431-015G 78.09	5	0	240
2	2411-020G 69.42	2421-020G 77.14	2431-020G 85.67	5	0	240
3	2411-030G 241.96	2421-030G 300.08	2431-030G 346.05	1	0	240
4	2411-040G 511.39	2421-040G 563.46	2431-040G 612.47	1	0	240

Socket Ends

1/2	2412-005G 23.14	2422-005G 25.65	2432-005G 28.54	10	120	240
3/4	2412-007G 29.15	2422-007G 32.42	2432-007G 36.00	10	80	240
1	2412-010G 34.29	2422-010G 38.06	2432-010G 42.31	10	0	240
1-1/4	2412-012G 47.62	2422-012G 52.94	2432-012G 58.75	5	0	240
1-1/2	2412-015G 60.02	2422-015G 70.23	2432-015G 78.09	5	0	240
2	2412-020G 69.42	2422-020G 77.14	2432-020G 85.67	5	0	240
3	2412-030G 241.96	2422-030G 300.08	2432-030G 346.05	1	0	240
4	2412-040G 511.39	2422-040G 563.46	2432-040G 612.47	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit
 (non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options
 and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 23.45	6632-005 26.40	10	120	210
3/4	6622-007 32.00	6632-007 32.77	10	80	210
1	6622-010 34.94	6632-010 39.18	10	0	210
1-1/4	6622-012 52.56	6632-012 60.73	6	0	210
1-1/2	6622-015 62.59	6632-015 69.62	5	0	210
2	6622-020 83.57	6632-020 93.89	8	0	210

Threaded Ends

1/2	6621-005 23.45	6631-005 26.40	10	120	210
3/4	6621-007 32.00	6631-007 32.77	10	80	210
1	6621-010 34.94	6631-010 39.18	10	0	210
1-1/4	6621-012 57.53	6631-012 60.73	6	0	210
1-1/2	6621-015 62.59	6631-015 69.62	5	0	210
2	6621-020 83.57	6631-020 93.89	8	0	210

Flanged Ends

1/2	6623-005 49.40	6633-005 51.91	10	0	210
3/4	6623-007 55.79	6633-007 57.74	10	120	210
1	6623-010 72.69	6633-010 76.60	10	0	210
1-1/4	6623-012 90.78	6633-012 97.39	10	0	210