



Valves Product

True Union Ball Valves (Regular Style) & Single Entry Ball Valves

True Union Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Venturied Ends

6 VENTURIED	2322-060C 2228.18	2332-060C 2311.88	1	0	233
--------------------	------------------------------	------------------------------	---	---	-----

Threaded Ends

2-1/2	2321-025C 632.18	2331-025C 702.39	1	0	232
3	2321-030C 739.18	2331-030C 821.33	1	0	232
4	2321-040C 1339.40	2331-040C 1488.23	1	0	232

Flanged Ends

1/2	2323-005C 149.56	2333-005C 152.79	6	0	232
3/4	2323-007C 183.35	2333-007C 190.99	5	0	232
1	2323-010C 209.93	2333-010C 222.83	5	0	232
1-1/4	2323-012C 313.62	2333-012C 324.63	2	0	232
1-1/2	2323-015C 345.00	2333-015C 356.44	3	0	232
2	2323-020C 480.06	2333-020C 571.74	2	0	232
2-1/2	2323-025C 851.20	2333-025C 1021.71	1	0	232
3	2323-030C 1244.83	2333-030C 1273.20	1	0	232
4	2323-040C 2183.21	2333-040C 2270.53	1	0	232

Flanged Venturied Ends

6 VENTURIED	2323-060C 3384.07	2333-060C 3501.35	1	0	233
--------------------	------------------------------	------------------------------	---	---	-----

Single Entry Ball Valves



PVC White – Socket/Threaded Style PVC Gray – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi

3" - 4" 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 22.18	2421-005W 24.60	2431-005W 27.36	10	120	240
3/4	2411-007W 30.04	2421-007W 30.97	2431-007W 34.41	10	80	240
1	2411-010W 32.79	2421-010W 36.41	2431-010W 40.49	10	0	240
1-1/4	2411-012W 45.59	2421-012W 50.69	2431-012W 56.31	6	0	240
1-1/2	2411-015W 59.09	2421-015W 68.61	2431-015W 74.39	5	0	240
2	2411-020W 66.52	2421-020W 73.84	2431-020W 82.07	5	0	240
3	2411-030W 241.93	2421-030W 300.13	2431-030W 346.03	1	0	240
4	2411-040W 511.41	2421-040W 563.44	2431-040W 612.49	1	0	240

Socket Ends

1/2	2412-005W 22.18	2422-005W 24.60	2432-005W 27.36	10	120	240
3/4	2412-007W 30.04	2422-007W 30.97	2432-007W 34.41	10	80	240
1	2412-010W 32.79	2422-010W 36.41	2432-010W 40.49	10	0	240
1-1/4	2412-012W 45.59	2422-012W 50.69	2432-012W 56.31	6	0	240
1-1/2	2412-015W 59.09	2422-015W 68.61	2432-015W 74.40	5	0	240
2	2412-020W 66.52	2422-020W 73.84	2432-020W 82.07	5	0	240
3	2412-030W 241.93	2422-030W 300.13	2432-030W 346.03	1	0	240

Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 511.41	2422-040W 563.44	2432-040W 612.49	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 24.36	2421-005G 27.00	2431-005G 30.04	10	120	240
3/4	2411-007G 30.68	2421-007G 34.13	2431-007G 37.89	10	80	240
1	2411-010G 36.09	2421-010G 40.06	2431-010G 44.54	10	0	240
1-1/4	2411-012G 50.13	2421-012G 55.73	2431-012G 61.84	6	0	240
1-1/2	2411-015G 63.12	2421-015G 73.93	2431-015G 82.20	5	0	240
2	2411-020G 73.07	2421-020G 81.20	2431-020G 90.18	5	0	240
3	2411-030G 254.69	2421-030G 315.87	2431-030G 364.26	1	0	240
4	2411-040G 538.31	2421-040G 593.12	2431-040G 644.71	1	0	240

Socket Ends

1/2	2412-005G 24.36	2422-005G 27.00	2432-005G 30.04	10	120	240
3/4	2412-007G 30.68	2422-007G 34.13	2432-007G 37.89	10	80	240
1	2412-010G 36.09	2422-010G 40.06	2432-010G 44.54	10	0	240
1-1/4	2412-012G 50.13	2422-012G 55.73	2432-012G 61.84	5	0	240
1-1/2	2412-015G 63.18	2422-015G 73.93	2432-015G 82.20	5	0	240
2	2412-020G 73.07	2422-020G 81.20	2432-020G 90.18	5	0	240
3	2412-030G 254.69	2422-030G 315.87	2432-030G 364.26	1	0	240
4	2412-040G 538.31	2422-040G 593.12	2432-040G 644.71	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 2" 235 psi
Flanged 150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit
(non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options
and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 24.68	6632-005 27.79	10	120	210
3/4	6622-007 33.68	6632-007 34.49	10	80	210
1	6622-010 36.78	6632-010 41.24	10	0	210
1-1/4	6622-012 55.33	6632-012 63.93	6	0	210
1-1/2	6622-015 65.88	6632-015 73.28	5	0	210
2	6622-020 87.97	6632-020 98.83	8	0	210

Threaded Ends

1/2	6621-005 24.68	6631-005 27.79	10	120	210
3/4	6621-007 33.68	6631-007 34.49	10	80	210
1	6621-010 36.78	6631-010 41.24	10	0	210
1-1/4	6621-012 60.56	6631-012 63.93	6	0	210
1-1/2	6621-015 65.88	6631-015 73.28	5	0	210
2	6621-020 87.97	6631-020 98.83	8	0	210

Flanged Ends

1/2	6623-005 52.00	6633-005 54.64	10	0	210
3/4	6623-007 58.73	6633-007 60.78	10	120	210
1	6623-010 76.52	6633-010 80.63	10	0	210
1-1/4	6623-012 95.56	6633-012 102.52	10	0	210