

Valves Product
True Union Ball Valves (Regular Style)



True Union Ball Valves (Regular Style)



Socket/Threaded Style

Flanged Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 2-1/2" - 6" 150 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves assembled with Silicone-Free, Water Soluble Lubricant.

6" Venturied Valves are 4" Ball Valves equipped with 4x6 End Connectors.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

1/2	2329-005 63.41	2339-005 70.56	1	18	230
3/4	2329-007 75.00	2339-007 83.48	1	12	230
1	2329-010 89.35	2339-010 99.53	1	8	230
1-1/4	2329-012 123.60	2339-012 157.76	1	8	230
1-1/2	2329-015 148.92	2339-015 165.27	1	8	230
2	2329-020 196.46	2339-020 216.35	1	4	230

Socket Ends

2-1/2	2322-025 358.78	2332-025 486.15	1	0	230
3	2322-030 473.03	2332-030 525.60	1	0	230
4	2322-040 799.21	2332-040 888.00	1	0	230

Socket Venturied Ends

6 VENTURIED	2322-060 1066.33	2332-060 1161.83	1	0	231
-------------	----------------------------	----------------------------	---	---	-----

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Threaded Ends

2-1/2	2321-025 358.78	2331-025 486.15	1	0	230
3	2321-030 473.03	2331-030 525.60	1	0	230
4	2321-040 799.21	2331-040 888.00	1	0	230

Flanged Ends

1/2	2323-005 90.72	2333-005 96.78	6	0	230
3/4	2323-007 114.93	2333-007 124.99	5	0	230
1	2323-010 139.12	2333-010 149.54	5	0	230
1-1/4	2323-012 163.29	2333-012 181.44	2	0	230
1-1/2	2323-015 205.65	2333-015 223.76	3	0	230
2	2323-020 327.49	2333-020 347.32	2	0	230
2-1/2	2323-025 574.55	2333-025 584.01	1	0	230
3	2323-030 635.02	2333-030 788.42	1	0	230
4	2323-040 1276.81	2333-040 1480.04	1	0	230

Flanged Venturied Ends

6 VENTURIED	2323-060 1862.11	2333-060 1909.82	1	0	231
-------------	----------------------------	----------------------------	---	---	-----

CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

Threaded End Connectors available on request

1/2	2329-005C 83.74	2339-005C 93.07	1	18	232
3/4	2329-007C 105.49	2339-007C 117.23	1	12	232
1	2329-010C 125.56	2339-010C 139.53	1	8	232
1-1/4	2329-012C 199.62	2339-012C 221.87	1	8	232
1-1/2	2329-015C 210.82	2339-015C 234.26	1	8	232
2	2329-020C 281.98	2339-020C 324.14	1	4	232

Socket Ends

2-1/2	2322-025C 600.57	2332-025C 667.27	1	0	232
3	2322-030C 702.22	2332-030C 780.26	1	0	232
4	2322-040C 1272.43	2332-040C 1413.82	1	0	232

Socket Venturied Ends



Valves Product

True Union Ball Valves (Regular Style) & Single Entry Ball Valves

True Union Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Venturied Ends

6 VENTURIED	2322-060C 2116.77	2332-060C 2196.29	1	0	233
--------------------	------------------------------	------------------------------	---	---	-----

Threaded Ends

2-1/2	2321-025C 600.57	2331-025C 667.27	1	0	232
3	2321-030C 702.22	2331-030C 780.26	1	0	232
4	2321-040C 1272.43	2331-040C 1413.82	1	0	232

Flanged Ends

1/2	2323-005C 142.08	2333-005C 145.15	6	0	232
3/4	2323-007C 174.18	2333-007C 181.44	5	0	232
1	2323-010C 199.43	2333-010C 211.69	5	0	232
1-1/4	2323-012C 297.94	2333-012C 308.40	2	0	232
1-1/2	2323-015C 327.75	2333-015C 338.62	3	0	232
2	2323-020C 456.06	2333-020C 543.15	2	0	232
2-1/2	2323-025C 808.64	2333-025C 970.62	1	0	232
3	2323-030C 1182.59	2333-030C 1209.54	1	0	232
4	2323-040C 2074.05	2333-040C 2157.00	1	0	232

Flanged Venturied Ends

6 VENTURIED	2323-060C 3214.87	2333-060C 3326.28	1	0	233
--------------------	------------------------------	------------------------------	---	---	-----

Single Entry Ball Valves



PVC White – Socket/Threaded Style PVC Gray – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi

3" - 4" 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 21.07	2421-005W 23.37	2431-005W 25.99	10	120	240
3/4	2411-007W 28.54	2421-007W 29.42	2431-007W 32.69	10	80	240
1	2411-010W 31.15	2421-010W 34.59	2431-010W 38.47	10	0	240
1-1/4	2411-012W 43.31	2421-012W 48.16	2431-012W 53.49	6	0	240
1-1/2	2411-015W 56.14	2421-015W 65.18	2431-015W 70.67	5	0	240
2	2411-020W 63.19	2421-020W 70.15	2431-020W 77.97	5	0	240
3	2411-030W 229.83	2421-030W 285.12	2431-030W 328.73	1	0	240
4	2411-040W 485.84	2421-040W 535.27	2431-040W 581.87	1	0	240

Socket Ends

1/2	2412-005W 21.07	2422-005W 23.37	2432-005W 25.99	10	120	240
3/4	2412-007W 28.54	2422-007W 29.42	2432-007W 32.69	10	80	240
1	2412-010W 31.15	2422-010W 34.59	2432-010W 38.47	10	0	240
1-1/4	2412-012W 43.31	2422-012W 48.16	2432-012W 53.49	6	0	240
1-1/2	2412-015W 56.14	2422-015W 65.18	2432-015W 70.68	5	0	240
2	2412-020W 63.19	2422-020W 70.15	2432-020W 77.97	5	0	240
3	2412-030W 229.83	2422-030W 285.12	2432-030W 328.73	1	0	240