

Valves Product
True Union Ball Valves (Regular Style)



True Union Ball Valves (Regular Style)



Socket/Threaded Style

Flanged Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 2-1/2" - 6" 150 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves assembled with Silicone-Free, Water Soluble Lubricant.

6" Venturied Valves are 4" Ball Valves equipped with 4x6 End Connectors.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

1/2	2329-005 60.24	2339-005 67.03	1	18	230
3/4	2329-007 71.25	2339-007 79.31	1	12	230
1	2329-010 84.88	2339-010 94.55	1	8	230
1-1/4	2329-012 117.42	2339-012 149.87	1	8	230
1-1/2	2329-015 141.47	2339-015 157.01	1	8	230
2	2329-020 186.64	2339-020 205.53	1	4	230

Socket Ends

2-1/2	2322-025 340.84	2332-025 461.84	1	0	230
3	2322-030 449.38	2332-030 499.32	1	0	230
4	2322-040 759.25	2332-040 843.60	1	0	230

Socket Venturied Ends

6 VENTURIED	2322-060 1013.01	2332-060 1103.74	1	0	231
-------------	---------------------	---------------------	---	---	-----

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Threaded Ends

2-1/2	2321-025 340.84	2331-025 461.84	1	0	230
3	2321-030 449.38	2331-030 499.32	1	0	230
4	2321-040 759.25	2331-040 843.60	1	0	230

Flanged Ends

1/2	2323-005 86.18	2333-005 91.94	6	0	230
3/4	2323-007 109.18	2333-007 118.74	5	0	230
1	2323-010 132.16	2333-010 142.06	5	0	230
1-1/4	2323-012 155.13	2333-012 172.37	2	0	230
1-1/2	2323-015 195.37	2333-015 212.57	3	0	230
2	2323-020 311.12	2333-020 329.95	2	0	230
2-1/2	2323-025 545.82	2333-025 554.81	1	0	230
3	2323-030 603.27	2333-030 749.00	1	0	230
4	2323-040 1212.97	2333-040 1406.04	1	0	230

Flanged Venturied Ends

6 VENTURIED	2323-060 1769.00	2333-060 1814.33	1	0	231
-------------	---------------------	---------------------	---	---	-----

CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

Threaded End Connectors available on request

1/2	2329-005C 79.55	2339-005C 88.42	1	18	232
3/4	2329-007C 100.22	2339-007C 111.37	1	12	232
1	2329-010C 119.28	2339-010C 132.55	1	8	232
1-1/4	2329-012C 189.64	2339-012C 210.78	1	8	232
1-1/2	2329-015C 200.28	2339-015C 222.55	1	8	232
2	2329-020C 267.88	2339-020C 307.93	1	4	232

Socket Ends

2-1/2	2322-025C 570.54	2332-025C 633.91	1	0	232
3	2322-030C 667.11	2332-030C 741.25	1	0	232
4	2322-040C 1208.81	2332-040C 1343.13	1	0	232

Socket Venturied Ends



Valves Product

True Union Ball Valves (Regular Style) & Single Entry Ball Valves

True Union Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Venturied Ends

6 VENTURIED	2322-060C 2010.93	2332-060C 2086.48	1	0	233
--------------------	----------------------	----------------------	---	---	-----

Threaded Ends

2-1/2	2321-025C 570.54	2331-025C 633.91	1	0	232
3	2321-030C 667.11	2331-030C 741.25	1	0	232
4	2321-040C 1208.81	2331-040C 1343.13	1	0	232

Flanged Ends

1/2	2323-005C 134.98	2333-005C 137.89	6	0	232
3/4	2323-007C 165.47	2333-007C 172.37	5	0	232
1	2323-010C 189.46	2333-010C 201.11	5	0	232
1-1/4	2323-012C 283.04	2333-012C 292.98	2	0	232
1-1/2	2323-015C 311.36	2333-015C 321.69	3	0	232
2	2323-020C 433.26	2333-020C 515.99	2	0	232
2-1/2	2323-025C 768.21	2333-025C 922.09	1	0	232
3	2323-030C 1123.46	2333-030C 1149.06	1	0	232
4	2323-040C 1970.35	2333-040C 2049.15	1	0	232

Flanged Venturied Ends

6 VENTURIED	2323-060C 3054.13	2333-060C 3159.97	1	0	233
--------------------	----------------------	----------------------	---	---	-----

Single Entry Ball Valves



PVC White – Socket/Threaded Style PVC Gray – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 4" 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 20.02	2421-005W 22.20	2431-005W 24.69	10	120	240
3/4	2411-007W 27.11	2421-007W 27.95	2431-007W 31.06	10	80	240
1	2411-010W 29.59	2421-010W 32.86	2431-010W 36.55	10	0	240
1-1/4	2411-012W 41.14	2421-012W 45.75	2431-012W 50.82	6	0	240
1-1/2	2411-015W 53.33	2421-015W 61.92	2431-015W 67.14	5	0	240
2	2411-020W 60.03	2421-020W 66.64	2431-020W 74.07	5	0	240
3	2411-030W 218.34	2421-030W 270.86	2431-030W 312.29	1	0	240
4	2411-040W 461.55	2421-040W 508.51	2431-040W 552.78	1	0	240

Socket Ends

1/2	2412-005W 20.02	2422-005W 22.20	2432-005W 24.69	10	120	240
3/4	2412-007W 27.11	2422-007W 27.95	2432-007W 31.06	10	80	240
1	2412-010W 29.59	2422-010W 32.86	2432-010W 36.55	10	0	240
1-1/4	2412-012W 41.14	2422-012W 45.75	2432-012W 50.82	6	0	240
1-1/2	2412-015W 53.33	2422-015W 61.92	2432-015W 67.15	5	0	240
2	2412-020W 60.03	2422-020W 66.64	2432-020W 74.07	5	0	240
3	2412-030W 218.34	2422-030W 270.86	2432-030W 312.29	1	0	240