

Valves Product
True Union Ball Valves (Regular Style)



True Union Ball Valves (Regular Style)



Socket/Threaded Style

Flanged Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 2-1/2" - 6" 150 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves assembled with Silicone-Free, Water Soluble Lubricant.

6" Venturied Valves are 4" Ball Valves equipped with 4x6 End Connectors.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

1/2	2329-005 66.75	2339-005 74.27	1	18	230
3/4	2329-007 78.95	2339-007 87.87	1	12	230
1	2329-010 94.05	2339-010 104.77	1	8	230
1-1/4	2329-012 130.11	2339-012 166.06	1	8	230
1-1/2	2329-015 156.76	2339-015 173.97	1	8	230
2	2329-020 206.80	2339-020 227.74	1	4	230

Socket Ends

2-1/2	2322-025 377.66	2332-025 511.74	1	0	230
3	2322-030 497.93	2332-030 553.26	1	0	230
4	2322-040 841.27	2332-040 934.74	1	0	230

Socket Venturied Ends

6 VENTURIED	2322-060 1122.45	2332-060 1222.98	1	0	231
-------------	----------------------------	----------------------------	---	---	-----

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Threaded Ends

2-1/2	2321-025 377.66	2331-025 511.74	1	0	230
3	2321-030 497.93	2331-030 553.26	1	0	230
4	2321-040 841.27	2331-040 934.74	1	0	230

Flanged Ends

1/2	2323-005 95.49	2333-005 101.87	6	0	230
3/4	2323-007 120.98	2333-007 131.57	5	0	230
1	2323-010 146.44	2333-010 157.41	5	0	230
1-1/4	2323-012 171.88	2333-012 190.99	2	0	230
1-1/2	2323-015 216.47	2333-015 235.54	3	0	230
2	2323-020 344.73	2333-020 365.60	2	0	230
2-1/2	2323-025 604.79	2333-025 614.75	1	0	230
3	2323-030 668.44	2333-030 829.92	1	0	230
4	2323-040 1344.01	2333-040 1557.94	1	0	230

Flanged Venturied Ends

6 VENTURIED	2323-060 1960.12	2333-060 2010.34	1	0	231
-------------	----------------------------	----------------------------	---	---	-----

CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket & Threaded Ends

Threaded End Connectors available on request

1/2	2329-005C 88.15	2339-005C 97.97	1	18	232
3/4	2329-007C 111.04	2339-007C 123.40	1	12	232
1	2329-010C 132.17	2339-010C 146.87	1	8	232
1-1/4	2329-012C 210.13	2339-012C 233.55	1	8	232
1-1/2	2329-015C 221.92	2339-015C 246.59	1	8	232
2	2329-020C 296.82	2339-020C 341.20	1	4	232

Socket Ends

2-1/2	2322-025C 632.18	2332-025C 702.39	1	0	232
3	2322-030C 739.18	2332-030C 821.33	1	0	232
4	2322-040C 1339.40	2332-040C 1488.23	1	0	232

Socket Venturied Ends



Valves Product

True Union Ball Valves (Regular Style) & Single Entry Ball Valves

True Union Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Venturied Ends

6 VENTURIED	2322-060C 2228.18	2332-060C 2311.88	1	0	233
--------------------	------------------------------	------------------------------	---	---	-----

Threaded Ends

2-1/2	2321-025C 632.18	2331-025C 702.39	1	0	232
3	2321-030C 739.18	2331-030C 821.33	1	0	232
4	2321-040C 1339.40	2331-040C 1488.23	1	0	232

Flanged Ends

1/2	2323-005C 149.56	2333-005C 152.79	6	0	232
3/4	2323-007C 183.35	2333-007C 190.99	5	0	232
1	2323-010C 209.93	2333-010C 222.83	5	0	232
1-1/4	2323-012C 313.62	2333-012C 324.63	2	0	232
1-1/2	2323-015C 345.00	2333-015C 356.44	3	0	232
2	2323-020C 480.06	2333-020C 571.74	2	0	232
2-1/2	2323-025C 851.20	2333-025C 1021.71	1	0	232
3	2323-030C 1244.83	2333-030C 1273.20	1	0	232
4	2323-040C 2183.21	2333-040C 2270.53	1	0	232

Flanged Venturied Ends

6 VENTURIED	2323-060C 3384.07	2333-060C 3501.35	1	0	233
--------------------	------------------------------	------------------------------	---	---	-----

Single Entry Ball Valves



PVC White – Socket/Threaded Style PVC Gray – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water

1/2" - 2" 235 psi

3" - 4" 150 psi

Maximum Service Temperature

PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 22.18	2421-005W 24.60	2431-005W 27.36	10	120	240
3/4	2411-007W 30.04	2421-007W 30.97	2431-007W 34.41	10	80	240
1	2411-010W 32.79	2421-010W 36.41	2431-010W 40.49	10	0	240
1-1/4	2411-012W 45.59	2421-012W 50.69	2431-012W 56.31	6	0	240
1-1/2	2411-015W 59.09	2421-015W 68.61	2431-015W 74.39	5	0	240
2	2411-020W 66.52	2421-020W 73.84	2431-020W 82.07	5	0	240
3	2411-030W 241.93	2421-030W 300.13	2431-030W 346.03	1	0	240
4	2411-040W 511.41	2421-040W 563.44	2431-040W 612.49	1	0	240

Socket Ends

1/2	2412-005W 22.18	2422-005W 24.60	2432-005W 27.36	10	120	240
3/4	2412-007W 30.04	2422-007W 30.97	2432-007W 34.41	10	80	240
1	2412-010W 32.79	2422-010W 36.41	2432-010W 40.49	10	0	240
1-1/4	2412-012W 45.59	2422-012W 50.69	2432-012W 56.31	6	0	240
1-1/2	2412-015W 59.09	2422-015W 68.61	2432-015W 74.40	5	0	240
2	2412-020W 66.52	2422-020W 73.84	2432-020W 82.07	5	0	240
3	2412-030W 241.93	2422-030W 300.13	2432-030W 346.03	1	0	240