



Valves Product

Lab Ball Valves & Utility Ball Valves

Lab Ball Valves



Socket/Threaded Valve Only



Valve & Adapters

Valve & Adapters includes:

- Pressure Rating @ 73°F (23°C), Water
1/4" - 3/8" 150 psi
- Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- Rated for Vacuum Service
- 1 - Threaded 1/4" Valve
- 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
- 2 - EPDM or FKM O-rings (AS568-013 size)
- 1 - End Connector Wrench
- 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
- OR -
- 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters

PVC Lab Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002A 28.54	1539-002A 29.83	1	25	218
1/4X3/8T	1529-002 28.54	1539-002 29.83	1	25	218

Valve only Threaded Ends

1/4	1521-002 22.80	1531-002 25.39	50	200	218
3/8	1521-003 32.05	1531-003 35.54	50	200	218

Valve only Socket Ends

1/4	1522-002 22.80	1532-002 25.80	50	200	218
3/8	1522-003 32.05	1532-003 35.54	50	200	218

CPVC Lab Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve & Adapters Threaded Ends

1/4X1/4T	1529-002CA 34.25	1539-002CA 34.92	1	25	219
1/4X3/8T	1529-002C 34.25	1539-002C 34.92	1	25	219

CPVC Lab Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Valve only Threaded Ends

1/4	1521-002C 27.42	1531-002C 30.15	50	200	219
3/8	1521-003C 38.46	1531-003C 36.04	50	200	219

Valve only Socket Ends

1/4	1522-002C 27.42	1532-002C 32.63	50	200	219
3/8	1522-003C 38.46	1532-003C 42.69	50	200	219

Utility Ball Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 6" 150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricant

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
------	---------------	-------------	--------	---------	-----------

PVC White

1/2	2621-005 10.38	2622-005 10.38	50	0	215
3/4	2621-007 12.33	2622-007 12.33	25	0	215
1	2621-010 16.76	2622-010 16.76	25	0	215
1-1/4	2621-012 22.19	2622-012 22.19	20	0	215
1-1/2	2621-015 33.87	2622-015 33.87	20	0	215
2	2621-020 42.81	2622-020 42.81	8	0	215
2-1/2	2621-025 73.28	2622-025 73.28	6	0	214
3	2621-030 131.43	2622-030 131.43	1	4	214
4	2621-040 240.89	2622-040 240.89	1	0	214
6 (Lever Handle)	---	2622-060 388.65	1	0	214

PVC Gray

1/2	2621-005G 10.38	2622-005G 10.38	50	0	215
3/4	2621-007G 12.33	2622-007G 12.33	25	0	215

Valves Product
Utility Ball Valves & CWV Ball Valves



Utility Ball Valves

PVC w/EPDM O-ring Seal (continued)

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
PVC Gray					
1	2621-010G 16.76	2622-010G 16.76	25	0	215
1-1/4	2621-012G 22.19	2622-012G 22.19	20	0	215
1-1/2	2621-015G 33.87	2622-015G 33.87	20	0	215
2	2621-020G 42.81	2622-020G 42.81	8	0	215
2-1/2	2621-025G 73.28	2622-025G 73.28	6	0	214
3	2621-030G 131.43	2622-030G 131.43	1	4	214
4	2621-040G 240.89	2622-040G 240.89	1	0	214
6	---	2622-060G 388.65	1	0	214

CPVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
CPVC					
1/2	2621-005C 13.68	2622-005C 13.68	50	0	216
3/4	2621-007C 17.39	2622-007C 17.39	25	0	216
1	2621-010C 18.89	2622-010C 18.89	25	0	216
1-1/4	2621-012C 26.62	2622-012C 26.62	20	0	216
1-1/2	2621-015C 41.28	2622-015C 41.28	20	0	216
2	2621-020C 51.36	2622-020C 51.36	8	0	216
2-1/2	---	2622-025C 104.54	6	0	216
3	---	2622-030C 152.62	1	4	216

CWV Ball Valves



A Combination of Economy & Quality
- Made in the U.S.A.

For Greater Value in a General
Purpose Cold Water Valve

Pressure Rating @ 73°F (23°C), Water
150 psi

You don't have to go overseas to find an economical general purpose ball valve! Spears® CWV BALL VALVES are produced in the U.S.A. with Spears® high quality construction and NSF® Certified for potable water service. Designed for use with cold water, these PVC valves may be suitable for some applications previously handled by Spears® Utility Valves. Available in IPS sizes 1/2" through 4" with a Full 1-Year Warranty.

CWV PVC Ball Valve

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Threaded Ends					
8721-005	1/2	50	0	204	9.34
8721-007	3/4	25	0	204	11.08
8721-010	1	25	0	204	15.07
8721-012	1-1/4	20	0	204	19.98
8721-015	1-1/2	20	0	204	30.49
8721-020	2	10	0	204	38.54
8721-025	2-1/2	6	0	205	65.96
8721-030	3	1	4	205	118.29
8721-040	4	1	0	205	216.81

CWV PVC Ball Valve

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Socket Ends					
8722-005	1/2	50	0	204	9.34
8722-007	3/4	25	0	204	11.08
8722-010	1	25	0	204	15.07
8722-012	1-1/4	20	0	204	19.98
8722-015	1-1/2	20	0	204	30.49
8722-020	2	10	0	204	38.54
8722-025	2-1/2	6	0	205	65.96
8722-030	3	1	4	205	118.29
8722-040	4	1	0	205	216.81