



Valves Product

Utility Swing Check Valves & True Union Utility Swing Check Valves & Compression Utility Swing Check Valves

Utility Swing Check Valves

PVC Clear Swing Check (continued)

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
2-1/2	S1520C25 75.28	S1520C25F 75.28	S1520C25FSR 104.94	5	0	026
3	S1520C30 83.64	S1520C30F 83.64	S1520C30FSR 134.76	4	0	026
4	S1520C40 112.60	S1520C40F 112.60	S1520C40FSR 165.54	2	0	026
6	S1520C60 232.72	S1520C60F 232.72	S1520C60FSR 295.44	1	0	026
8	S1520C80 388.73	---	---	1	0	026

True Union Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

Full Flow (open) 150 psi
Back Pressure (closed) 75 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings Apply
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720-05 22.13	S1720-05F 22.13	S1720-05FSR 25.34	35	0	026
3/4	S1720-07 22.80	S1720-07F 22.80	S1720-07FSR 27.45	30	0	026
1	S1720-10 23.76	S1720-10F 23.76	S1720-10FSR 30.19	18	0	026
1-1/4	S1720-12 25.01	S1720-12F 25.01	S1720-12FSR 35.31	12	0	026
1-1/2	S1720-15 27.49	S1720-15F 27.49	S1720-15FSR 45.15	10	0	026
2	S1720-20 41.29	S1720-20F 41.29	S1720-20FSR 60.35	10	0	026
2-1/2	S1720-25 68.86	S1720-25F 68.86	S1720-25FSR 98.48	2	0	026
3	S1720-30 87.93	S1720-30F 87.93	S1720-30FSR 139.07	2	0	026
4	S1720-40 118.68	S1720-40F 118.68	S1720-40FSR 171.13	1	0	026

PVC Clear True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720C05 28.65	S1720C05F 28.65	S1720C05FSR 31.87	35	0	026
3/4	S1720C07 29.13	S1720C07F 29.13	S1720C07FSR 33.77	30	0	026
1	S1720C10 31.83	S1720C10F 31.83	S1720C10FSR 38.26	18	0	026
1-1/4	S1720C12 33.53	S1720C12F 33.53	S1720C12FSR 43.82	12	0	026
1-1/2	S1720C15 35.96	S1720C15F 35.96	S1720C15FSR 53.61	10	0	026
2	S1720C20 50.58	S1720C20F 50.58	S1720C20FSR 69.73	10	0	026
2-1/2	S1720C25 83.07	S1720C25F 83.07	S1720C25FSR 112.72	2	0	026
3	S1720C30 95.60	S1720C30F 95.60	S1720C30FSR 146.73	2	0	026
4	S1720C40 127.46	S1720C40F 127.46	S1720C40FSR 180.37	1	0	026

Compression Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water
Full Flow (open) 150 psi
Back Pressure (closed) 75 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shutoff
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500-05	1/2	20	0	026	25.86
S1500-07	3/4	35	0	026	27.21
S1500-10	1	20	0	026	28.36



Compression Utility Swing Check Valves

PVC White Compression End Swing Check (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500-12	1-1/4	12	0	026	33.29
S1500-15	1-1/2	12	0	026	37.15
S1500-20	2	10	0	026	58.59
S1500-25	2-1/2	5	0	026	97.87
S1500-30	3	4	0	026	127.04
S1500-40	4	2	0	026	195.18

PVC Clear Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500C05	1/2	35	0	026	28.43
S1500C07	3/4	35	0	026	30.60
S1500C10	1	20	0	026	31.23
S1500C12	1-1/4	12	0	026	35.06
S1500C15	1-1/2	12	0	026	39.52
S1500C20	2	10	0	026	58.99
S1500C25	2-1/2	5	0	026	98.96
S1500C30	3	4	0	026	144.54
S1500C40	4	2	0	026	199.15

Compression Coupling Nut Wrenches

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
CCW-005	1/2	1	50	299	13.92
CCW-007	3/4	1	50	299	14.16
CCW-010	1	1	50	299	14.76
CCW-012	1-1/4	1	50	299	16.69
CCW-015	1-1/2	1	50	299	18.01
CCW-020 ¹	2	1	50	299	20.13
CCW-030 ²	3	1	25	299	24.76

¹ CCW-20 - Wrench also fits 2-1/2" Coupling Body

² CCW-30 - Wrench also fits 4" Coupling Body

Compression Coupling Nut Wrench Sets

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
CCW-000	Set	1	25	299	116.26

Complete Set of Wrenches, Sizes 1/2" - 3"

Utility Spring Check Valves

(Spring Assisted Swing Check)



Pressure Rating @ 73°F (23°C), Water
 Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi

Maximum Service Temperature
 140°F (60°C)

Temperature/Pressure De-ratings Apply
 EPDM Seat

Stainless Steel Spring Assisted
 (non-adjustable)

General Installation Information: Spring check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Spring Check (Spring Assisted Swing Check)

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1580-05	S1580-05F	S1580-05FSR	20	0	026
	38.31	38.31	41.54			
3/4	S1580-07	S1580-07F	S1580-07FSR	20	0	026
	43.36	43.36	47.97			
1	S1580-10	S1580-10F	S1580-10FSR	20	0	026
	45.17	45.17	51.58			
1-1/4	S1580-12	S1580-12F	S1580-12FSR	12	0	026
	47.02	47.02	57.35			
1-1/2	S1580-15	S1580-15F	S1580-15FSR	12	0	026
	50.06	50.06	67.66			
2	S1580-20	S1580-20F	S1580-20FSR	15	0	026
	52.47	52.47	71.60			
2-1/2	S1580-25	S1580-25F	S1580-25FSR	5	0	026
	93.13	93.13	122.79			
3	S1580-30	S1580-30F	S1580-30FSR	4	0	026
	97.13	97.13	148.26			
4	S1580-40	S1580-40F	S1580-40FSR	2	0	026
	137.85	137.85	190.82			

PVC Clear Spring Check (Spring Assisted Swing Check)

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1580C05	S1580C05F	S1580C05FSR	20	0	026
	39.46	39.46	42.75			
3/4	S1580C07	S1580C07F	S1580C07FSR	20	0	026
	44.68	44.68	49.35			
1	S1580C10	S1580C10F	S1580C10FSR	20	0	026
	46.58	46.58	52.99			
1-1/4	S1580C12	S1580C12F	S1580C12FSR	12	0	026
	48.49	48.49	58.79			
1-1/2	S1580C15	S1580C15F	S1580C15FSR	12	0	026
	51.38	51.38	69.04			
2	S1580C20	S1580C20F	S1580C20FSR	15	0	026
	53.33	53.33	72.44			