



Industrial Swing Check Valves

Industrial Swing Check Valve With Counter Balance

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
PP					
3/4	4423CB-007P 840.96	4433CB-007P 934.37	1	12	113
1	4423CB-010P 1006.02	4433CB-010P 1096.44	1	4	113
1-1/4	4423CB-012P 1026.55	4433CB-012P 1579.65	1	0	113
1-1/2	4423CB-015P 1451.02	4433CB-015P 1948.38	1	0	113
2	4423CB-020P 1563.14	4433CB-020P 1756.31	1	0	113
2-1/2	4423CB-025P 2413.23	4433CB-025P 2964.47	1	0	112
3	4423CB-030P 2936.20	4433CB-030P 3673.63	1	0	112
4	4423CB-040P 3362.38	4433CB-040P 3693.83	1	0	112
6	4423CB-060P 6255.79	4433CB-060P 8027.78	1	0	112
8	4423CB-080P 11420.52	4433CB-080P 12488.34	1	0	112

Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

1/2" - 4" Full Flow (open)	150 psi
Back Pressure (closed)	75 psi
6" - 8" Full Flow (open)	100 psi
Back Pressure (closed)	50 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings
Apply
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves **MUST** be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

Industrial Swing Check Valve Accessory and Repair Kits

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

Industrial Swing Check Valve Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 30.66	SK-VRK-007 37.39	1	10	299
1	SK-ERK-010 40.05	SK-VRK-010 48.84	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 95.77	SK-VRK-015 121.12	1	10	299
2	SK-ERK-020 102.81	SK-VRK-020 125.36	1	10	299
2-1/2	SK-ERK-025 108.73	SK-VRK-025 139.16	1	10	299
3	SK-ERK-030 123.27	SK-VRK-030 150.43	1	10	299
4	SK-ERK-040 134.51	SK-VRK-040 164.01	1	10	299
6	SK-ERK-060 267.33	SK-VRK-060 315.58	1	10	299
8	SK-ERK-080 336.37	SK-VRK-080 408.06	1	10	299

PVC White Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 19.45	S1520-05F 19.45	S1520-05FSR 22.69	35	0	026
3/4	S1520-07 20.08	S1520-07F 20.08	S1520-07FSR 24.69	35	0	026
1	S1520-10 20.92	S1520-10F 20.92	S1520-10FSR 27.35	20	0	026
1-1/4	S1520-12 21.73	S1520-12F 21.73	S1520-12FSR 32.05	12	0	026
1-1/2	S1520-15 23.03	S1520-15F 23.03	S1520-15FSR 40.65	12	0	026
2	S1520-20 35.75	S1520-20F 35.75	S1520-20FSR 54.88	15	0	026
2-1/2	S1520-25 59.46	S1520-25F 59.46	S1520-25FSR 78.60	5	0	026
3	S1520-30 66.08	S1520-30F 66.08	S1520-30FSR 117.21	4	0	026
4	S1520-40 93.56	S1520-40F 93.56	S1520-40FSR 146.54	2	0	026
6	S1520-60 196.60	S1520-60F 196.60	S1520-60FSR 259.32	1	0	026
8	S1520-80 365.22	---	---	1	0	026

PVC Clear Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 26.45	S1520C05F 26.45	S1520C05FSR 29.68	35	0	026
3/4	S1520C07 26.98	S1520C07F 26.98	S1520C07FSR 31.63	35	0	026
1	S1520C10 27.49	S1520C10F 27.49	S1520C10FSR 33.93	20	0	026
1-1/4	S1520C12 28.86	S1520C12F 28.86	S1520C12FSR 39.16	12	0	026
1-1/2	S1520C15 31.37	S1520C15F 31.37	S1520C15FSR 49.02	12	0	026
2	S1520C20 45.17	S1520C20F 45.17	S1520C20FSR 64.28	15	0	026