



**Industrial Swing Check Valves**

**Industrial Swing Check Valve With Counter Balance**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
<b>PP</b>					
3/4	4423CB-007P 798.91	4433CB-007P 887.65	1	12	113
1	4423CB-010P 955.72	4433CB-010P 1041.62	1	4	113
1-1/4	4423CB-012P 975.22	4433CB-012P 1500.67	1	0	113
1-1/2	4423CB-015P 1378.47	4433CB-015P 1850.96	1	0	113
2	4423CB-020P 1484.98	4433CB-020P 1668.49	1	0	113
2-1/2	4423CB-025P 2292.57	4433CB-025P 2816.25	1	0	112
3	4423CB-030P 2789.39	4433CB-030P 3489.95	1	0	112
4	4423CB-040P 3194.26	4433CB-040P 3509.14	1	0	112
6	4423CB-060P 5943.00	4433CB-060P 7626.39	1	0	112
8	4423CB-080P 10849.49	4433CB-080P 11863.92	1	0	112

**Industrial Swing Check Valve Accessory and Repair Kits**

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

**Industrial Swing Check Valve Repair Kits**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 29.13	SK-VRK-007 35.52	1	10	299
1	SK-ERK-010 38.05	SK-VRK-010 46.40	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 90.98	SK-VRK-015 115.06	1	10	299
2	SK-ERK-020 97.67	SK-VRK-020 119.09	1	10	299
2-1/2	SK-ERK-025 103.29	SK-VRK-025 132.20	1	10	299
3	SK-ERK-030 117.11	SK-VRK-030 142.91	1	10	299
4	SK-ERK-040 127.78	SK-VRK-040 155.81	1	10	299
6	SK-ERK-060 253.96	SK-VRK-060 299.80	1	10	299
8	SK-ERK-080 319.55	SK-VRK-080 387.66	1	10	299

**Utility Swing Check Valves**



**Pressure Rating @ 73°F (23°C), Water**

1/2" - 4" Full Flow (open)	150 psi
Back Pressure (closed)	75 psi
6" - 8" Full Flow (open)	100 psi
Back Pressure (closed)	50 psi

**Maximum Service Temperature**  
140°F (60°C)

**Temperature/Pressure De-ratings**  
Apply  
EPDM Seat

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves **MUST** be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White Swing Check**

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 18.48	S1520-05F 18.48	S1520-05FSR 21.56	35	0	026
3/4	S1520-07 19.08	S1520-07F 19.08	S1520-07FSR 23.46	35	0	026
1	S1520-10 19.87	S1520-10F 19.87	S1520-10FSR 25.98	20	0	026
1-1/4	S1520-12 20.64	S1520-12F 20.64	S1520-12FSR 30.45	12	0	026
1-1/2	S1520-15 21.88	S1520-15F 21.88	S1520-15FSR 38.62	12	0	026
2	S1520-20 33.96	S1520-20F 33.96	S1520-20FSR 52.14	15	0	026
2-1/2	S1520-25 56.49	S1520-25F 56.49	S1520-25FSR 74.67	5	0	026
3	S1520-30 62.78	S1520-30F 62.78	S1520-30FSR 111.35	4	0	026
4	S1520-40 88.88	S1520-40F 88.88	S1520-40FSR 139.21	2	0	026
6	S1520-60 186.77	S1520-60F 186.77	S1520-60FSR 246.35	1	0	026
8	S1520-80 346.96	---	---	1	0	026

**PVC Clear Swing Check**

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 25.13	S1520C05F 25.13	S1520C05FSR 28.20	35	0	026
3/4	S1520C07 25.63	S1520C07F 25.63	S1520C07FSR 30.05	35	0	026
1	S1520C10 26.12	S1520C10F 26.12	S1520C10FSR 32.23	20	0	026
1-1/4	S1520C12 27.42	S1520C12F 27.42	S1520C12FSR 37.20	12	0	026
1-1/2	S1520C15 29.80	S1520C15F 29.80	S1520C15FSR 46.57	12	0	026
2	S1520C20 42.91	S1520C20F 42.91	S1520C20FSR 61.07	15	0	026