



Valves Product
Industrial Swing Check Valves & Industrial Swing Check Valve Accessory and Repair Kits & Utility Swing Check Valves

Industrial Swing Check Valves

Industrial Swing Check Valve With Counter Balance

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
PP					
3/4	4423CB-007P 758.96	4433CB-007P 843.27	1	12	113
1	4423CB-010P 907.93	4433CB-010P 989.54	1	4	113
1-1/4	4423CB-012P 926.46	4433CB-012P 1425.64	1	0	113
1-1/2	4423CB-015P 1309.55	4433CB-015P 1758.41	1	0	113
2	4423CB-020P 1410.73	4433CB-020P 1585.07	1	0	113
2-1/2	4423CB-025P 2177.94	4433CB-025P 2675.44	1	0	112
3	4423CB-030P 2649.92	4433CB-030P 3315.45	1	0	112
4	4423CB-040P 3034.55	4433CB-040P 3333.68	1	0	112
6	4423CB-060P 5645.85	4433CB-060P 7245.07	1	0	112
8	4423CB-080P 10307.02	4433CB-080P 11270.72	1	0	112

Industrial Swing Check Valve Accessory and Repair Kits

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

Industrial Swing Check Valve Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 27.67	SK-VRK-007 33.74	1	10	299
1	SK-ERK-010 36.15	SK-VRK-010 44.08	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 86.43	SK-VRK-015 109.31	1	10	299
2	SK-ERK-020 92.79	SK-VRK-020 113.14	1	10	299
2-1/2	SK-ERK-025 98.13	SK-VRK-025 125.59	1	10	299
3	SK-ERK-030 111.25	SK-VRK-030 135.76	1	10	299
4	SK-ERK-040 121.39	SK-VRK-040 148.02	1	10	299
6	SK-ERK-060 241.26	SK-VRK-060 284.81	1	10	299
8	SK-ERK-080 303.57	SK-VRK-080 368.28	1	10	299

Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

1/2" - 4" Full Flow (open)	150 psi
Back Pressure (closed)	75 psi
6" - 8" Full Flow (open)	100 psi
Back Pressure (closed)	50 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings Apply
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves **MUST** be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 17.56	S1520-05F 17.56	S1520-05FSR 20.48	35	0	026
3/4	S1520-07 18.13	S1520-07F 18.13	S1520-07FSR 22.29	35	0	026
1	S1520-10 18.88	S1520-10F 18.88	S1520-10FSR 24.68	20	0	026
1-1/4	S1520-12 19.61	S1520-12F 19.61	S1520-12FSR 28.93	12	0	026
1-1/2	S1520-15 20.79	S1520-15F 20.79	S1520-15FSR 36.69	12	0	026
2	S1520-20 32.26	S1520-20F 32.26	S1520-20FSR 49.53	15	0	026
2-1/2	S1520-25 53.67	S1520-25F 53.67	S1520-25FSR 70.94	5	0	026
3	S1520-30 59.64	S1520-30F 59.64	S1520-30FSR 105.78	4	0	026
4	S1520-40 84.44	S1520-40F 84.44	S1520-40FSR 132.25	2	0	026
6	S1520-60 177.43	S1520-60F 177.43	S1520-60FSR 234.03	1	0	026
8	S1520-80 329.61	---	---	1	0	026

PVC Clear Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 23.87	S1520C05F 23.87	S1520C05FSR 26.79	35	0	026
3/4	S1520C07 24.35	S1520C07F 24.35	S1520C07FSR 28.55	35	0	026
1	S1520C10 24.81	S1520C10F 24.81	S1520C10FSR 30.62	20	0	026
1-1/4	S1520C12 26.05	S1520C12F 26.05	S1520C12FSR 35.34	12	0	026
1-1/2	S1520C15 28.31	S1520C15F 28.31	S1520C15FSR 44.24	12	0	026
2	S1520C20 40.76	S1520C20F 40.76	S1520C20FSR 58.02	15	0	026

Valves Product
Utility Swing Check Valves & True Union Utility Swing Check Valves & Compression Utility Swing Check Valves



Utility Swing Check Valves

PVC Clear Swing Check (continued)

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
2-1/2	S1520C25 67.94	S1520C25F 67.94	S1520C25FSR 94.71	5	0	026
3	S1520C30 75.49	S1520C30F 75.49	S1520C30FSR 121.62	4	0	026
4	S1520C40 101.62	S1520C40F 101.62	S1520C40FSR 149.40	2	0	026
6	S1520C60 210.03	S1520C60F 210.03	S1520C60FSR 266.64	1	0	026
8	S1520C80 350.83	---	---	1	0	026

True Union Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi

Maximum Service Temperature
 140°F (60°C)

Temperature/Pressure De-ratings Apply
 EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720-05 19.97	S1720-05F 19.97	S1720-05FSR 22.87	35	0	026
3/4	S1720-07 20.58	S1720-07F 20.58	S1720-07FSR 24.78	30	0	026
1	S1720-10 21.44	S1720-10F 21.44	S1720-10FSR 27.25	18	0	026
1-1/4	S1720-12 22.57	S1720-12F 22.57	S1720-12FSR 31.86	12	0	026
1-1/2	S1720-15 24.81	S1720-15F 24.81	S1720-15FSR 40.75	10	0	026
2	S1720-20 37.27	S1720-20F 37.27	S1720-20FSR 54.46	10	0	026
2-1/2	S1720-25 62.15	S1720-25F 62.15	S1720-25FSR 88.88	2	0	026
3	S1720-30 79.35	S1720-30F 79.35	S1720-30FSR 125.51	2	0	026
4	S1720-40 107.11	S1720-40F 107.11	S1720-40FSR 154.44	1	0	026

PVC Clear True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720C05 25.86	S1720C05F 25.86	S1720C05FSR 28.77	35	0	026
3/4	S1720C07 26.29	S1720C07F 26.29	S1720C07FSR 30.48	30	0	026
1	S1720C10 28.73	S1720C10F 28.73	S1720C10FSR 34.53	18	0	026
1-1/4	S1720C12 30.26	S1720C12F 30.26	S1720C12FSR 39.55	12	0	026
1-1/2	S1720C15 32.45	S1720C15F 32.45	S1720C15FSR 48.38	10	0	026
2	S1720C20 45.65	S1720C20F 45.65	S1720C20FSR 62.93	10	0	026
2-1/2	S1720C25 74.97	S1720C25F 74.97	S1720C25FSR 101.73	2	0	026
3	S1720C30 86.28	S1720C30F 86.28	S1720C30FSR 132.42	2	0	026
4	S1720C40 115.04	S1720C40F 115.04	S1720C40FSR 162.78	1	0	026

Compression Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi

Maximum Service Temperature
 140°F (60°C)

Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shutoff
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500-05	1/2	20	0	026	23.34
S1500-07	3/4	35	0	026	24.56
S1500-10	1	20	0	026	25.59