



Industrial Swing Check Valves

Industrial Swing Check Valve With Counter Balance

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
PP					
3/4	4423CB-007P 798.91	4433CB-007P 887.65	1	12	113
1	4423CB-010P 955.72	4433CB-010P 1041.62	1	4	113
1-1/4	4423CB-012P 975.22	4433CB-012P 1500.67	1	0	113
1-1/2	4423CB-015P 1378.47	4433CB-015P 1850.96	1	0	113
2	4423CB-020P 1484.98	4433CB-020P 1668.49	1	0	113
2-1/2	4423CB-025P 2292.57	4433CB-025P 2816.25	1	0	112
3	4423CB-030P 2789.39	4433CB-030P 3489.95	1	0	112
4	4423CB-040P 3194.26	4433CB-040P 3509.14	1	0	112
6	4423CB-060P 5943.00	4433CB-060P 7626.39	1	0	112
8	4423CB-080P 10849.49	4433CB-080P 11863.92	1	0	112

Industrial Swing Check Valve Accessory and Repair Kits

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

Industrial Swing Check Valve Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 29.13	SK-VRK-007 35.52	1	10	299
1	SK-ERK-010 38.05	SK-VRK-010 46.40	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 90.98	SK-VRK-015 115.06	1	10	299
2	SK-ERK-020 97.67	SK-VRK-020 119.09	1	10	299
2-1/2	SK-ERK-025 103.29	SK-VRK-025 132.20	1	10	299
3	SK-ERK-030 117.11	SK-VRK-030 142.91	1	10	299
4	SK-ERK-040 127.78	SK-VRK-040 155.81	1	10	299
6	SK-ERK-060 253.96	SK-VRK-060 299.80	1	10	299
8	SK-ERK-080 319.55	SK-VRK-080 387.66	1	10	299

Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

1/2" - 4" Full Flow (open)	150 psi
Back Pressure (closed)	75 psi
6" - 8" Full Flow (open)	100 psi
Back Pressure (closed)	50 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings Apply
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves **MUST** be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 18.48	S1520-05F 18.48	S1520-05FSR 21.56	35	0	026
3/4	S1520-07 19.08	S1520-07F 19.08	S1520-07FSR 23.46	35	0	026
1	S1520-10 19.87	S1520-10F 19.87	S1520-10FSR 25.98	20	0	026
1-1/4	S1520-12 20.64	S1520-12F 20.64	S1520-12FSR 30.45	12	0	026
1-1/2	S1520-15 21.88	S1520-15F 21.88	S1520-15FSR 38.62	12	0	026
2	S1520-20 33.96	S1520-20F 33.96	S1520-20FSR 52.14	15	0	026
2-1/2	S1520-25 56.49	S1520-25F 56.49	S1520-25FSR 74.67	5	0	026
3	S1520-30 62.78	S1520-30F 62.78	S1520-30FSR 111.35	4	0	026
4	S1520-40 88.88	S1520-40F 88.88	S1520-40FSR 139.21	2	0	026
6	S1520-60 186.77	S1520-60F 186.77	S1520-60FSR 246.35	1	0	026
8	S1520-80 346.96	---	---	1	0	026

PVC Clear Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 25.13	S1520C05F 25.13	S1520C05FSR 28.20	35	0	026
3/4	S1520C07 25.63	S1520C07F 25.63	S1520C07FSR 30.05	35	0	026
1	S1520C10 26.12	S1520C10F 26.12	S1520C10FSR 32.23	20	0	026
1-1/4	S1520C12 27.42	S1520C12F 27.42	S1520C12FSR 37.20	12	0	026
1-1/2	S1520C15 29.80	S1520C15F 29.80	S1520C15FSR 46.57	12	0	026
2	S1520C20 42.91	S1520C20F 42.91	S1520C20FSR 61.07	15	0	026



Valves Product

Utility Swing Check Valves & True Union Utility Swing Check Valves & Compression Utility Swing Check Valves

Utility Swing Check Valves

PVC Clear Swing Check (continued)

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
2-1/2	S1520C25 71.52	S1520C25F 71.52	S1520C25FSR 99.69	5	0	026
3	S1520C30 79.46	S1520C30F 79.46	S1520C30FSR 128.02	4	0	026
4	S1520C40 106.97	S1520C40F 106.97	S1520C40FSR 157.26	2	0	026
6	S1520C60 221.08	S1520C60F 221.08	S1520C60FSR 280.67	1	0	026
8	S1520C80 369.29	---	---	1	0	026

True Union Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water

Full Flow (open) 150 psi
Back Pressure (closed) 75 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings Apply
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720-05 21.02	S1720-05F 21.02	S1720-05FSR 24.07	35	0	026
3/4	S1720-07 21.66	S1720-07F 21.66	S1720-07FSR 26.08	30	0	026
1	S1720-10 22.57	S1720-10F 22.57	S1720-10FSR 28.68	18	0	026
1-1/4	S1720-12 23.76	S1720-12F 23.76	S1720-12FSR 33.54	12	0	026
1-1/2	S1720-15 26.12	S1720-15F 26.12	S1720-15FSR 42.89	10	0	026
2	S1720-20 39.23	S1720-20F 39.23	S1720-20FSR 57.33	10	0	026
2-1/2	S1720-25 65.42	S1720-25F 65.42	S1720-25FSR 93.56	2	0	026
3	S1720-30 83.53	S1720-30F 83.53	S1720-30FSR 132.12	2	0	026
4	S1720-40 112.75	S1720-40F 112.75	S1720-40FSR 162.57	1	0	026

PVC Clear True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720C05 27.22	S1720C05F 27.22	S1720C05FSR 30.28	35	0	026
3/4	S1720C07 27.67	S1720C07F 27.67	S1720C07FSR 32.08	30	0	026
1	S1720C10 30.24	S1720C10F 30.24	S1720C10FSR 36.35	18	0	026
1-1/4	S1720C12 31.85	S1720C12F 31.85	S1720C12FSR 41.63	12	0	026
1-1/2	S1720C15 34.16	S1720C15F 34.16	S1720C15FSR 50.93	10	0	026
2	S1720C20 48.05	S1720C20F 48.05	S1720C20FSR 66.24	10	0	026
2-1/2	S1720C25 78.92	S1720C25F 78.92	S1720C25FSR 107.08	2	0	026
3	S1720C30 90.82	S1720C30F 90.82	S1720C30FSR 139.39	2	0	026
4	S1720C40 121.09	S1720C40F 121.09	S1720C40FSR 171.35	1	0	026

Compression Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water
Full Flow (open) 150 psi
Back Pressure (closed) 75 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shutoff
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500-05	1/2	20	0	026	24.57
S1500-07	3/4	35	0	026	25.85
S1500-10	1	20	0	026	26.94