



**Industrial Swing Check Valves**

**Industrial Swing Check Valve With Counter Balance**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
<b>PP</b>					
3/4	4423CB-007P 840.96	4433CB-007P 934.37	1	12	113
1	4423CB-010P 1006.02	4433CB-010P 1096.44	1	4	113
1-1/4	4423CB-012P 1026.55	4433CB-012P 1579.65	1	0	113
1-1/2	4423CB-015P 1451.02	4433CB-015P 1948.38	1	0	113
2	4423CB-020P 1563.14	4433CB-020P 1756.31	1	0	113
2-1/2	4423CB-025P 2413.23	4433CB-025P 2964.47	1	0	112
3	4423CB-030P 2936.20	4433CB-030P 3673.63	1	0	112
4	4423CB-040P 3362.38	4433CB-040P 3693.83	1	0	112
6	4423CB-060P 6255.79	4433CB-060P 8027.78	1	0	112
8	4423CB-080P 11420.52	4433CB-080P 12488.34	1	0	112

**Industrial Swing Check Valve Accessory and Repair Kits**

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

**Industrial Swing Check Valve Repair Kits**

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 30.66	SK-VRK-007 37.39	1	10	299
1	SK-ERK-010 40.05	SK-VRK-010 48.84	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 95.77	SK-VRK-015 121.12	1	10	299
2	SK-ERK-020 102.81	SK-VRK-020 125.36	1	10	299
2-1/2	SK-ERK-025 108.73	SK-VRK-025 139.16	1	10	299
3	SK-ERK-030 123.27	SK-VRK-030 150.43	1	10	299
4	SK-ERK-040 134.51	SK-VRK-040 164.01	1	10	299
6	SK-ERK-060 267.33	SK-VRK-060 315.58	1	10	299
8	SK-ERK-080 336.37	SK-VRK-080 408.06	1	10	299

**Utility Swing Check Valves**



**Pressure Rating @ 73°F (23°C), Water**

1/2" - 4" Full Flow (open)	150 psi
Back Pressure (closed)	75 psi
6" - 8" Full Flow (open)	100 psi
Back Pressure (closed)	50 psi

**Maximum Service Temperature**  
140°F (60°C)

**Temperature/Pressure De-ratings**  
Apply  
EPDM Seat

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves **MUST** be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White Swing Check**

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 19.45	S1520-05F 19.45	S1520-05FSR 22.69	35	0	026
3/4	S1520-07 20.08	S1520-07F 20.08	S1520-07FSR 24.69	35	0	026
1	S1520-10 20.92	S1520-10F 20.92	S1520-10FSR 27.35	20	0	026
1-1/4	S1520-12 21.73	S1520-12F 21.73	S1520-12FSR 32.05	12	0	026
1-1/2	S1520-15 23.03	S1520-15F 23.03	S1520-15FSR 40.65	12	0	026
2	S1520-20 35.75	S1520-20F 35.75	S1520-20FSR 54.88	15	0	026
2-1/2	S1520-25 59.46	S1520-25F 59.46	S1520-25FSR 78.60	5	0	026
3	S1520-30 66.08	S1520-30F 66.08	S1520-30FSR 117.21	4	0	026
4	S1520-40 93.56	S1520-40F 93.56	S1520-40FSR 146.54	2	0	026
6	S1520-60 196.60	S1520-60F 196.60	S1520-60FSR 259.32	1	0	026
8	S1520-80 365.22	---	---	1	0	026

**PVC Clear Swing Check**

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 26.45	S1520C05F 26.45	S1520C05FSR 29.68	35	0	026
3/4	S1520C07 26.98	S1520C07F 26.98	S1520C07FSR 31.63	35	0	026
1	S1520C10 27.49	S1520C10F 27.49	S1520C10FSR 33.93	20	0	026
1-1/4	S1520C12 28.86	S1520C12F 28.86	S1520C12FSR 39.16	12	0	026
1-1/2	S1520C15 31.37	S1520C15F 31.37	S1520C15FSR 49.02	12	0	026
2	S1520C20 45.17	S1520C20F 45.17	S1520C20FSR 64.28	15	0	026



**Valves Product**

**Utility Swing Check Valves & True Union Utility Swing Check Valves & Compression Utility Swing Check Valves**

**Utility Swing Check Valves**

**PVC Clear Swing Check (continued)**

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
2-1/2	S1520C25 75.28	S1520C25F 75.28	S1520C25FSR 104.94	5	0	026
3	S1520C30 83.64	S1520C30F 83.64	S1520C30FSR 134.76	4	0	026
4	S1520C40 112.60	S1520C40F 112.60	S1520C40FSR 165.54	2	0	026
6	S1520C60 232.72	S1520C60F 232.72	S1520C60FSR 295.44	1	0	026
8	S1520C80 388.73	---	---	1	0	026

**True Union Utility Swing Check Valves**



**Pressure Rating @ 73°F (23°C), Water**

Full Flow (open) 150 psi  
Back Pressure (closed) 75 psi

**Maximum Service Temperature**  
140°F (60°C)

Temperature/Pressure De-ratings Apply  
EPDM Seat

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White True Union Swing Check**

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720-05 22.13	S1720-05F 22.13	S1720-05FSR 25.34	35	0	026
3/4	S1720-07 22.80	S1720-07F 22.80	S1720-07FSR 27.45	30	0	026
1	S1720-10 23.76	S1720-10F 23.76	S1720-10FSR 30.19	18	0	026
1-1/4	S1720-12 25.01	S1720-12F 25.01	S1720-12FSR 35.31	12	0	026
1-1/2	S1720-15 27.49	S1720-15F 27.49	S1720-15FSR 45.15	10	0	026
2	S1720-20 41.29	S1720-20F 41.29	S1720-20FSR 60.35	10	0	026
2-1/2	S1720-25 68.86	S1720-25F 68.86	S1720-25FSR 98.48	2	0	026
3	S1720-30 87.93	S1720-30F 87.93	S1720-30FSR 139.07	2	0	026
4	S1720-40 118.68	S1720-40F 118.68	S1720-40FSR 171.13	1	0	026

**PVC Clear True Union Swing Check**

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720C05 28.65	S1720C05F 28.65	S1720C05FSR 31.87	35	0	026
3/4	S1720C07 29.13	S1720C07F 29.13	S1720C07FSR 33.77	30	0	026
1	S1720C10 31.83	S1720C10F 31.83	S1720C10FSR 38.26	18	0	026
1-1/4	S1720C12 33.53	S1720C12F 33.53	S1720C12FSR 43.82	12	0	026
1-1/2	S1720C15 35.96	S1720C15F 35.96	S1720C15FSR 53.61	10	0	026
2	S1720C20 50.58	S1720C20F 50.58	S1720C20FSR 69.73	10	0	026
2-1/2	S1720C25 83.07	S1720C25F 83.07	S1720C25FSR 112.72	2	0	026
3	S1720C30 95.60	S1720C30F 95.60	S1720C30FSR 146.73	2	0	026
4	S1720C40 127.46	S1720C40F 127.46	S1720C40FSR 180.37	1	0	026

**Compression Utility Swing Check Valves**



**Pressure Rating @ 73°F (23°C), Water**  
Full Flow (open) 150 psi  
Back Pressure (closed) 75 psi

**Maximum Service Temperature**  
140°F (60°C)

Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shutoff
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White Compression End Swing Check**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Compression End</b>					
S1500-05	1/2	20	0	026	25.86
S1500-07	3/4	35	0	026	27.21
S1500-10	1	20	0	026	28.36