



**Compression Utility Swing Check Valves**

**PVC White Compression End Swing Check (continued)**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Compression End</b>					
S1500-12	1-1/4	12	0	026	30.05
S1500-15	1-1/2	12	0	026	33.53
S1500-20	2	10	0	026	52.88
S1500-25	2-1/2	5	0	026	88.33
S1500-30	3	4	0	026	114.66
S1500-40	4	2	0	026	176.15

**PVC Clear Compression End Swing Check**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Compression End</b>					
S1500C05	1/2	35	0	026	25.66
S1500C07	3/4	35	0	026	27.62
S1500C10	1	20	0	026	28.19
S1500C12	1-1/4	12	0	026	31.64
S1500C15	1-1/2	12	0	026	35.66
S1500C20	2	10	0	026	53.24
S1500C25	2-1/2	5	0	026	89.31
S1500C30	3	4	0	026	130.44
S1500C40	4	2	0	026	179.73

**Compression Coupling Nut Wrenches**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
CCW-005	1/2	1	50	299	12.56
CCW-007	3/4	1	50	299	12.78
CCW-010	1	1	50	299	13.32
CCW-012	1-1/4	1	50	299	15.07
CCW-015	1-1/2	1	50	299	16.25
CCW-020 <sup>1</sup>	2	1	50	299	18.16
CCW-030 <sup>2</sup>	3	1	25	299	22.34

<sup>1</sup> CCW-20 - Wrench also fits 2-1/2" Coupling Body

<sup>2</sup> CCW-30 - Wrench also fits 4" Coupling Body

**Compression Coupling Nut Wrench Sets**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
CCW-000	Set	1	25	299	104.93

Complete Set of Wrenches, Sizes 1/2" - 3"

**Utility Spring Check Valves**

(Spring Assisted Swing Check)



**Pressure Rating @ 73°F (23°C), Water**  
 Full Flow (open) 150 psi  
 Back Pressure (closed) 75 psi

**Maximum Service Temperature**  
 140°F (60°C)

**Temperature/Pressure De-ratings Apply**  
 EPDM Seat

**Stainless Steel Spring Assisted**  
 (non-adjustable)

**General Installation Information:** Spring check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White Spring Check (Spring Assisted Swing Check)**

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1580-05	S1580-05F	S1580-05FSR	20	0	026
	34.57	34.57	37.49			
3/4	S1580-07	S1580-07F	S1580-07FSR	20	0	026
	39.13	39.13	43.29			
1	S1580-10	S1580-10F	S1580-10FSR	20	0	026
	40.76	40.76	46.55			
1-1/4	S1580-12	S1580-12F	S1580-12FSR	12	0	026
	42.44	42.44	51.76			
1-1/2	S1580-15	S1580-15F	S1580-15FSR	12	0	026
	45.18	45.18	61.07			
2	S1580-20	S1580-20F	S1580-20FSR	15	0	026
	47.36	47.36	64.62			
2-1/2	S1580-25	S1580-25F	S1580-25FSR	4	0	026
	84.05	84.05	110.82			
3	S1580-30	S1580-30F	S1580-30FSR	4	0	026
	87.66	87.66	133.81			
4	S1580-40	S1580-40F	S1580-40FSR	2	0	026
	124.41	124.41	172.22			

**PVC Clear Spring Check (Spring Assisted Swing Check)**

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1580C05	S1580C05F	S1580C05FSR	20	0	026
	35.62	35.62	38.58			
3/4	S1580C07	S1580C07F	S1580C07FSR	20	0	026
	40.33	40.33	44.54			
1	S1580C10	S1580C10F	S1580C10FSR	20	0	026
	42.04	42.04	47.82			
1-1/4	S1580C12	S1580C12F	S1580C12FSR	12	0	026
	43.77	43.77	53.06			
1-1/2	S1580C15	S1580C15F	S1580C15FSR	12	0	026
	46.37	46.37	62.31			
2	S1580C20	S1580C20F	S1580C20FSR	15	0	026
	48.13	48.13	65.38			



**Utility Spring Check Valves**

**PVC Clear Spring Check (Spring Assisted Swing Check)**

(continued)

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
2-1/2	S1580C25 86.66	S1580C25F 86.66	S1580C25FSR 113.39	5	0	026
3	S1580C30 90.24	S1580C30F 90.24	S1580C30FSR 179.55	4	0	026
4	S1580C40 128.21	S1580C40F 128.21	S1580C40FSR 176.01	2	0	026

**True Union Utility Spring Check Valves**

Pressure Rating @ 73°F (23°C), Water  
Full Flow (open) 150 psi  
Back Pressure (closed) 75 psi

Maximum Service Temperature  
140°F (60°C)

Temperature/Pressure De-ratings Apply



EPDM Seat

Stainless Steel Spring Assisted  
(non-adjustable)

**General Installation Information:** Spring check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White True Union Spring Check (Spring Assisted Swing Check)**

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1780-05 45.97	S1780-05F 45.97	S1780-05FSR 48.88	20	0	026
3/4	S1780-07 52.15	S1780-07F 52.15	S1780-07FSR 56.34	30	0	026
1	S1780-10 54.35	S1780-10F 54.35	S1780-10FSR 60.13	18	0	026
1-1/4	S1780-12 56.61	S1780-12F 56.61	S1780-12FSR 65.86	12	0	026
1-1/2	S1780-15 60.31	S1780-15F 60.31	S1780-15FSR 76.25	10	0	026
2	S1780-20 62.79	S1780-20F 62.79	S1780-20FSR 80.03	10	0	026
2-1/2	S1780-25 112.06	S1780-25F 112.06	S1780-25FSR 138.77	2	0	026
3	S1780-30 116.91	S1780-30F 116.91	S1780-30FSR 163.04	2	0	026
4	S1780-40 165.88	S1780-40F 165.88	S1780-40FSR 213.73	1	0	026

**PVC Clear True Union Spring Check (Spring Assisted Swing Check)**

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1780C05 47.42	S1780C05F 47.42	S1780C05FSR 50.34	20	0	026
3/4	S1780C07 53.78	S1780C07F 53.78	S1780C07FSR 57.97	30	0	026
1	S1780C10 56.02	S1780C10F 56.02	S1780C10FSR 61.85	18	0	026
1-1/4	S1780C12 58.33	S1780C12F 58.33	S1780C12FSR 67.59	12	0	026
1-1/2	S1780C15 61.85	S1780C15F 61.85	S1780C15FSR 78.12	10	0	026
2	S1780C20 63.65	S1780C20F 63.65	S1780C20FSR 81.93	10	0	026
2-1/2	S1780C25 115.54	S1780C25F 115.54	S1780C25FSR 142.31	2	0	026
3	S1780C30 120.51	S1780C30F 120.51	S1780C30FSR 166.64	2	0	026
4	S1780C40 171.03	S1780C40F 171.03	S1780C40FSR 218.87	1	0	026

**Diaphragm Check Valves**



Pressure Rating @ 73°F (23°C), Water  
Full Flow (open) = 150 psi  
Back Pressure (closed) = 100 psi  
Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)  
Temperature/Pressure De-ratings Apply  
Santoprene™ TPE Seat

**PVC Diaphragm Check Valves - Socket**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
6562-007	3/4	15	0	004	93.78

**PVC Diaphragm Check Valves - Thread**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
6561-007	3/4	15	0	004	93.78

**CPVC Diaphragm Check Valves - Socket**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
6562-007C	3/4	15	0	004	123.16